MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, SCREW THREADS, HIGH DENSITY, HIGH SHOCK, SHIPBOARD, CRIMP CONTACTS RECEPTACLE, WALL MOUNTING, CLASSES D AND DS

This specification sheet is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the accessories described herein shall consist of this document and the latest issue of specification MIL-C-28840.




FIGURE 1. Dimensions and configuration

(B) Denotes change

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 20261O-20T19:36Z
Check the source to verify that this is the current version before use.

(B)

TABLE I. Dimensions and configuration

1/ DESIGNATOR	N DIA. MAX.	O REF. MTG. HOLE	R T.P. ℄ TO ℄	S	T	FOR INSERT ARRANGEMENT MIL-STD-1698
A (11)	.750 (19.05)	.812 (20.62)	.750 (19.05)	1.043 (26.49) 1.003 (25.48)	.130 (3.30) .115 (2.92)	Section 90
B (13)	.875 (22.22)	.937 (23.80)	.843 (21.41)	1.158 (29.41) 1.118 (28.40)	.130 (3.30) .115 (2.92)	Section 10
C (15)	1.062 (26.97)	1.124 (28.55)	.968 (24.59)	1.278 (32.46) 1.238 (31.45)	.130 (3.30) .115 (2.92)	Section 20
D (17)	1.125 (28.58)	1.187 (30.15)	1.015 (25.78)	1.403 (35.64) 1.363 (34.62)	.130 (3.30) .115 (2.92)	Section 30
E (19)	1.312 (33.32)	1.374 (34.90)	1.140 (28.96)	1.528 (38.81) 1.488 (37.80)	.130 (3.30) .115 (2.92)	Section 40
F (23)	1.500 (38.10)	1.562 (39.67)	1.281 (32.54)	1.738 (44.15) 1.698 (43.13)	.130 (3.30) .115 (2.92)	Section 50
G (25)	1.625 (41.28)	1.687 (42.85)	1.392 (35.36)	1.838 (46.69) 1.798 (45.67)	.157 (3.99) .142 (3.61)	Section 60
H (29)	1.812 (46.02)	1.874 (47.60)	1.568 (39.83)	2.158 (54.81) 2.118 (53.80)	.157 (3.99) .142 (3.61)	Section 70
J (33)	2.000 (50.80)	2.062 (52.37)	1.734 (44.04)	2.348 (59.64) 2.308 (58.62)	.183 (4.65) .168 (4.27)	Section 80

NOTES

1. Shell sizes are provided within parentheses for information and are not a part of the designator.
2. Dimensions are in inches.
3. Metric equivalents (to the Nearest .01 mm) are given for general information only and are based upon 1.0 inch equals 25.4 mm.
4. Dimensions apply after plating.
5. Designator of backshell size within each shell size.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T19:36Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Classes: D and DS

Insert Arrangements: See the section of MIL-STD-1698 corresponding to desired shell size.

Contacts: Style P or S crimp type.

Shell polarization: 1 thru 6, key position


Marking: Part number on shell.

Mating counterpart: Plug connectors specified in MIL-C- 28840 /16,17,18,19,26 28 & 29

Installation and removal tool: As specified in MIL-I-81969/33 and /34

(B) A backshell shall be used to meet moisture and water pressure requirements.

EXAMPLE OF PART NUMBER M28840 /10 A G 1 P 1



CLASSES	CODE LETTER
D	A
DS	B

Preparing activity:
Navy - EC
(Project 5935-N174-9)

Review activities:
Navy - SH

User activities:
Navy - OS

Source: https://assist.dla.mil -- Downloaded: 20261O-20T19:36Z
Check the source to verify that this is the current version before use.