MIL-B-13831J(ME)
15 July 1985
SUPERSEDING
MIL-B-13831H(ME)
19 July 1983

MILITARY SPECIFICATION

BOAT, RECONNAISSANCE, PNEUMATIC: 3-MAN

This specification is approved for use by the USA Belvoir Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 3-man, pneumatic, reconnaissance boat complete with paddles, pump, repair items, and carrying case.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-C-14505	- Cloth, Coated, Polychloroprene: (for Pneumatic Floating Equipment).
MIL-G-20241	- Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-P-23377	- Primer Coatings: Epoxy-Polyamide, Chemical and Solvent Resistant.
MIL-S-81733	- Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-889	- Dissimilar Metals.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13211E3061	- Boat Assembly, Reconnaissance, Pneumatic: 3-Man.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 751	- Standard Methods for Testing Coated Fabrics.
D 3951	- Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The boat, paddles, pump, repair kit, and carrying case shall be in accordance with TA13211E3061 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the boat assembly. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.8 and 6.9).

3.3.1 Material deterioration and control. The boat shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the boat may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as a coat of epoxy primer conforming to MIL-P-23377, or corrosion inhibiting sealant conforming to MIL-S-81733, type IV for fraying surface application or chromate tape conforming to MIL-G-20241. Protection against any galvanic corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or designated representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

3.3.2 Coating compound. The coating compound shall be as specified in MIL-C-14505.

3.3.3 Coated cloth. The uncured coated cloth used in fabrication of the boat shall conform to MIL-C-14505, class as specified on the drawings.

3.3.4 Gum sheeting and strip. Gum sheeting and strip used in fabrication of the boat shall be cut from gum sheeting made from the coating compound specified in 3.3.2. Thickness shall be not less than 0.018 inch, nor more than 0.026 inch; width as specified on the drawings.

3.4 Weight. The weight of the finished boat complete with pump, paddles, repair kit items, and carrying case shall be not more than 43 pounds. The weight of packaging material for the repair kit items and for the pump shall not be included. The weight of each assembled paddle shall be not more than 24 ounces.

3.5 Flotation tube. The flotation tube shall be fabricated from the uncured coated cloth specified in 3.3.3 with the warp threads running circumferentially around the tube. Only one longitudinal seam shall be permitted in each section of the tube. Each tube compartment shall withstand an air pressure of 6 pounds per square inch (psi) for a period of 10 minutes without any evidence of failure such as seam slippage, rupture, or permanent distortion. With all four compartments of the tube inflated to an air pressure of 3 psi, the final pressure reading after a period of 24 hours shall be not less than 2.0 psi. With alternate compartments inflated to an air pressure of 3 psi for a period of 4 hours, the inflated compartments shall retain a pressure of not less than 2.0 psi. Repeated foldings of the boat shall not damage the tube, and the pressure shall not drop more than 0.2 psi below the final pressure reading obtained during the 24-hour air retention test (see 4.5.2).

3.6 Floor. The floor shall be fabricated from the coated cloth specified in 3.3.3 and shall be an individual air-retaining envelope. The floor shall withstand an air pressure of 5 psi for a period of 10 minutes without evidence of failure such as rupture, floor beam separation, or permanent distortion. When inflated to an air pressure of 3 psi for a period of 24 hours, the final pressure reading shall be not less than 2.0 psi. Repeated foldings of the boat shall not damage the floor, and the pressure shall not drop more than 0.2 psi below the final pressure reading obtained during the 24-hour air retention test (see 4.5.2).

3.7 Towrope. The nylon towrope shall be attached to the D-ring with a bowline knot; the free end shall be securely lashed back onto the rope with not less than 10 turns of 40-pound nylon thread. The outer end of the towrope shall be backspliced with not less than four tucks to prevent fraying.

3.8 Lifeline. A one-piece nylon cord shall be installed starting at the bow D-ring encircling the boat and ending back at the bow D-ring. The lifeline shall be tied to the bow D-ring with bowline knots; the free ends shall be securely lashed back onto the cord with not less than 10 turns of 40-pound nylon thread.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

The cord shall be attached to all intermediate D-rings by means of figure 8 knots. The lifeline between any two attachment points shall be in the form of a catenary. The length of the lifeline between attachment points as shown on the drawings shall be increased 5 to 7 percent of the distance between attachment points.

3.9 Attachment patch assemblies. When tested as specified in 4.5.2.4, the patch assemblies shall withstand the following loads without any evidence of failure or separation of the patches from the boat.

Assemblies	Pull in pounds
Towrope patch	500
Lifeline patch	200

3.10 Seams. All seams shall be water- and airtight to the extent specified herein and shall develop the full strength of the coated cloth when tested as specified in 4.5.2.7. Seam overlap shall be not less than 1 inch. Seams subjected to a deadweight load of 40 pounds per inch of seam width at a temperature of 200° F shall show no signs of slippage after 24 hours (see 4.5.2.7).

3.11 Fabrication. All gum strips and tape splices shall overlap not less than 1/4 inch. The boat, less the towrope and lifeline, shall be vulcanized as a complete unit in a pressure-type autoclave. Partial curing of the floor and flotation tube separately will be permitted provided that the final vulcanization process does not conflict with other requirements of this specification. All exposed edges shall be covered with 3/4-inch-wide gum strips, except as otherwise noted on the drawings. Each air compartment of the flotation tube and the floor shall be fitted with inflation-deflation valves as shown on the drawings. When inflated to 3 psi and placed on a horizontal surface, warpage or twisting of the completed boat shall not exceed 1-1/2 inches, measured vertically from any one corner. Swashing of the inner walls of the inflatable air compartment with latex or any other liquid sealing compound shall not be permitted either before or after vulcanization. Fabrication of the boat shall insure its watertightness to the degree that when the completed boat is inflated and placed in water and loaded with 600 pounds (distributed) for a period of 1 hour, the boat shall not leak in excess of 1 quart of water (see 4.5.2.6).

3.11.1 Optional fabrication. The following construction may be used in lieu of that shown on the drawings provided the weight of the completed boat with pump, paddles, repair kit items and carrying case is not more than 43 pounds, and all other specification requirements are met:

a. Chafers for the tube and skeg may be multipiece construction to eliminate wrinkling and to permit material to conform to the curvature of the boat.
b. Coated fabric conforming to MIL-C-14505, class 11, may be substituted for class 3 fabric.

3.12 Repair patches. The first article boat shall contain no repair patches. For production boats, a maximum of three patches shall be allowed for any boat.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

Patches shall be prepared from coated cloth conforming to MIL-C-14505, class 11, applied with adhesive, and vulcanized with local application of heat and pressure. Patched boats shall not exceed 20 percent of boats submitted for acceptance at one time. The edge of any repair patch shall extend not less than 2 inches beyond the extremity of the defect. Gum strips, coating compound or adhesive shall be used on the periphery of all applied patches to sealcoat the edges. Covering or overlapping of patches shall not be permitted. Any applied patch shall not adversely affect the strength or serviceability of the boat, and any patched boat shall conform to requirements of this specification.

3.13 Cemented surfaces. Surfaces to be cemented shall be wiped clean with a cleaning solvent before adhesive is applied. The surfaces shall be free from grease, grit and dirt, oil, excess material used in fabrication, and any other foreign materials that could harmfully affect the application of adhesive and the bonding of the cemented surfaces.

3.13.1 Nonadhering cemented surfaces. All gum strips and tape splices shall be totally adhering. Any isolated nonadhering cemented surface of the gum strips or tapes shall be reapplied by recementing with an appropriate air curing cement.

3.14 Workmanship. The finished boat complete with all specified bonded and attached components shall show no evidence of bubbles, bulges, ripples, folds, wrinkles, puckers, defective or loose components, or any other manufacturing defects which could impair serviceability. All metal parts shall be free of sharp edges and corners except where sharp edges or corners are necessary and not detrimental to safety.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and mateials used are manufactured, examined and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection comparison (see 4.6).
d. Inspection of packaging (see 4.7).

4.3 First article inspection.

4.3.1 Examination. The boat, carrying case, pump, repair kit, and paddles shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The boat shall be tested as specified in 4.5.2.1 through 4.5.2.7. Samples for the lap seam test shall be fabricated identically to the seams in the boat from cloth representative of the boat and vulcanized simultaneously and identically to the boats represented. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling for tests.

4.4.1.1 Sample size. One sample boat shall be selected at random from each lot of 40 boats or fraction thereof submitted for acceptance at one time.

4.4.1.2 Lap seam. Samples for the lap seam tests shall be fabricated identically to seams in the boat, except the width of overlap shall not exceed the minimum overlap used in any seam in the boat, from cloth representative of the boat, and vulcanized identically to the boats represented. The sample shall contain not less than 13 inches of linear seam and shall contain 3 inches of coated fabric extending on each side of the overlap. One lap seam sample shall be prepared and furnished for test for each 40 boats or fraction thereof submitted for acceptance at one time.

4.4.2 Examination. Each boat, carrying case, pump, paddles, and repair kit items shall be examined for the defects specified in 4.5.1. The presence of one or more defects shall be cause for rejection.

4.4.3 Tests.

4.4.3.1 Individual. Each boat shall be tested as specified in 4.5.2.1 through 4.5.2.3. Failure of any test shall be cause for rejection. Rejected boats may be repaired and resubmitted for test and acceptance at the contractor's expense. Repairs shall conform to the requirements specified in 3.12. Reworking or revulcanization shall not adversely affect the strength or serviceability of the boat.

4.4.3.2 Samples.

4.4.3.2.1 Pull resistance. Samples selected in accordance with 4.4.1.1 shall be tested as specified in 4.5.2.4. Failure of any test shall be cause for rejection of the lot represented by the sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

4.4.3.2.2 Lap seam tests. Samples selected and fabricated in accordance with 4.4.1.2 shall be tested as specified in 4.5.2.7. Failure of any test specimen prepared from the samples shall be cause for rejection of the lot represented by the samples.

4.5 Inspection procedure.

4.5.1 Examination. The boat, carrying case, pump, repair kit items, and paddles shall be examined for the following defects:

101. Materials not as specified.
102. Materials are not corrosion resistant or treated to be made corrosion resistant for the applicable storage and operating environment.
103. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
104. Contractor does not have documentation available for identification of material, material finishes or treatments.
105. Nonconformance to dimensions shown on drawings.
106. Parts incorrect, missing, not correctly attached, or damaged.
107. Weight of boat and related items more than 43 pounds.
108. Fabric lapped less than 1 inch at seams.
109. Gum strip and tape splice lapped less than 1/4 inch.
110. Warp threads not circumferentially around the tube.
111. Warp or twist in boat exceeds 1-1/2 inches.
112. Fabrication of carrying case not as specified.
113. Stitching inadequate or defective.
114. Fittings and fastening devices not as specified.
115. Hardware finish incorrect.
116. Installation of inflation valves not as specified.
117. Weight of complete paddle more than 24 ounces.
118. Paddle-locking mechanism inoperable.
119. Repair kit or items therein missing or incorrect.
120. Rope work not as specified.
121. More than three patches on any one production boat or any patches on a first article boat.
122. The percentage of patched boats in each lot submitted for acceptance at one time shall be determined. Nonconformance to 3.12 shall be cause for rejection.
123. Repair patches not as specified.
124. Workmanship not as specified.
125. Coating compound not as specified.
126. Coated cloth not as specified.
127. Gum sheeting and strip not as specified.
128. Towrope missing or not as specified.
129. Lifeline missing or not as specified.
130. Cemented surfaces not as specified.
131. Nonadhering cemented surfaces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

4.5.2 Tests.

4.5.2.1 Overpressure. Inflate each compartment of the flotation tube to a pressure of 6 psi. Inflate the floor to a pressure of 5 psi. Nonconformance to 3.5 or 3.6 shall constitute failure of this test.

4.5.2.2 Air retention. Inflate all compartments of the completed boat with air to a pressure of 3 psi. After not less than 2 hours, adjust the pressure in all compartments to the 3 psi as specified above. After this adjustment, seal the valve caps in such a manner that the boat cannot be inflated without breaking the seals. After 24 additional hours, take a final pressure reading of each compartment. Adjust the final pressure reading to compensate for any temperature and barometric pressure changes during the test period. The correction for any temperature change shall be calculated in accordance with 4.5.2.2.1; for any barometric pressure change, the correction shall be in accordance with 4.5.2.2.2. Nonconformance to 3.5 or 3.6 shall constitute failure of this test.

4.5.2.2.1 Temperature correction. For each degree Fahrenheit rise in temperature, 0.03 psig shall be subtracted from the final pressure reading. For each degree Fahrenheit drop in temperature, 0.03 psig shall be added to the final pressure reading. The corresponding correction per degree centigrade is 0.056 psig.

4.5.2.2.2 Barometric pressure correction. For each 0.1 inch of mercury rise in barometric pressure, 0.049 psig shall be subtracted from the final temperature corrected reading. For each 0.1 inch of mercury drop in barometric pressure, 0.049 psig shall be added to the final temperature corrected reading.

4.5.2.3 Bulkheads. After successful completion of the air tests in 4.5.2.1 and 4.5.2.2, inflate the bow and stern compartments of the flotation tube to an air pressure of 3 psi, with the valves in the central compartments left open. After not less than 1 hour, adjust the pressure to 3 psi and seal the valves as specified in 4.5.2.2. After 4 additional hours, take a final pressure reading of the inflated compartments. Adjust the final readings to compensate for temperature and barometric pressure changes as specified in 4.5.2.2. Nonconformance to 3.5 shall constitute failure of this test.

4.5.2.4 Pull resistance. Apply separately a pull of 500 pounds to the towrope patch and 200 pounds to each of two lifeline patches. Pulls shall be applied through the D-rings. The pull on the towrope patch shall be in the direction of the towrope (forward). The pull on all other patches shall be normal to the plane of the patch. Position the boat so that test loads will not distort the boat. Hold each load for not less than 7 seconds and afterwards examine the attachment patch assembly for defects. Nonconformance to 3.9 shall constitute failure of these tests.

4.5.2.5 Folding and air retest. Boat(s) shall be tested as follows: deflate all compartments, fold boat, and place in carrying case; remove boat from carrying case, inflate all tube compartments and floor to 3 psi. Repeat this cycle

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

25 times. After completion of the folding cycles, inflate and test for air retention as specified in 4.5.2.2. Nonconformance to 3.5 or 3.6 shall constitute failure of this test.

4.5.2.6 Watertightness. Inflate all compartments of the boat to a pressure of 3 psi. Place the boat in water of at least 2 feet in depth and of sufficient breadth to allow the boat to float unobstructedly. Place in the boat 600 pounds of weighted material (filled sandbags or other noninjurious material) that shall distribute the load to the entire floor as evenly as practical. If porous, water-absorbing material is used for this test, such as sandbags, the material shall be wrapped with plastic/polyethylene sheeting to prevent absorption of any water that possibly leaks into the boat during this test. After the loaded boat has been in the water for 1 hour, remove the 600 pounds of material from the boat and measure whatever water that leaked into the boat. Nonconformance to 3.11 shall constitute failure of this test.

4.5.2.7 Lap seam strength. Prepare six specimens from the samples selected as specified in 4.4.1.2 by cutting the seam sample into 2-inch widths. Test three specimens to failure in accordance with ASTM D 751, paragraph concerning seam strength. Rupture of any specimen at the seam before rupture of the coated cloth shall constitute failure of this test. If the specimens pass the above test, test the remaining three specimens as follows: subject each specimen to a tensile load (deadweight) of 80 pounds (40 pounds per inch width) at a temperature of 200° F for a period of 24 hours and examine the seam for slippage. Nonconformance to 3.10 shall constitute failure of this test.

4.6 Inspection comparison. The Government may select boat assemblies at any time during the contract production period and subject these boat assemblies to the examination specified in 4.5.1 and the tests specified in 4.5.2 to determine conformance to the requirements of this specification. The inspection will be performed by the Government, at a site selected by the Government, on boat assemblies selected at random from those which have been accepted by the Government and will not include the previously inspected first article boat assemblies. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison, and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.6.1 Inspection failure. Failure of an inspection comparison boat assembly to meet any requirement specified herein during and as a result of the examination and tests specified in 4.6 shall be cause for rejection of the inspection comparison boat assembly and shall be cause for refusal by the Government to continue acceptance of production boat assemblies until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on boat assemblies previously accepted and produced under the contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all boat

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

assemblies accepted prior to the completion of inspection comparison are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.7 Inspection of packaging.

4.7.1 Quality conformance inspection of pack.

4.7.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.7.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.7.1.3 Examination. Samples selected in accordance with 4.7.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

132.	Repair kit items and instruction sheet not in the repair kit pocket for level A or commercial.
133.	Pump and paddles not in their compartments for level A or commercial.
134.	Powdered soapstone or talc not applied to the boat before folding for level A or commercial.
135.	Boat and all components not contained in the carrying case level A or commercial.
136.	Shipping containers not as specified for level A or B.
137.	The gross weight of shipping container exceeds 200 pounds for level A.
138.	Strapping not as specified for level A.
139.	The gross weight or size exceeds the limitation of the box specification for level B.
140.	Fiberboard boxes not waterproof sealed and reinforced as specfiied for level B.
141.	Marking illegible, incorrect, or incomplete for level A, level B, or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each pump with hose; patches contained in the contractor's box or a box conforming to PPP-B-566, variety, style, type, and class optional; each repair kit item, except the vulcanizing fluid and repair instructions sheet, shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3. The repair kit items shall be placed in the repair kit pocket in a manner to prevent damage to the air inflatable tube or floor. The pump with hose and the paddles shall be placed in their respective compartments in the carrying case. The towline shall be coiled or hanked. The boat shall be dusted inside and outside with soapstone or talc, carefully folded, and placed in the carrying case, and the carrying case shall be secured with the webbing straps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. Each complete boat shall be preserved in accordance with ASTM D 3951. Specifically the repair kit items, the pump with hose, and the paddles shall be placed in their respective pocket or compartment. The boat shall be dusted inside and outside with soapstone or talc, folded, placed in the carrying case, and the case secured with the straps.

5.2 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

5.2.1 Level A. The carrying cases containing complete boats shall be packed in a close fitting box conforming to PPP-B-601, overseas type, style optional. The gross weight of each box shall not exceed 200 pounds. The boxes shall be closed and strapped in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, finish B, size as applicable.

5.2.2 Level B. The carrying cases containing complete boats shall be packed in a close-fitting box conforming to PPP-B-640, class 2, style optional; or PPP-B-636, V3c, V11c, V13c, V15c, style optional. The gross weight or size shall not exceed the limitation of the applicable box specification. The box shall be waterproof sealed and reinforced with tape in accordance with the appendix to the box specification.

5.2.3 Commercial. The carrying cases, containing complete boats, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129, and in addition, each package for the repair kit items shall be marked with the following information:

Nomanclature
Manufacturer's Identification
NSN
Contract No.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951, and in addition, each package for the repair kit items shall be marked as specified in 5.3.1. Weight and cube data shall be marked on each shipping container.

6. NOTES

6.1 Intended use. The boat is intended to carry a crew of three men with individual equipment on reconnaissance missions across or along streams.

6.2 Ordering data. Acquisition documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.
b. When a first article is required for inspection and approval and the number of units required (see 3.2).
c. Degree of preservation and packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the items should be an initial production unit. The first article should consist of 1 unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the document's first article.

6.4 International standardization. Certain provisions of this specification are the subject of International Quadripartite (ABCA) Standardization Agreement 91. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

6.5 Pump drawings. The contracting officer should furnish drawings (per DL13211E9598) for the pump.

6.6 Data requirements. The contracting officer should include requirements for such data as the contractor's maintenance and operation manual to be furnished with each boat.

6.7 Provisioning. The contracting officer should include provisioning requirements for repair items as necessary and instructions on shipment of boats.

6.8 Materiel deterioration prevention and control (MADPAC). The contracting officer should consider for inclusion in all applicable invitations for bid, requests for proposal, and contracts the following statement:

> "The technical proposal shall provide assurance that all system/item parts shall be fabricated from compatible materials, suitably finished, to provide protection from corrosion and other forms of materiel deterioration. The assurance shall be in the form of a finish plan, utilizing state-of-art technology, which clearly identifies the specific finish or treatment to be used on the various components and assemblies, to provide protection against the various forms of materiel deterioration in the applicable operating and storage environments to which they may be exposed." (See 3.3).

6.9 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 1940-A059

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-13831J(ME)	Boat, Reconnaissance, Pneumatic: 3-Man

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:27Z
Check the source to verify that this is the current version before use.