MIL-B-13872C (PA)
26 November 1975
Superseding
MIL-B-13872B (MU)
18 January 1971

MILITARY SPECIFICATION

BOXES, CONTAINERS, FOR NON-ELECTRIC BLASTING CAPS

*This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers two containers of different sizes and materials used for transport of blasting caps in the field.

1.2 Classification. - The blasting cap boxes shall be of the following types:

Type I - Wood box, 50 cap capacity
Type II - Plastic box, 10 cap capacity

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601 - Box, Wood, Cleated Plywood
PPP-B-636 - Box, Fiberboard
PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-L-10547 - Liner, Case, and Sheet, Overwrap, Water Vaporproof or Waterproof, Flexible

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-F-50449 - Filler, Sheet Form (For use in Ammunition Containers)

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-331 - Fuze and Fuze Components; Environmental and Performance Tests for
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

*U.S. ARMY PICATINNY ARSENAL

76-14-37 - Box, Cap, 50 Cap Capacity, Assembly
9257217 - Box, Cap, 10 Cap Capacity
P-4599 - Packaging Data Sheet

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*(For meaning of asterisk see paragraph 6.5).

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Boxes. - The boxes shall comply with all requirements specified on Drawing (dwg.) 76-14-37 or 9257217, whichever is applicable, and with all requirements specified in applicable specifications.

*3.3 Hot temperature (applicable to Type II only). - The box shall show no evidence of warp, split, open cover, broken or damaged hinge or catch after being tested.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

*3.4 Cold temperature (applicable to Type II only). - The box shall comply with the requirements of 3.3 and in addition shall be capable of being readily opened manually and the caps be easily removed after being tested.

3.5 Workmanship. - All assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, cracks, mold flash, chips, splinters, sharp edges, surface defect (see 6.4), dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined. All packing components shall be dry.

3.6 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples shall be as specified in the contract.

*4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated.

4.3.2 Inspections to be performed. - See MIL-A-48078 and paras 4.4.2.1 thru 4.4.2.2, testing per para. 4.4.3, molding inspections per para 4.4.5.1, and Table I specified herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Box, Cap, 50 Cap Capacity, Assembly (Type I)				76-14-37
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Lock Assembly (Dwg. 9204426) Examination for Defects	32	100%	3.2	4.4.2.1
	Box Assembly, 50Cap Capacity (Dwg. 76-14-37) Examination for Defects	32	100%	3.2	4.4.2.2
	Lot Assembly Spring Catch Displacement Test (Dwg. 9204430)	32	100%	3.2	4.4.3.3

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Box, Cap, 10 Cap Capacity (Type II)				9257217
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Ten Cap Blasting Box (Dwg. 9257217) Examination for Defects	See Note a	100%	3.2	4.4.5.1
	Hot Temperature	13	100%	3.2	4.4.3.1
	Cold Temperature	13	100%	3.2	4.4.3.2

NOTE:

a. The first article sample shall consist of a minimum of twenty-six(26) boxes (i.e., 5 of each assembly, which include five (5) items from each cavity used to produce molded parts, and be so identified as to permit tracing each item to the cavity in which it was molded), except that a minimum of twenty-six (26) boxes shall be submitted if a single cavity is used.

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects, molding inspections, and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9204426
*4.4.2.1	Lock, Assembly				NEXT HIGHER ASSEMBLY 76-14-37
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major A					
101.	Peening of button to catch improper		0.40%	3.2	Visual/Manual
102.	Cover insecure on back plate		0.40%	3.2	Manual
103.	Spring missing		0.40%	3.2	Manual
Minor					
201	Cover flush with back plate maximum (max)		0.65%	3.2	Feeler gage
202	Protective coating missing or contains bare spot		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.2	Box, Assembly, 50 Cap Capacity	1 OF 1	76-14-37
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major B:					
131.	Diameter of holes (min)		0.65%	3.2	Plug Gage, GO (CD)
132.	Depth of holes		0.65%	3.2	Depth Gage (CD)
133.	Location of holes		0.65%	3.2	Location Gage (CD)
134.	Depth of Recess in cover (min)		0.65%	3.2	Depth Gage (CD)
135.	Location of lock assembly		0.65%	3.2	Steel Rule (CD)
136.	Number of holes incorrect		0.65%	3.2	Visual
137.	Lock assembly does not lock or release cover as designed		0.65%	3.2	Manual
Minor:					
201.	Total Length, max.		0.65%	3.2	Steel Rule (CD)
202.	Total width including hinge and lock (max)		0.65%	3.2	Steel Rule (CD)
203.	Total height (max)		0.65%	3.2	Steel Rule (CD)
204.	Hinge insecure or damaged to the extent that function may be impaired		0.65%	3.2	Visual
205.	Marking missing, incorrect or illegible		0.65%	3.2	Visual
206.	Grain direction incorrect		0.65%	3.2	Visual
207.	Protective coating missing or contains bare spot		0.65%	3.2	Visual
208.	Escutcheon pin or base screw protrudes or missing		0.65%	3.2	Visual
209.	Liner missing		0.65%	3.2	Visual
210.	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-B-13872C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.3	Box, Fiberboard before Sealing				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Box improperly positioned in fiberboard box		0.40%	3.2	Visual
132	Plain pads omitted		0.40%	3.2	Visual
Minor					
201	Box punctured, torn or cut		0.65%	3.2	Visual
202	Contents loosely packed in box		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.4	Box, Paperboard before Sealing				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Box loose in paperboard box		0.40%	3.2	Visual
132	Paperboard box punctured		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-B-13872C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.5	Box, Fiberboard or Paperboard Sealed				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Tape missing or improperly applied		0.40%	3.2	Visual
132	Contents loose within box		0.40%	3.2	Visual
133	Marking missing, incorrect or illegible		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.6	Sealed Caseliner		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Seal improper or incomplete		0.40%	3.2	Visual
132	Liner punctured, torn or cut		0.40%	3.2	Visual
Minor					
201	Bag bulges due to insufficient air removal before sealing		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

*4.4.3.1 Hot temperature (see 3.3) - Major A defect. - A sample of thirteen (13) 10 cap capacity plastic boxes shall be selected from each lot of boxes for this test. If one or more boxes fail to comply with the requirements, the lot shall be rejected. In addition the box shall be subjected to an information only inspection for external cracks. However, presence of more than three (3) cracks in the webbing, or any web crack which extends to the periphery of the box shall be cause of lot rejection. The test shall be performed as specified in 4.5.1.

*4.4.3.2 Cold temperature (see 3.4) - Major A defect. - A sample of thirteen (13) 10 cap capacity plastic boxes shall be selected from each lot for this test. If one or more boxes fails to comply with the requirements, the lot shall be rejected. In addition the box shall be subjected to an information only inspection for external cracks. However, presence of more than three (3) cracks in the webbing, or any web crack which extends to the periphery of the box shall be cause of lot rejection. The test shall be performed as specified in 4.5.2.

*4.4.3.3 Lot assembly spring catch displacement (see dwg. 9204430) - Major A defect. - A sample of thirty-two (32) lock assemblies shall be selected from each lot for this test. If one or more assemblies fail to comply with the requirement, the lot shall be rejected. The test shall be performed as specified in 4.5.3.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, the molding paragraphs starting with 4.4.5.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.1 herein.

4.4.5 Dimensional control of molded parts (applicable to Type II only). - In place of normal sampling and inspections associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (see Note 1) a sample

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

of twenty (20) boxes (as molded) from each cavity shall be inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification, when more than one cavity is used in production. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraph 4.4.5.1 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the twenty (20) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective boxes are found when inspection is performed for the control of the cavity, the cavity producing the defective box shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request. Contractor design of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T-T for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

Note 1. - In establishing the curing time, dimensionally check ten (10) boxes from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to Picatinny Arsenal, Dover, New Jersey 07801 ATTN: SARPA-QA-A-M. If any new change in material, cycle time, a reworked cavity, or a new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-13872C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.5.1	Box, Assembly, 10 Cap Capacity		9257217
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major B:		See Note			
101.	Length of body catch	20	100%	3.2	Gage
102.	Depth of holes	20	100%	3.2	Gage
103.	Diameter of holes	20	100%	3.2	Gage
104.	Coloring incorrect	20	100%	3.2	Visual
105.	Coining missing or incomplete (see b below)	--	0.40%	3.2	Visual
106.	Lid damaged or does not function as designed	20	100%	3.2	Visual
107.	Catch does not function as designed	20	100%	3.2	Visual/Manual
108.	Catch manual protrusion on lid broken or incomplete	20	100%	3.2	Visual
109.	Box damaged to extent that function is impaired	20	100%	3.2	Visual
Minor:					
201.	Embossed marking illegible	20	100%	3.2	Visual
202.	Evidence of poor workmanship	20	100%	3.5	Visual

NOTES:

a. See para. 4.4.5 above for disposition of rejected boxes.

b. Coining defects shall not cause cavity requalification.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

4.5 Test methods and procedures.

4.5.1 Hot temperature. - The 10 cap plastic boxes shall be filled with inert loaded blasting caps. The inert loaded boxes shall then be conditioned at seventy-one (71) degrees Centigrade (C.), minimum, for one hundred (100) hours minimum. Within fifteen (15) minutes after removal from the conditioning chamber, the boxes shall be subjected to the Five Foot Drop Test specified in MIL-STD-331. The boxes shall be examined after the drop test to determine compliance with the requirements.

4.5.2 Cold temperature. - The 10 cap plastic boxes shall be filled with inert loaded blasting caps. The inert loaded boxes shall then be conditioned at minus forty (-40) degrees C., minimum, for forty-eight (48) hours, minimum. Within fifteen (15) minutes after removal from the conditioning chamber, the boxes shall be subjected to the Five Foot Drop Test specified in MIL-STD-331. The boxes shall be examined after the drop test to determine compliance with the requirements.

4.5.3 Lock assembly spring catch displacement. - The spring catch assembly of the lock assembly shall be assembled in the equipment (CD) specified in 4.4.4. The required load shall be applied and the displacement measured to determine compliance with the requirement. The ability of the catch to return to its normal position shall be observed.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A

5.1.1.1 Box, Cap, 10 Cap Capacity Type II. - Fifty (50) boxes shall be packaged in a fiberboard conforming to PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 200. The cap boxes shall be packaged in 5 rows of 5 per layer, 2 layers per box. Cap boxes shall be positioned on end with the cover end of each box alternately reversed and the like sides of the boxes butted together to form each row. A plain fiberboard pad of the same grade as that of the box shall be placed on the bottom of the box, between the cap box layers

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

and on top of the box contents. Additional top pads shall be added as required for a tight package. Box size shall be approximately 10 3/8 by 6 by 5 3/8 inches in depth, inside dimensions. Plain pads shall be equal to the inside length and width of the fiber box less 1/8 inch tolerance. Fiber boxes shall be closed by applying a length of 3 inch wide tape conforming to PPP-T-45 Type II, Class 1, over the entire length of the top and bottom center seam of the box with approximately 2 inch extension of the tape onto the end panels.

*5.1.1.2 Box, Cap 50 Cap Capacity Type I. - Each box shall be inserted into a paperboard box constructed in accordance with Specification PPP-B-566 for a Variety 1, Style II, Type D, Class a box. Box size shall be approximately 2 7/16 by 1-11/16 inches in depth, inside dimensions. A length of tape approximately 1 inch long by 1 inch wide shall be placed across the bottom and top closed flaps of the box. Tape shall conform to PPP-T-42.

5.1.2 Level C. - Boxes shall be perserved and packaged the same as Level A requirements.

*5.1.2.1 Intermediate packaging. - Forty (40) boxes shall be placed in a fiberboard box conforming to PPP-B-636 for a Type CF, Class Domestic, Variety SW Grade 200 Style RSC box. Box size shall be approximately 10 1/4 by 9 by 6 1/2 inches in depth, inside dimensions. Boxes shall be closed by application of 2 inch wide tape, PPP-T-45, Type II, Class 1 or PPP-T-76 over the full length of the top and bottom center seam of the box with an approximate 3 inch extension onto the end panels.

5.2 Packing

5.2.1 Level A

5.2.1.1 Box, Cap, 10 Cap Capacity Type II. - Six packages (300 cap boxes) shall be packed in a waterproof lined wooden box. The liner shall conform to MIL-L-10547, Type I or IV, Grade B or C. The box shall meet the requirements of PPP-B-621 for a Class 2, Grade B, Style 2 or 4 box, or PPP-B-601 Overseas Type, Style A or B box. Fillers conforming to MIL-F-50449 shall be added at the ends of the box, and on top of the closed liner as required

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

for a tight pack. Liner size shall be approximately 18 1/4 by 13 by 24 inches high, inside dimensions. Liners shall be closed in accordance with instructions contained in MIL-L-10547. Box size shall be approximately 18 by 12 3/4 by 11 1/4 inches in depth inside dimensions. Boxes shall be closed and strapped in accordance with instructions contained in the appendix of the box specification.

*5.2.1.2 Box, Cap, 50 Cap Capacity Type I. - Intermediate packages shall be packed same as described in paragraph 5.2.1.1 except the quantity per box shall be eight (8) boxes (320 Cap Boxes). Liner size shall be approximately 30 1/4 by 18 by 25 inches in depth, and box size shall be approximately 30 by 17 3/4 by 13 1/8 inches in depth inside dimensions.

*5.2.2 Level C. - Type I and II boxes shall be packed the same as Level A requirements except boxes shall be 'Class 1" for PPP-B-621 and "Domestic Type" for PPP-B-601 boxes. Fillers shall consist of commercial chipboard minimum 1/16 inch thick. Waterproof liners are not required.

5.3 Marking. - Unit and exterior boxes shall be marked in accordance with MIL-STD-1169 requirements.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.2 Submission of Inspection Equipment Designs for Approval (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801.

6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

*6.4 Crazing. - Fine cracks which may extend in a network on or under the surface or through a layer of plastic material. Usually occurs in the presence of an organic liquid or vapor, with or without the application of mechanical stress, per MIL-HDBK-700A/Plastics. (For the Type II box specified herein, crazing is not a workmanship defect).

6.5 Asterisks - The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-158

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.