MILITARY SPECIFICATION

SAW, BAND, METAL CUTTING, 14 INCH

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one size and type of motor-driven band saw for metal cutting.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

CC-M-1807	-	Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).

MILITARY

MIL-T-152	-	Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment.
MIL-V-173	-	Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, ATTN: SMCAR-ETS (R), Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-889 - Dissimilar Metals.

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

US DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN GEAR MANUFACTURERS' ASSOCIATION (AGMA)

AGMA 360.02 - Manual for Machine Tool Gearing.
AGMA 390.03 - Gear Handbook, Volume 1, Gear Classification, Materials, and Measuring Methods for Unassembled Gears.

(Application for copies should be addressed to the American Gear Manufacturers' Association, 1901 N. Fort Myer Dr., Arlington, VA 22209.)

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION (ISO)

ISO 54 - Cylindrical Gears for General Engineering and for Heavy Engineering - Modules and Diametral Pitches.
ISO 1122/1 - Glossary of Gear Terms - Part 1: Geometrical Definitions.

(Application for copies of ISO documents should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging.
ASTM E380 - Standard for Metric Practice.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL ELECTRICAL MANUFACTURERS' ASSOCIATION (NEMA)

NEMA ICS 1 - General Standards for Industrial Control and Systems.

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 2101 L Street, NW, Washington, DC 20037.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 70 - National Electrical Code.
NFPA 79 - Electrical Standard for Metalworking Machine Tools and Plastics Machinery.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy MA 02269.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish one or more band saws for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The band saw shall be new and of the manufacturer's latest design which shall meet the requirements specified herein. The saw shall be a vertical cutting, floor-mounted, variable or multiple speed type designed for straight line and contour sawing of various metals. The design shall be such that all parts subject to wear, breakage, or distortion shall be accessible for adjustment, repair, and replacement without modification, distortion, or damage to the saw or any saw component.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

* 3.2.1 Safety and health requirements. Safety devices shall be provided for all parts presenting safety hazards. Guards shall be removable to provide easy access to guarded parts. The saw shall comply with the general safety and health requirements promulgated under OSHA 2206 that are applicable to the saw itself. Exceptions and additional requirements for safety and health shall be as specified in the contract (see 6.2.1 and 6.4).

* 3.2.2 Lubrication. All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with standard means for lubrication. Oil holes, grease fittings, and filler caps shall be accessible without requiring disassembly of functional parts. Lubrication reservoirs, if applicable, shall have means for checking levels.

* 3.2.3 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

* 3.3 Construction. The band saw shall be constructed to be capable of performing the operations specified herein. The saw and its equipment shall be complete so that, when installed and connected to a proper power source, it can be used for all operations for which it was designed.

* 3.3.1 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the machine tool industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

* 3.3.2 Reclaimed materials. The contractor is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity, and intent of the materials originally selected or specified. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment.

* 3.3.3 Castings and forgings. Castings shall be free from blowholes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from scale, inclusions, cold shuts, mismatching, sharp edges, or other defects. Castings and forgings shall be free from any properties adversely affecting their strength, durability, or suitability. Reclaiming or repair of major castings and forgings shall be permitted if the repair is not on a critical surface.

* 3.3.4 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain the performance requirements of the welded, brazed, or soldered part. These operations shall not be employed as repair measures for defective parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

* 3.3.5 Painting. Unless otherwise specified (see 6.2.1), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces shall be clean and be free of all foreign matter detrimental to painting. At least one coat of primer (or a phosphate or chromate base) and one coat of enamel, or equivalent (i.e., epoxy enamel), shall be applied.

* 3.3.6 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

* 3.3.7 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness and adjustment. The methods for preventing loss of tightness or adjustment shall be in accordance with accepted engineering standards and practice. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise deformed.

* 3.3.8 Gears. All gears and pinion designs selected for use in the saw or its components shall be manufactured to either English (USA) standard inch diametral pitch per AGMA 360.02 and AGMA 390.03 or Metric (SI) module ratio per the International Organization for Standardization (ISO) ISO 54 and ISO 1122/1 and ASTM E380.

* 3.3.9 Electrical components. Electrical components shall conform to, and be located in accordance with, NEMA ISC 1 and NFPA 79.

* 3.3.10 Electrical connections. Connections to screw-type terminals shall be mechanically secured with means to prevent loss of tightness. All other electrical connections shall be mechanically secured and soldered or brazed. Only rosin base fluxes shall be used in soldering operations.

* 3.3.11 Surfaces. All castings, forgings, molded parts, stampings, and welded parts shall be clean and free of sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous material. External surfaces shall be smooth and all edges shall be rounded or beveled.

3.4 Performance and product characteristics.

3.4.1 Sizes and capacities. Sizes and capacities of the band saw shall conform to the following requirements:

Minimum throat depth	13 3/4 inches
Minimum range of work thickness (under guide)	0 to 6 1/4 inches
Minimum range of band saw blade width	1/8 to 3/4 inch
Minimum range of band speed	40 to 3,000 surface feet per minute
Minimum number of band speeds	8
Minimum area of worktable	14 inches long by 14 inches wide
Minimum tilt of worktable	45° right, 10° left
Height of worktable from floor	38 to 44 inches
Maximum overall height of machine	72 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

3.4.2 Straight line sawing. The band saw shall be capable of sawing 1/2 inch thick, 1040-1050 carbon steel at a linear rate of not less than 2 1/2 inches per minute while equipped with a 1/2 inch wide saw blade of the type to be furnished with the machine, while operating at the speed recommended by the manufacturer.

3.5 Components. The band saw shall be composed of, but not limited to, the components covered in 3.5.1 thru 3.5.9.4.

3.5.1 Housing. The housing shall be fabricated of sheet steel, cast iron, or any combination thereof. The housing shall enclose the carrier wheels and shall incorporate hinged or removable sections to facilitate changing saw blades and cleaning the interior of the housing. The base shall incorporate four bolt holes to secure the saw to the floor.

3.5.2 Carrier wheels. Carrier wheels shall be fabricated of metal or pressure-molded plastic. Carrier wheels shall be dynamically balanced and shall be mounted on anti-friction, precision bearings. Carrier wheel tires shall be of an oil-resistant material.

* 3.5.3 Band tension and tracking adjustment mechanism(s). The band saw shall incorporate a means for adjusting band tension and for accurately tracking the band. The mechanism(s) shall have an adjustment range, to compensate for band lengths, varying from two inches less than the rated band length to 1/2 inch more than rated band length. The adjustment shall be actuated by a handwheel or crank. The mechanism shall include an indicator used to determine the correct tension for each specified blade width.

3.5.4 Band saw guide blocks. Upper and lower guide blocks, covering the blade capacity of the machine, shall be furnished. Guide blocks shall contain a back-up bearing supported by single row, sealed-for-life ball bearings. The upper guide block shall be vertically adjustable and shall be provided with a device for locking the guide at any vertical setting. The lower guide block shall be mounted below the worktable surface.

* 3.5.5 Worktable. The worktable shall be of steel or cast iron, heavily ribbed, and machine finished on the top working surface. The front and back edges shall be machine finished. The sides need not be machined or ground but shall be painted. Provision shall be made for receiving hand-feed attachments, mitering attachments, and other accessories as required. The table shall have a tilting mechanism that shall permit the table to be easily tilted and securely set to an angle accurate to within one degree (°). The worktable shall withstand, without damage, a uniformly distributed load of 500 ±10 pounds. A table groove (front to back) 3/8 inch deep by 3/4 inch wide shall be provided.

3.5.6 Drive unit. All speed controls shall be accessible to the operator. When gears are employed to transmit sawing power, the gear train shall be sealed and operate in an oil bath. Gear shafts shall be mounted on anti-friction bearings. Construction of geared drive units shall permit gear changes without damage to the mechanism. The entire drive unit shall be enclosed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

* 3.5.7 Drive motor. Unless otherwise specified (see 6.2.1), the motor shall be a squirrel-cage induction type of not less than one horsepower (hp) and operate on nominal 115/230 volts (initially wired for 115 volts), 60 hertz, single phase, continuous duty rating, conforming to the requirements of CC-M-1807.

* 3.5.7.1 Control switch. The drive motor shall be equipped with an ON-OFF switch. The switch shall comply with NEMA ICS 1.

* 3.5.8 Power cord. Unless otherwise specified (see 6.2.1), the saw shall be furnished with not less than eight feet of 3-wire, No. 14 American Wire Gage, National Electrical Code type SO or STO, heavy duty, electric power cord conforming to NFPA 70. The cord shall terminate in one inch of stripped, tinned wire.

3.5.9 Standard equipment. The following standard equipment shall be furnished with each band saw.

3.5.9.1 Adjustable angle gage. The band saw shall be furnished with an adjustable angle gage with pointer calibration, and positive stops at 90° and 45° positions (left and right swing) for making angle and mitre cuts. The gage shall work in conjunction with a groove or guide to allow the gage to slide across the worktable during cutting operations.

* 3.5.9.2 Band saw blade preparation equipment. Band saw blade preparation equipment shall include a shear, resistance-type butt welder, grinder, and thickness gage with the following characteristics.

3.5.9.2.1 Shear. The shear shall be capable of cutting band saw blades up to and including 3/4 inch in width and .025 through .035 inch in thickness. The shear shall be capable of uniformly shearing band saw blades at an angle of 90 degrees across the width of the blade without permanently bending or deforming the blade material.

3.5.9.2.2 Resistance type butt welder. The welder shall be capable of welding and annealing band saw blades up to and including 3/4 inch in width and .025 through .035 inch in thickness. The welder shall operate from 115 volts, 60 hertz. A switch for starting and stopping the welder shall be provided. The welder shall be capable of welding saw blades without mismatch.

3.5.9.2.3 Grinder. The grinder shall be capable of grinding welds and dressing saw blades. The grinder shall be completely guarded except for that portion of the grinder used for grinding. The grinder motor shall operate from 115 volts, 60 hertz and shall be of the drip-proof, continuous-duty type with sealed ball bearings. The grinder motor shall be rated at not less than 1/10 horsepower and shall conform to CC-M-1807.

3.5.9.2.4 Thickness gage. A thickness gage shall be provided for gaging band saw blades of .025 through .035 inch in thickness.

3.5.9.3 Band saw speed selector. A dial-type selector, or a table of information, shall be conveniently located on the band saw or in the instruction manual provided with the machine. The selector or information shall indicate the radius cutting limits for each blade width within the range specified in 3.4.1, and shall include the following information for common metals and alloys:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

(a) Sawing speeds in feet per minute.
(b) Type of band saw blade.
(c) Pitch of saw teeth.

* 3.5.9.4 Rip fence. A rip fence shall be mounted on the work table. The rip fence shall either be double faced or reversible for rip sawing on either side of the blade. The rip fence shall have a locking device which shall retain the fence in infinite adjustments at any point across the entire width of the table.

3.6 Accessories. Saw blades and abrasive belts shall be furnished as specified (see 6.2.1). As a minimum, the following characteristics for saw blades shall be addressed:

(a) Type of set.
(b) Style of teeth.
(c) Blade width.
(d) Blade thickness.
(e) Number of teeth (pitch).

* 3.7 Fungus control. Components of electrical circuitry that are hermetically sealed or inherently resistant to fungus growth and moisture need not be treated. Components of electrical circuitry that are not inherently resistant to fungus growth or moisture shall be treated in accordance with MIL-T-152 and MIL-V-173.

3.8 Product identification. The band saw shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2.1), shall include the National Stock Number.

* 3.9 Workmanship. Standards of workmanship shall assure that the band saw shall have the stability, strength, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2.1), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of (a) through (c) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).
(b) Tests (see 4.6.1, 4.6.2, and 4.6.3).
(c) Packaging inspection (see 4.7).

* 4.4.1 Sampling. When required (see 6.2.1), sampling for quality conformance inspection shall be as specified in MIL-STD-105 at the Inspection Level and Acceptable Quality Level (AQL) specified in the contract. For packaging inspection (see 4.7), special inspection level S-4 and an AQL of 4.0 percent defective shall be used.

* 4.5 Product examination. The saws shall be examined to determine compliance with the requirements of Section 3 and the contract. As a minimum, the following characteristics shall be examined:

CHARACTERISTICS	REQUIREMENT PARAGRAPH
Design	3.2 through 3.2.3
Construction	3.3 through 3.3.11
Performance and product characteristics	3.4.1 and 3.4.2
Components 1/	3.5 through 3.5.9.4
Accessories	3.6
Fungus control 1/	3.7
Product identification	3.8
Workmanship	3.9

1/ Vendor certification required where applicable.

4.6 Tests.

4.6.1 Band saw blade preparation equipment test. A 1/4 inch wide and a 1/2 inch wide band saw blade shall be cut, welded, and dress ground in accordance with the manufacturer's instructions to determine compliance with 3.5.9.2. These band saw blades shall then be individually mounted on the machine and tested as follows:

(a) Using the 1/4 inch wide blade, the band saw shall saw a half circle in 1/4 inch steel plate in accordance with the table of information specified in 3.5.9.3.
(b) Using the 1/2 inch wide blade, the band saw shall be operated in accordance with the manufacturers criteria to saw 1/2 inch thick 1040-1050 carbon steel to determine compliance with 3.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

4.6.2 Table tilt test. With the machine set up for normal operation, the worktable shall be set at angles of 0°, 5°, 15°, 30°, and 45° to the right and 10° to the left. The table shall then be measured for accuracy to determine compliance with 3.4.1 and 3.5.5. Failure of the machine to meet these requirements shall be cause for rejection.

4.6.3 Static load test. The worktable shall be locked at the zero point on the table tilt scale. The table shall then be subjected to an evenly distributed load of 500 ±10 pounds for 30 minutes. Any evidence of failure, or deformation of the table or its supports, shall be cause for rejection of the band saw.

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5. PACKAGING

* 5.1 Military preservation, packing, and marking. When specified (see 6.2.1), requirements for Level A preservation and for Levels A and B packing and marking shall be in accordance with MIL-M-18058.

* 5.2 Industrial preservation, packing, and marking. Unless otherwise specified (see 6.2.1), preservation, packing, and marking shall be in accordance with ASTM D3951-82.

6. NOTES

6.1 Intended use. The band saw covered by this specification is used for general straight line and contour sawing operations on various metals and plastics.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) First article when required (see 3.1).
(c) Exceptions and additional safety/health requirements when required (see 3.2.1 and 6.4).
(d) Painting and finishing if different (see 3.3.5).
(e) Drive motor if different (see 3.5.7).
(f) Power cord if different (see 3.5.8).
(g) Accessories required (see 3.6).
(h) Product identification if different (see 3.8).
(i) First article inspection if different (see 4.3).
(j) Quality conformance inspection if different (see 4.4).
(k) Sampling when required (see 4.4.1).
(l) Level of preservation, packing, and marking if different (see 5.1 and 5.2).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

* 6.4 Safety and health requirements. In order that equipment integrated into the user's operational environment will comply with OSHA limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc, as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - AL

Preparing activity:

Army - AL

Project No. 3405-0066

Review activities:

DLA - GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research and
Development Center
Attn: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(FOLD DETACH THIS ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:31Z
Check the source to verify that this is the current version before use.