MILITARY SPECIFICATION

ADHESIVE-SEALANTS, SILICONE, RTV, ONE-COMPONENT

This amendment forms a part of MIL-A-46106B, dated 11 December 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Add the following:

"QQ-S-698 Steel Sheet and Strip, Low Carbon"

PAGE 3

2.2: Delete "ASTM A366 - Steel, Carbon, Cold-Rolled Sheet, Commercial Quality"

PAGE 4

3.2.2: Delete and substitute:

"3.2.2 Primer. When required, each manufacturer of a silicone adhesive-sealant shall supply a suitable primer which shall be furnished with the product. The manufacturer shall certify that the primer, when used with the adhesive meets the requirements for primer within this specification (see 3.4.2)."

PAGE 12

4.2.2.6, line 5: Delete "steel conforming to ASTM A366, Temper 5" and substitute "steel conforming to QQ-S-698"

PAGE 14

4.5.2.2, line 5: Delete "adhesion test specimens shall be cured for 336 ± 4 hours (14 days ± 4 hours)" and substitute " adhesion test specimens shall be cured for 168 ± 4 hours (7 days ± 4 hours)"

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:52Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MR
Navy - AS
Air Force - 11

Review activities:
Army - ME, MD, AT, MI, SM, AR
Navy - YD
Air Force - 11

User activities:
Navy - SH
GSA - FSS (10FTE)

Preparing activity:
Army - MR

Project 8040-0518

(KBWP# ID-0165A/DISC-0021A. FOR MTL USE ONLY.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:52Z
Check the source to verify that this is the current version before use.