A-A-2011A
July 30, 1992
SUPERSEDING
A-A-2011
June 1, 1982

COMMERCIAL ITEM DESCRIPTION
REFRIGERATORS, MECHANICAL, HOUSEHOLD
(ELECTRIC, SELF-CONTAINED)

The General Services Administration has authorized the use of this Commercial Item Description in preference to Federal Specification AA-R-211.

This Commercial Item Description (CID) covers the requirements for self-contained household refrigerators with electric-motor-driven condensing units.

Salient Characteristics.
Household refrigerators covered by this CID are of the following types, storage volumes and dimensions:

Type 1. The refrigerator shall contain a low temperature food storage compartment below 32 degrees fahrenheit (F), and a manually initiated defrost system with manual or automatic reset.

Type 2. The refrigerator shall contain an isolated frozen food storage compartment below 8 degrees (F), and an automatically initiated defrost system with automatic reset for general food storage compartment only.

Type 3. The refrigerator shall contain an isolated frozen food storage compartment below 8 degrees (F), and an automatically initiated defrost system with automatic reset for both general food storage and frozen storage compartments.

Minimum Total Storage Volume	Maximum Overall Dimensions		
(cu. ft)	Width (in.)	Height (in.)	Depth (in.)
9.5	28	61	31
11.5	32	64	31
12.5	32	66	31
13.5	34	69	31
14.5	34	71	31
15.5	34	71	31
16.5	48	71	32
18.5	48	71	32
20.5	48	71	32

FSC 4110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Note: The depth shall be measured from the rearmost part of the refrigerator to the outside panel of the door when the door is closed (exclude the width of the handle in this measurement).

The refrigerator shall have a frozen food storage compartment with a minimum volume of 1 cubic foot.

Asbestos shall not be used as a material in any part of the refrigerator.

Unless otherwise specified, the refrigerator shall operate on a 115 volt, 60 hertz. A three-wire cord with a three-pronged plug shall be supplied for use as a power supply cord. The cord shall extend a minimum of 60 inches and a maximum of 120 inches from the point at which it is attached to the back of the refrigerator.

When specified, the refrigerator shall operate on 220 volts, 50 hertz CID. The refrigerator shall not utilize an externally mounted transformer. Unless otherwise specified, the refrigerator shall be provided with a schuko type plug attached to a three wire power cord.

The refrigerator shall be capable of producing air temperatures in the general food storage compartment of 36 degrees (F) in an ambient of 70 degrees (F), 38 degrees (F) in an ambient of 90 degrees (F), and 43 degrees (F) in an ambient of 110 degrees (F). The performance test procedures shall be as specified in ANSI/AHAM-1.

Refrigerators shall conform to the applicable requirements of ANSI/UL 250. Acceptable evidence of meeting the requirements of this standard shall be the UL label or UL listing mark permanently affixed to the refrigerator. In lieu of the UL label or listing mark, the contractor may submit a certified test report from a recognized independent testing laboratory acceptable to the Government, indicating that the refrigerator has been tested and conforms to the applicable requirements of the UL standard.

The annual energy consumption shall be determined in accordance with the Code of Federal Regulations, Title 10, Chapter II, Part 430 dated January 1, 1990. Energy consumption requirements are waived for refrigerators specified to operate on 220 volts, 50 hertz.

Note: The energy consumption for the Type 3 refrigerator shall be determined with the Anti-Sweat heater switch in the high energy consuming position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

The determined annual energy consumption shall not exceed the annual energy consumption as calculated by one of the following applicable formulas:

Type 1 EC = 487 + 32.42V
Type 2 EC = 487 + 48.67V
Type 3 EC = 487 + 85.17V

V = Total refrigerated volume in cubic feet.

EC = Energy consumption in kilowatt hour per year (KWH/YR).

American National Standard ANSI/AHAM HRF-1 shall be used to calculate the total refrigerated volume of household refrigerators.

The refrigerator shall include the following:

A) An adjustable temperature control accessible for adjustment and servicing.

B) A minimum of two copolymer of polyethylene plastic ice cube trays.

C) A switch for the interior lights which operates automatically by opening the door.

D) The general food storage area shall have an egg storage rack which holds a minimum of 12 eggs and a butter dish.

E) The door handles for both the refrigerator and freezer on the two door models, and the outside door for the single door models, shall be metal or metal reinforced.

F) Each external door shall be equipped with a magnetic gasket.

G) The general food storage area shall have a minimum of three food shelves. The platform above the vegetable bin may count as a general food shelf if it can support a minimum of 25 pounds.

H) A minimum of two adjustable leg levelers and shall be free standing.

Unless otherwise specified, doors shall swing to the right. A right hand swing is defined as having hinges located on the right side of the door when facing the front of the refrigerator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Refrigerators with a minimum total storage volume of 18.5 or 20.5 cubic feet shall have rollers. Refrigerators with automatic ice makers, shall have rollers.

The outer shells (including door) shall be carbon steel sheet finished in baked synthetic enamel. The inner liner of the general food storage, frozen food storage, and exterior doors shall be carbon steel sheet or molded plastic. The carbon steel sheet inner liner shall have a white porcelain enamel or a white baked synthetic enamel finish.

The flat surfaces of the molded plastic liner shall have an average thickness of 0.055 inch. Corners of the molded plastic inner liner shall have a 1/32 inch minimum thickness.

When molded plastic liners are used in conjunction with foamed-in-place polyurethane employing fluorinated hydrocarbons, the liner material shall be isolated from the polyurethane foam or must be made of acrylonitrile butadiene styrene (ABS) or a chemical resistant high impact polystyrene (HIPS) laminated with an impact polystyrene gloss cap.

When the insulation is foamed-in-place polyurethane with fluorinated hydrocarbons, ABS plastic or polypropylene or chemical resistant HIPS shall be used for breaker strips or the breaker strip material shall be isolated from the polyurethane foam.

Plastic compartment liners, breaker strips, and molded plastic door liners when assembled to outer doors shall not show any cracks or crazing when tested in accordance with the Environmental Cracking Resistance Test specified in ANSI/AHAM HRF-1.

Bottom breaker strips and/or exposed area of molded plastic liner bottoms shall not show any cracks or crazing when subjected to the impact test specified in ANSI/AHAM HRF-1.

Workmanship. Welding and brazing shall be complete, uniform, and properly fused, having no holes, slag, inclusions, scale or flux deposits and shall not be cracked, fractured, or undercut. Soldering shall be complete, clean, adherent, and without pinholes. When used on structural parts subject to vibration, fasteners (i.e. bolts, nuts, screws, studs) shall have locked washers or shall be self-locking type. Fasteners shall not be broken, fractured, stripped, or loose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

First article test. The first article test shall consist of the tests and inspections necessary to prove compliance with each of the requirements of this CID. A certificate of compliance stating that the requirements are met will be considered acceptable evidence when substantiating evidence (i.e. recent test report) is supplied.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Packaging, packing and marking. Packaging, packing and marking shall be as specified in the contract or order.

Notes.

ANSI/UL 250 is available from Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, Illinois 60062.

ANSI/AHAM HRF-1 is available from the Association of Home Appliance Manufacturers, 20 North Wacker Drive, Chicago, Illinois 60606.

When this Commercial Item Description is used for procurement, the purchaser should specify the refrigerator type, minimum storage volume, and the electrical requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.