A-A-50010A
March 23, 1987
SUPERSEDING
A-A-50010
August 24, 1981

COMMERCIAL ITEM DESCRIPTION

TOASTERS, ELECTRIC AND TOASTERS, GAS, CONVEYOR, HEAVY-DUTY

The General Services Administration has authorized the use of this commercial item description in preference to S-T-540.

1. CLASSIFICATION

1.1 Classification. The toasters covered by this CID are intended for non-shipboard use where volume food serving is done. Toasters shall be of the following types and sizes:

Type I - Electric
Type II - Gas
Size 1 - 540 Slices per hour
Size 2 - 720 Slices per hour
Size 3 - 950 Slices per hour

2. SALIENT CHARACTERISTICS

2.1 Codes and standards. Toasters shall comply with the applicable requirements of ANSI Z83.14b, NSF Standard No. 4, and UL Standard No. 197. Plugs shall comply with the applicable requirements of the National Electrical Manufacturers Association Standard WD1.

2.2 Type I. Type I toasters shall be electrically heated. Toasters equipped with quartz heating elements shall be capable of resisting a drop of 4 inches from an upright position onto a hard surface, without any damage to the heating elements. In addition, the quartz heating elements shall be so located or guarded that they are not subject to damage during cleaning operations. Unless otherwise specified (see 5.2), type I toasters shall be designed to operate on 208 volts, 60 hertz, 1-phase power supply. Unless otherwise specified, a terminal board or box shall be furnished within the toaster enclosure for permanent connection. The terminal board or box shall have a ground terminal connected to the outer toaster shell. When toasters are not to be supplied with a terminal board or box, the toasters shall be supplied with a 6-foot cord and a NEMA 6-30 plug (see 5.2).

FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:37Z
Check the source to verify that this is the current version before use.

2.3 Type II. Type II toasters shall be gas heated. Unless otherwise specified (see 5.2), type II toasters shall be supplied to operate on natural gas. The orifice hoods or spuds installed for natural gas shall be unpainted brass. The toasters shall be capable of being converted to burn liquified petroleum gas (LPG). Black color-coded orifice hoods or spuds along with complete instructions shall be furnished for conversion to LPG. Unless otherwise specified, a pressure regulator for natural gas shall be furnished with each toaster. Each toaster shall be furnished with a 60-inch connector conforming to Z21.45 and a quick disconnect conforming to Z21.41. The toaster shall be equipped with means for automatic ignition of gas. A pilot including a 100 percent shut-off device shall be provided for each toaster burner. The pilot shall automatically shut off the gas to all toaster burners including the toaster pilot burners in the event ignition becomes inoperative. Unless otherwise specified (see 5.2), toasters shall be designed to operate on 120 volts, 60 hertz, 1-phase power supply and shall be supplied with a 6-foot cord and a NEMA 5-15 plug.

2.4 Design, construction and performance. The toaster shall be capable of toasting bread slices or bun halves. The toasters shall have an electric motor driven conveyor system. The toaster shall be capable of evenly toasting 4-1/2 inch by 4-1/2 inch bread slices at the minimum rate of 540 slices per hour for size 1, and 720 slices per hour for size 2, and 950 slices per hour for size 3. The toasters shall not exceed 35 inches in height, 20 inches in width, and 24 inches in depth. The outer shell of the toaster shall be fabricated from stainless steel and shall have an opening for placement of bread or bun slices on the conveyor racks. Means shall be provided to catch and dispose of crumbs. Means shall be provided for obtaining light, medium or dark colored toast or buns. Unless otherwise specified (see 5.2), all toasters shall be provided with four removable and adjustable legs providing for a minimum of 4 inches space below the base of the toaster.

2.5 Lubrication. All bearings, revolving shafts, and other rotating or sliding parts requiring periodic lubrication shall be provided with means for lubrication and shall be lubricated prior to shipment.

2.6 Data name plate (Government unique requirement see 5.4). The toaster shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirement for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the toaster by rivets, screws or by welding in such a manner as to meet the applicable NSF requirements for this equipment. The plate shall bear the following information which shall be stamped, engraved, or applied by photosensitive means:

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:37Z
Check the source to verify that this is the currentversion before use.

National Stock Number
Procurement Instrument Identification Number and Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number, Serial Number and Date of Manufacture
Government Approved Manual Number (see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the toaster.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, complies with the referenced industry standards, and is the same as the product offered for sale in the commercial marketplace, except for those additional requirements/characteristics specified herein. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each toaster shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each toaster shall be cleaned, preserved, and cushioned to protect against corrosion, deterioration, and physical damage during shipping and storage. Disassembled parts and accessories shall be packaged in a fiberboard box conforming to type CF or SF, class domestic, style optional of PPP-B-636.

4.3.2 Export packing. Each toaster with its packaged parts, shall be packed in a wood-cleated plywood box conforming to type domestic, style optional of PPP-B-601, or a wood cleated fiberboard box conforming to class II of PPP-B-591. Each box shall be waterproofed with a sealed case liner conforming to type I, II, or IV, grade optional of MIL-L-10547. Each box shall be closed and strapped in accordance with PPP-B-601 or PPP-B-591, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:37Z
Check the source to verify that this is the current version before use.

4.3.3 Palletization. When specified, shipping containers shall be palletized in accordance with MIL-STD-147 (see 5.2).

4.4 Marking (commercial and export). Marking of unit packs, shipping containers and palletized unit loads shall be in accordance with MIL-STD-129, or ASTM D 3951, as applicable.

5. NOTES

5.1 Intended use. The toasters are intended for use where volume food serving is done.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Type and size of toaster required (see 1.).
c. When type I toasters are required to operate on other than 208 volts, 60 hertz, 1-phase power supply (see 2.2).
d. When type I toasters are to be supplied with a NEMA 6-30 plug (see 2.2).
e. When type II toasters have to operate on other than natural gas (see 2.3).
f. Power supply necessary to operate type II, when other than specified (see 2.3).
g. When removable and adjustable legs are not necessary (see 2.4).
h. Government approved manual number to be included on data name plate (see 2.6).
i. Selection of applicable packaging and packing required (see 4.1).
j. When palletization of shipping containers is required (see 4.3.3).

5.3 Sources of documents.

5.3.1 Sources for nongovernment association documents.

Standard WD1 - General Purpose Wiring Devices, is available from:

National Electrical Manufacturers Association (NEMA)
155 East 44th Street
New York, NY 10017

NSF Standard No. 4 - Commercial Cooking and Hot Food Storage, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

UL Standard No. 197 - Commercial Electric Cooking Appliances, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

ANSI Z21.41 - Quick-Disconnect Devices for Use With Gas Fuel
ANSI Z21.45 - Flexible Connectors of Other Than All Metal Construction for Gas Appliances
ANSI Z83.14 - Gas Counter Appliances

All available from:

American National Standards Institute (ANSI)
1430 Broadway
New York, NY 10018

or

The American Gas Association, Inc.
8501 East Pleasant Valley Road
Cleveland, OH 44131

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103.

5.3.2 Sources of governmental documents.

Military documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:37Z
Check the source to verify that this is the current version before use.

A-A-50010A

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review activities

Army - MD
Navy - MC, SA, YD
Air Force - 84
DLA - GS

User activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0719

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:37Z
Check the source to verify that this is the current version before use.