A-A-50017B
July 8, 1986
SUPERSEDING
A-A-50017A
March 29, 1985

COMMERCIAL-ITEM DESCRIPTION

CASE, PRODUCE DISPLAY, NON-REFRIGERATED

The General Services Administration has authorized the use of this Commercial Item Description.

1. Classification. This commercial item description covers produce display cases of the following types and sizes:

Type I - End Island
Not greater than 74 inches long by 43 inches deep by 46 inches high

Type II - Wide Island

Size 1 - Not greater than 97 inches long by 74 inches deep by 46 inches high

Size 2 - Not greater than 145 inches long by 74 inches deep by 46 inches high

Type III - Display case with canopy

Size 1 - Not greater than 97 inches long by 46 inches deep by 75 inches high

Size 2 - Not greater than 145 inches long by 46 inches deep by 75 inches high

2. Salient characteristics.

2.1 Design and Construction The type I and type II, sizes 1 and 2 shall consist of framing and shelves, insulation, outer shell, liner or panels, drain and cart bumpers. Type III, sizes 1 and 2 shall consist of framing and shelves,

FSC 7195

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

insulation, outer shell, liner or panels, drain, canopy top, fluorescent lights, mirror and cart bumpers Accessories to be supplied with the unit shall include water spray attachment, adjustable wire shelves or racks, bag racks, price tag molding, and splash guard (kick plate). The unit shall be provided with a minimum 1-inch drain. All units shall be provided with joiner kits and the necessary trim. Produce dividers shall be provided for each lineal foot. Cases to be joined together shall be marked and furnished with complete assembly components, drawings and installation instructions.

2 1 1 Framing and shelves. The framing members shall form a rigid structure capable of supporting loaded wire shelves and the entire unit during handling and shipment. The framing members shall be aluminum stainless steel or otherwise finished to prevent corrosion. The wire shelves shall be fabricated from stainless steel or from steel electro-zinc plated or electroless nickel plated with a protective coating.

2 1.2 Insulation expanded The insulation shall be expanded polystyrene, or expanded polyurethane having a K factor determined by using a 75°F mean temperature, expressed in British thermal units (BTU) per hour per degree F temperature difference per inch of thickness All space between the outer shell and inner shell shall be filled with insulation Loose fill type insulation shall not be acceptable The insulation shall be rigid as specified in 2 1 3 or foamed in place as specified in 2 1 4 The density of the expanded insulation shall be determined by cutting a 6 inch cube (1/8 of a cubic foot), weighing the cube, and multiplying the weight by 8. When foamed in place insulation is used the expanded foam shall be tested for conformance to the density requirement prior to beginning each day's production of cases

2 1 3 Insulation rigid Rigid insulation shall be pre-expanded polyurethane or pre-expanded polystyrene having a manufacturer's commercial K factor of not more than 0.15 for polyurethane and 0 25 for polystyrene and a minimum core density of 1 8 pounds per cubic foot.

2.1 4 Insulation foamed in place Foamed in place insulation shall be polyure-thane foam having a manufacturer's commercial rated K factor of not more than 0 15. The foam shall have a density of not less than 1 7 pounds per cubic foot when frothed and 1.9 pounds per cubic foot when poured.

2 1.5 Outer shell The front, top and ends of the outer shell of the case shall be enameling iron, aluminum or carbon steel The bottom of the case shall be steel, aluminum or galvanized steel The rear of the case shall be enameled iron, aluminum carbon steel or galvanized steel

2 1 6 Liner or panels The inner liner of the insulated panels of the case shall be aluminum alloy, fiberglass or galvanized steel. Seams shall be smooth so that the interior can be kept clean and sanitary Tapping plates and structural reinforcement (when required), shall be secured to the insulation side of the inner liner to provide support for brackets, shelves or other items to be fastened to, supported by, or hung on the exposed side of the inner liner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

2.1.7 Drain. Display cases shall be provided with a free flowing drain not less than 1 inch National Pipe Thread. Drains shall be accessible for normal installation.

2.1.8 Cart bumpers. Cart bumpers shall be stainless steel, aluminum or high-impact resistant plastic or rubber normally used for this purpose.

2.1 9 Water spray attachment. A retractable water spray attachment shall be provided on the display cases when specified (see 5.1), to help keep vegetables crisp and fresh The attachment hose shall be long enough to cover the length of the case provided.

2.1.10 Corner bumpers. When specified (see 5 2), upright bumpers shall be installed at the specified corners to prevent damage from merchandise stocking trucks. Corner bumpers shall be fabricated of 10 gauge, type 300 series stainless steel or 10 gauge chrome plated steel Corner bumpers may be either angle type, 6 inches by 6 inches by 24 inches high, or semi-circular 7-1/2 inch diameter by 24 inches high. Either type shall have a base with provisions for anchoring

2.1.11 Fluorescent lights. Canopy top shall be equipped with a minimum of one row of fluorescent lights with bulb reflectors extending over the entire length of the case.

2 1.12 Mirror. Canopy top shall be equipped with a mirror or mirrors sized and inclined for optimum display of case contents and extending over the entire length of the case.

2 2 Data name plate. The display cases shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the (item) by rivets, screws or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (list only if different from Manufacturer)
Manufacturer's Model Number

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

2.3 Finish. The exterior of the case shall be finished in baked synthetic enamel. The top, fronts, back and sides shall be green color No. 14187 of FED-STD-595.

2.4 Electrical characteristics. Unless otherwise specified (see 5.2), type III cases shall be designed to operate on 120 volts, single phase, 60 Hz power supply, and shall conform to Underwriters Laboratories Standard 471.

2.5 Workmanship. The case shall be complete and clean. All sharp corners, edges, or projections on the interior or exterior of the cases shall be eliminated or protected to prevent injury during cleaning, loading or removing products from the cases.

3. Quality assurance The contractor is responsible for assuring that the items furnished to the Government conform to all requirements specified in referenced documents and herein The contractor shall furnish a certificate of compliance certifying that the items being furnished comply with the stated requirements The Government reserves the right to inspect the items to verify the certification and may reject any item or lot of items when it is determined that:

a Any required component or design characteristic is missing or not as specified herein.

b. Any aspects of design, construction, assembly, function or finish is not in accordance with good commercial practice

c. Packaging packing and marking is not as specified.

4 PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.1).

4.2 Commercial.

4.2.1 Commercial packaging Each case shall be packaged in accordance with commercial practice

4.2.2 Commercial packing Each case shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies Containers shall comply with the National Motor Freight Classification, or Uniform Freight Classification as applicable

4.3 Export.

4.3.1 Export packaging. Each case shall be disassembled to the extent determined by the contractor to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be packaged in a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

weather-resistant fiberboard box constructed and closed in accordance with Method IV as specified in PPP-B-636. The case and parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration and physical damage during shipment and storage.

4.3.2 Export packing. Each case with its packaged parts shall be packed in a wood-cleated plywood box conforming to overseas type, style A or J, grade B, type 2 load of PPP-B-601, or nailed wood box conforming to class 2, style 2 or 4, grade B, type 2 load of PPP-B-621. Contents shall be cushioned, blocked and braced, and waterproofed in accordance with MIL-STD-1186 Each box shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable

4.4 Marking of interior boxes and shipping containers (commercial and export) Marking for interior boxes and shipping containers shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use The non-refrigerated produce display cases coverd by this Commercial Item Description are intended for use in commisaries for the display of produce.

5.2 Ordering data:

a Title, number, and date of this document
b Type case and applicable size required (see 1.)
c. Water spray attachment, if required (see 2.1 9)
d Number and type of corner bumpers to be supplied (see 2 1.10).
e Electrical characteristics when other than specified (see 2.4).
f Selection of applicable packaging and packing required (see 4.1)

5.3 Sources of information for nongovernment association documents.

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc , Traffic Department
1616 P Street, N.W , Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

Underwriters Laboratories, Inc.
333 Pfingsten Road
Northbrook, IL 60062

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

A-A-50017B

MILITARY INTERESTS:

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7195-0095

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.