INCH-POUND

A-A-50022C
March 19, 2025
SUPERSEDING
A-A-50022B
January 10, 1996

COMMERCIAL ITEM DESCRIPTION

GLOVES, WELDER'S, LEATHER, GAUNTLET

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers one type of welder's leather gauntlet gloves. The gloves are intended to be used by male and female welders across the Department of Defense (DoD) in a welder's shop environment.

2. CLASSIFICATION.

2.1 Sizes. The gloves shall be of one type in the following sizes (see 7.5):

Schedule of sizes.

XX-Small	Medium
X-Small	Large
Small	X-Large

3. SALIENT CHARACTERISTICS.

3.1 Description. The welder's gloves shall be leather, of the Gunn Cut pattern, with a one-piece continuous back. They shall be inseam sewn. All seams except the hem and two (2) rows of out seam stitching joining the front of the gauntlet to the palm shall include leather reinforcing welts. The seam at the base of the second and third fingers shall be out seam sewn with two (2) rows of stitching and shall be covered with a leather welt. Each pair of gloves shall be matched, paired, and tacked together so that they can be easily pulled apart without damage.

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System ASSIST online database https://assist.dla.mil.

AMSC / N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

3.2 Basic material.

3.2.1 Leather. The leather shall be flesh split cattlehide bends in accordance with Type VIII of MIL-DTL-32092 and shall be suitable for use in gloves. Both sides of the leather shall be smooth and free of loose flesh, middle splits, head splits and shoulder splits shall not be used. The leather shall be chrome tanned, 2-1/2 to 3-1/2 ounces in weight when tested as specified in ASTM D1813. Sampling of leather for all required tests shall be in accordance with FED-STD-311.

3.2.2 Color. The color of the gloves shall be light grey or cream or as specified in the contract or purchase order.

3.2.3 Lining materials.

3.2.3.1 Gauntlet, inside. The inside of the front and back leather gauntlet shall be lined with unbleached cotton duck cloth and shall conform to the requirements specified when tested in accordance with the methods listed below in Table I.

TABLE I. Physical requirements of gauntlet lining.

Characteristic	Requirement	Test Method
Weight, oz./yd ^{2}, (min.)	8.25	ASTM D3776/D3776M, Opt. C
Tear strength, lbf (min) Machine direction Transverse direction	 4 3	ASTM D1424

3.2.3.2 Back of hand, inside. There shall be a lining of knitted cool-cotton plaited cloth on the inside back of hand extending from the bottom of the gauntlet facing to the tips of the fingers. The cotton back of the knitted cloth shall be next to the leather. The knitted cloth shall be a wool/cotton fabric of not less than 50's grade fleece or pulled new wool. The cotton backing yarn shall be no more than 30 percent of the weight of the cloth when tested in accordance with AATCC 20A. The scoured and finished cloth shall weigh a minimum of 10 (± 1) ounces per square yard when tested in accordance with ASTM D3776/D3776M.

3.3 Requirements.

3.3.1 Labile sulfur. The use of dyes and compounds containing sulfur capable of oxidation to sulfuric acid is prohibited. The cloth shall be “Free” of labile sulfur when tested as specified in 3.3.1.1.

3.3.1.1 Presence of labile sulfur test. Two (2) 1.50 (± 0.01) gram samples from each sample unit shall be tested. Each of the two (2) samples shall be cut into very small pieces and placed into separate test tubes. Prepare an acidic tin(II) chloride (stannous chloride) solution by dissolving 100 g $SnCl_2$ (ACS grade) in 100 mL of 35% hydrochloric acid (ACS grade) and adding the mixture to 50 mL of distilled water. Prepare a lead acetate solution by dissolving 5.0 g of lead

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

acetate (CP reagent grade) in a small amount of distilled water and diluting to a total of 100 mL. If the solution is not clear, add a few drops (one at a time) of glacial acetic acid until the solution is clear. The samples shall be submersed the acidic tin(II) chloride solution. A filter paper wet out with the lead acetate solution shall be placed over the top of the test tube. The test tube containing the textile sample, tin(II) chloride and wet filter paper shall be heated over a low flame until the solution is boiling. The solution should not be heated for more than 15 seconds. A brown to black stain on the filter paper should be evaluated as follows:

Free - The filter paper shows no discoloration or staining of any kind.
Slight - The filter paper shows a light tan to light brown discoloration stain.
Moderate - The filter paper shows a dark brown discoloration stain.
Severe - The filter paper shows a black color stain.

The rating shall be recorded. The results shall be recorded as “pass” or “fail.

3.4 Thread. The welder’s gloves shall be sewn with a commercially acceptable unbleached cotton thread in accordance with Type I or II of A-A-52094.

3.5 Combination size, identification, and instruction label. Each welder’s glove shall have a combination size, identification, and instructions label in accordance with Type VI, Class 4 of MIL-DTL-32075. The label shall be sewn on all sides, centered on inside back of the leather gauntlet and shall contain the following information:

ITEM DESCRIPTION (GLOVES)	S
CONTRACT NUMBER:	I
NATIONAL STOCK NUMBER (NSN)	Z
FUR, WOOL OR FIBER PRODUCTS ACT INFORMATION	E
CONTRACTOR’S NAME: (BOTTOM LABEL)	

3.5.1 Barcode hang tag. Each welder’s glove shall have a barcode label/hangtag conforming to Type VIII, Class 17 of MIL-DTL-32075. The bar-coding element shall be a 13-digit National Stock Number (NSN). There shall be a 12-digit Universal Product Code (UPC) number assigned for all NSNs by the contracting activity. The initials “UPC” must appear beneath the code. The barcode for NSN and UPC type shall be a medium to high density and shall be located so that it is completely visible on the gloves when it is folded and/or packaged as specified and so it causes no damage to the welder’s gloves.

3.6 Toxicity. Unless otherwise specified in the contract or procurement documents, the finished gloves, shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 3.6.1.

3.6.1 Toxicity test. When the toxicity requirement (see 3.6) can be demonstrated with historical use data, on the finishing treatments used, toxicity testing may not be required, (see 7.1.4 and 7.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. The finished gloves shall conform to the quality of the product established in this document. The welder's gloves shall be free from defects which would affect its serviceability, appearance, uniformity and quality assurance standards defined by the technical data in the procurement documents.

4. REGULATORY REQUIREMENTS. Unless otherwise specified, the offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation FAR, or the sustainable acquisition of EO 13693; as applicable. (See 7.1.3).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The welder's gloves shall meet the salient characteristics of this CID conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The finished welder's gloves offered must have been sold to the government or commercial market.

5.3 End item inspection procedures. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection of Attributes (see 7.2.2).

5.4 Visual examination. Each finished welder's gloves shall be examined for the defects listed in Table III as defined in ASTM D3990. The lot size shall be expressed in units of paired gloves. The sample unit shall be one (1) pair of gloves.

TABLE III. Visual examination defects.

Material defects: Any hole, cut, tear, permanent fold, pleat, or crease; any spot or stain on outside, discoloration, color or type of leather not as specified, any serious material defects or objectionable odor.
Stitches, seams and stitching: Loose, broken or skipped stitches, needle chew, any part caught in an unrelated operation or stitching, raw edge, thread ends not removed, any seam slippage, re-stitching, pleating or puckering; distorted, open, pulled or snagged stitches, twisted, ragged or inconsistent edge.
Workmanship: Any component part omitted, twisted, not specified size, missing, misplaced or distorted parts; poorly shaped, any dimension of item not as specified; design not as specified. Failure to meet product conformance; serviceability, reliability and quality of materials as defined by this document.
Label(s): Missing, incorrect, or illegible; bar code or UPC code label omitted or not readable by scanner; human-readable interpretation (HRI) omitted or illegible; bar code not visible on folded packaged item, bar code label causes damage to the item.
Packaging: Not packaged in accordance with the contract or procurement documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

5.5 Acceptance criteria. Acceptance criteria shall be as specified in the contract or procurement documents (see 7.5).

6. PACKAGING. The preservation, packing and marking shall be as specified in the contract or purchase order (see 7.5).

7. NOTES.

7.1 Source of Government documents:

7.1.1 Copies of Government documents are available online at https://quicksearch.dla.mil.

7.1.2 EPA and EO 13693 information is available online at https://www.epa.gov.

7.1.3 Federal Acquisition Regulations (FAR) are available online at https://acquisition.gov.

7.1.4 Toxicity testing. If dermal toxicity testing is required, it will be conducted in accordance with Title 40, Protection of Environment, Code of Federal Regulations current edition and applicable sections, which are also consistent with the OECD tests:

Skin Sensitization 406 and Dermal Irritation 404 (https://www.oecd-ilibrary.org/environment/oecd-guidelines-for-the-testing-of-chemicals-section-4-health-effects_20745788?page=1).

Dermal Sensitization (https://www.law.cornell.edu/cfr/text/40/798.4100).
Dermal Toxicity (https://www.law.cornell.edu/cfr/text/40/798.2250).

7.2 Source of non-Government documents.

7.2.1 AATCC Test Methods are available for purchase online at https://aatcc.org.

7.2.2 ASQ/ANSI Z1.4 – Sampling Procedures are available online at https://asq.org.

7.2.3 ASTM Standards are available for purchase online at https://www.astm.org.

7.3 Intended use. The welding gloves are intended to be used by male and female welders across the Department of Defense.

7.4 Certificate of compliance. The contracting activity may select to accept a certificate of compliance for a stated requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.

7.5 Ordering data. Acquisition documents should specify the following

a. Title, number, and date of this CID.
b. Component sizes required (see 2.1).
c. Color required (see 3.2.1).
d. When toxicity testing is required (see 3.6).
e. Product conformance (see 5.1).
f. Acceptance criteria (see 5.5).
g. Packaging requirements (see 6.).

7.6 National Stock Number (NSNs). The following is a list of NSNs assigned that correspond to this CID. This list may not be indicative of all possible NSNs associated with the CID.

NSN	Size
8415-01-054-4371	XX-Small
8415-01-054-4370	X-Small
8415-00-269-0432	Small
8420-00-268-7860	Medium
8415-00-268-7859	Large
8414-00-269-0433	X-Large

7.7 Key words.

Handwear
Protection

MILITARY INTEREST

Custodians:
Army – GL
Navy – NU
Air Force – 11

Review activities:
Navy – CG1, MC

CIVIL AGENCY COORDINATING ACTVITY:
GSA-FAS

Preparing activity
DLA-CT

(Project: 8415-2024-014)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:37Z
Check the source to verify that this is the current version before use.