MIL-F-27629D(USAF)
AMENDMENT 2
13 May 1981

SUPERSEDING
AMENDMENT 1
1 AUG 1973

MILITARY SPECIFICATION

FILTER-SEPARATOR, LIQUID FUEL FFU-1/E

This amendment forms a part of Military Specification MIL-F-27629D(USAF) dated 2 July 1970.

PAGE 1

2.1 Add:

"MIL-STD-882 System Safety Program for Systems and Associated Subsystems and Equipment; Requirements for".

PAGE 2

2.2 Add:

"DEPARTMENT OF LABOR, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

Occupational Safety and Health Act (OSHA) with Supplemental Revisions

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)"

PAGE 3

3.4.1 Add new paragraph:

"Reclaimed Materials. Recycled and recovered raw materials shall be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. None of the above shall be interpreted to mean that the use of used or rebuilt products will be allowed."

PAGE 5

3.7.5 Differential pressure gage. Delete this paragraph in its entirety.

3.7.5.1 Differential pressure indicator (bellows type). Delete first sentence and substitute the following:

"A bellows type differential pressure indicator shall be provided with the filter separator."

FSC 4330

Source: https://assist.dla.mil -- Downloaded: 20261O-20T12:32Z
Check the source to verify that this is the current version before use.

MIL-F-27629D(USAF)
AMENDMENT 2
13 May 1981

SUPERSEDING
AMENDMENT 1
1 AUG 1973

MILITARY SPECIFICATION

FILTER-SEPARATOR, LIQUID FUEL FFU-1/E

This amendment forms a part of Military Specification MIL-F-27629D(USAF) dated 2 July 1970.

PAGE 1

2.1 Add:

"MIL-STD-882 System Safety Program for Systems and Associated Subsystems and Equipment; Requirements for".

PAGE 2

2.2 Add:

"DEPARTMENT OF LABOR, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

Occupational Safety and Health Act (OSHA) with Supplemental Revisions

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)"

PAGE 3

3.4.1 Add new paragraph:

"Reclaimed Materials. Recycled and recovered raw materials shall be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. None of the above shall be interpreted to mean that the use of used or rebuilt products will be allowed."

PAGE 5

3.7.5 Differential pressure gage. Delete this paragraph in its entirety.

3.7.5.1 Differential pressure indicator (bellows type). Delete first sentence and substitute the following:

"A bellows type differential pressure indicator shall be provided with the filter separator."

FSC 4330

Source: https://assist.dla.mil -- Downloaded: 202610-20T12:32Z
Check the source to verify that this is the current version before use.