NOT MEASUREMENT SENSITIVE

MIL-I-3575/23C
15 February 1990
SUPERSEDING
MIL-I-3575/23B
31 MARCH 1969

MILITARY SPECIFICATION SHEET

INSIGNIA, BRANCH OF SERVICE, OFFICERS, INSPECTOR GENERAL

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3575.



Dash no.:
-1: Regular
-2: Subdued

MATERIAL:
-1: Gilding metal
-2: Red brass or zinc aluminum

DIMENSIONS (Inches):
HEIGHT (Overall): 3/4 inch (1.91 cm) (REF)
THICKNESS (At thickest point): .080 inch ± .005 inch (0.203 cm) ± (0.012 cm)

FINISH:
-1: Letters hard enameled. Gold plated mirror-like polished
-2: Dull flat black enamel

NOTES:
1. Blue enamel shall match TIOH color chip no. 18 or the standard sample.
2. The attaching device shall be prong and clutch type. The prongs shall be located on the centerline of the fasces, equidistant from each end and 5/8 inch ± 1/64 inch (1.59 cm) ± (0.04 cm) apart.
3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer.
4. The enamel for dash no. 2 shall match chip no. 37038 of FED-STD 595.
5. The insignia shall be pierced as shown.

Custodian:
Army-IH

Preparing Activity:
Army-IH

Review Activity:
DLA-CT

Project no. 8455-0447

User Activity:
Army-SM

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:20Z
Check the source to verify that this is the current version before use.