NOT MEASUREMENT SENSITIVE

MIL-I-3575/27B
15 February 1990
SUPERSEDING
MIL-I-3575/27A
31 March 1969

MILITARY SPECIFICATION SHEET

INSIGNIA, BRANCH OF SERVICE, OFFICERS, TRANSPORTATION CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3575.



Dash No:
-1: Regular
-2: Subdued

MATERIAL:
-1: Red brass
-2: Red brass or zinc aluminum

DIMENSIONS:
CIRCUMSCRIBING DIAMETER: 1 inch (2.54 cm) (REF)
THICKNESS (At thickest point): .080 inch ± .005 inch (0.203 cm) ± (0.012 cm)

FINISH:
-1: Gold plated matte, finish with polished highlights.
-2: Dull flat black enamel

NOTES:
1. Attaching device shall be prong and clutch type. Prongs shall be located on the horizontal center line, equidistant from each end and 3/4 inch ± 1/64 inch (1.91 cm) ± (0.04 cm) apart.
2. The enamel for dash no.2 shall match chip no. 37038 of FED-STD 595.
3. Pierced areas shall be as indicated.

Custodians:
Army-IH

Preparing Activity:
Army-IH

Review Activity:
DLA-CT

Project no. 8455-0447

User Activity:
Army-SM

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:21Z
Check the source to verify that this is the current version before use.