NOT MEASUREMENT SENSITIVE

MIL-I-3575/31C
15 February 1990
SUPERSEDING
MIL-I-3575/31B
31 March 1969

MILITARY SPECIFICATION SHEET

INSIGNIA, BRANCH OF SERVICE, OFFICERS, MILITARY INTELLIGENCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3575.



Dash No.:
-1: Regular
-2: Subdued

MATERIAL:
-1: Red brass
-2: Red brass or zinc aluminum

DIMENSIONS:
HEIGHT (Overall): 1-1/4 inch (3.18 cm) (REF)
THICKNESS (At thickest point): .125 inch ± .005 inch (0.317 cm) ± (0.012 cm)

FINISH:
-1: Soft baked enameled. Gold plated mirror-like polished finish.
-2: Dull flat black enamel

NOTES:
1. Enameled area shall be as indicated. Blue enamel color shall match TIOH chip no. 20 or the standard sample.
2. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and 5/8 inch ± 1/64 inch (1.59 cm) ± (0.04 cm) apart.
3. The enamel for dash no. 2 shall match chip no.37038 of FED-STD 595.

Custodian:
Army - IH

Preparing Activity:
Army - IH

Review Activity:
DLA-CT

Project no. 8455-0447

User Activity:
Army - SM

FSC 8455

AMSC N/A

DISTRIBUTION STATEMENT A. Approve for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:22Z
Check the source to verify that this is the current version before use.