INCH-POUND

MIL-F-70807A (AR)
30 November 1994
SUPERSEDING
MIL-F-70807 (AR)
11 March 1988

MILITARY SPECIFICATION

FUZE, PD, M745 (LESS BOOSTER AND LEAD)

This specification is approved for use by the U.S. Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements and acceptance criteria for Fuze, Point Detonating, M745, Less Booster and Lead.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (See 6.2).

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specifications for

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander, U.S. Army ARDEC, ATTN: AMSTA-AR-EDE-S, Picatinny Arsenal, NJ 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A **FSC 1390**

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from DODSSP - Customer Service, Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT

11927103 - Fuze, PD, M745 (Less Booster and Lead)

PACKAGING

9347415 - Packing & Marking of Box, Fiberboard for Fuze, Multi-Option, M734 & Fuze, PD, M745

(Copies of other Government documemts, drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. (See contract provisions for additional precedence criteria).

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.3 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 11927103, all associated drawings, and with all requirements specified in applicable specifications and drawings.

3.4 Ballistic performance requirements.

3.4.1 Premature function. There shall be no premature function of the fuze during ballistic testing. Premature function is defined as the initiation of the fuze explosive components causing the functioning of the cartridge in the mortar tube or less than 100 meters in flight from the muzzle.

3.4.2 Parts separation. There shall be no parts separation of the fuze during flight such that it creates instability of the cartridge causing short or out of pattern rounds.

3.4.3 Early function. There shall be no early function of the fuze during flight prior to normal impact function.

3.4.4 Proper function. The loaded fuze with booster and lead, shall function on impact.

3.5 Environmental requirements.

3.5.1 Temperature and humidity. The fuze shall meet the requirements of Test C1 of MIL-STD-331 and of 4.5.3.1.

3.5.2 Transportation handling and vibration. The fuze shall meet the requirements of Tests A5 and B2 of MIL-STD-331 and of 4.5.3.2.

3.6 Component performance requirements.

3.6.1 Safety and arming (S&A) device tests.

3.6.1.1 Spring gear latch test (non-destructive, non-arming). With the zig-zag body in the forward position, the spring gear latch shall prevent rotation of more than three revolutions of the turbine when subjected to an air pressure of 0.206 +.000/-.006 psig. in accordance with 4.5.4.1.

3.6.1.2 Acceleration sensor non-function test. The zig-zag body shall not lock down when subjected to an acceleration of 215g min for a minimum 1.0 second.

3.6.1.3 Acceleration sensor function test. The zig-zag body shall lock down when subjected to an acceleration of 395g max for a minimum of 1.0 second.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.6.1.4 Arming time. With the zig-zag body locked down, with air pressure of .206 +.000/-.006 psig on the turbine, and mated with a standard M745 turbine alternator, the S&A rotor shall arm between 2.5 and 4.0 seconds at ambient temperature. At -50 F., the S&A rotor shall arm between 2.5 and 5.5 seconds with a mean arming time not to exceed 4.7 seconds.

3.6.1.5 Spring gear latch test (destructive, non-arming). With the zig-zag body in the forward (up) position, the spring gear latch shall prevent rotation of the gear train with a minimum air pressure of 0.7 ± .05 psig in accordance with 4.5.4.5 applied to the turbine for at least 3 seconds. The S&A shall have passed this test if the following are met:

The jackscrew setting does not become more than .659 inch. This dimension applies with the zig-zag locked down and the rotor assembly in the fully seated (toward the barrier) position. The S&A device need not be operable after the test but shall be in the safe position following the test.

3.7 Workmanship. All parts and assemblies shall be finished and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning methods shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined.

3.8 Comparison samples. A comparison sample of twenty-four (24) fuzes shall be submitted to a technical agency designated by the procuring activity for each production lot.

3.9 Special defects. The Government has deemed that Special Defects listed in this document warrant special consideration and handling by the contractor. If one or more of these defects are found, the contractor shall shut down the line, investigate for defect cause, correct the process (prior to restart), and at restart, recheck that the correction was adequate by a method determined by the contractor to be effective. Screening shall not be considered to be a viable process correction. An incident report must be forwarded to the cognizant technical organization (see 6.6) within twenty-four (24) hours of each occurrence.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to the prescribed requirements.

4.1.1 Responsibility of compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall be part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation with provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed in TABLE I and Figure 1 in the quantities indicated.

TABLE I - First article inspection.

PART NUMBER	NOMENCLATURE	QUANTITIES
11722595	Pin, Firing	10
11722976	Cover, Fuze Base	10
11722986	Jackscrew	10
11722987	Wheel, Jackscrew	10
11722988	Shaft, Wheel & Worm	10
11722989	Shaft, Worm Drive	10
11723011	Spring, Gear Latch	10
11723018	Body, Zig-Zag	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

11723019	Cover, Rotor	10
11723020	Nose, Ogive	10
11723028	Barrier, Fuze Base	10
11723031	Insert, Detonator	10
11723032	Housing, Primer Cage	10
11723035	Can, Rotor	10
11723036	Rotor Subassembly	10
11723038	Plate, Switch	10
11723048	Spring, Bias	10
11723093	Spring, Stab Primer	10
11723105	Cam	10
11723117	Pin, Groove	10
11723119	Spring, Rotor	10
11723120	Spring, Lock	10
11723131	Lock, Rotor	10
11723132	Spring, Rotor Lock	10
11736664	Post, Center	10
11736666	Spring, Grounding	10
11737592	Grease Lubricating Mixture	1 sample
11927081	Cage, Detonator	10
11927105	Safety and Arming Device (Loaded)	10
11927106	Alternator & Switch Plate Assembly	10
11927107	Primer Housing Assembly	10
11927108	Fuze Base Cover Assembly	10
11927109	Fuze Base Assembly	10
11927122	Rotor Assembly	10
11927123	Head Assembly	10
11927124	Nose, Insert, M745	10
11927125	Base Fuze	10
11927134	Base, Ogive	10

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in this detail specification (See 4.3.1) and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

85

SAFETY & ARMING DEVICE
11927120

30 | 25 | 30

-25 F | 70 F | 145 F

5 | 25 | 25 | 25 | 5

CHARACTERISTICS	REQ. PARA.	TEST PARA.	ACC	REJ
SPRING GEAR LATCH (NON-DESTRUCTIVE)	3.6.1.1	4.5.4.1	0	1
ZIG ZAG NON-FUNCTION	3.6.1.2	4.5.4.2	0	1
ZIG ZAG FUNCTION	3.6.1.3	4.5.4.3	0	1
ARMING TIME	3.6.1.4	4.5.4.4	0	1

CHARACTERISTICS	REQ. PARA.	TEST PARA.	ACC	REJ
SPRING GEAR LATCH (DESTRUCTIVE)	3.6.1.5	4.5.4.5	0	1

260

FUZE, PD, M745
(LESS BOOSTER & LEAD)
11927103

24 | 44 | 192

MIL-STD-331 TESTS
WITH
INERT BOOSTER & LEAD

TEST	REQ. PARA.	TEST PARA.	N	SAFE ACC	SAFE REJ	
TEMP & HUMIDITY	3.5.1	4.5.3.1	20	0	1	GRP C (10)
TRANSPORTATION HANDLING & VIBRATION	3.5.2	4.5.3.2	24	0	1	GRP D (10)

ENGINEERING CONTROL SAMPLES

BALLISTIC TEST w/ LOADED FUZE (11927102)
REQ. PARA. 3.4.1 - 3.4.4
TEST PARA. 4.5.2

GROUP	CHARGE	QE	145 F	70 F	-50 F	TOTAL
A	0	85 °	48	48	—	96
B	4	45 °	32	32	32	96
C	4	45 °	10	—	—	10
D	4	45 °	—	—	10	10

ACCEPTANCE CRITERIA
DUDS = 3/4 FOR GROUPS A AND B COMBINED
EARLY AND PREMATURE = 0/1 ALL GROUPS
DUDS = 2/3 FOR GROUPS C AND D COMBINED

FIGURE 1
FIRST ARTICLE INSPECTION FLOW CHART

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All materials submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with the requirements.
In addition, inspection lots of fuzes shall contain components that meet the following criteria:

a. M55 detonators from one lot interfix number from one manufacturer.

b. M61 detonators from one lot interfix number from one manufacturer.

c. Turbine alternators from one lot interfix number from one manufacturer.

d. The lot size shall be a maximum of 50,000 fuzes or one month's production, whichever is smaller. Minimum lot size for initial two lots of new production is 1,000 and 5,000 thereafter.

4.4.2 Examinations and test.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The Contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE II - Attribute sampling inspection

Lot Size	Inspection Levels					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, variables sampling or other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.4). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall specifically be incorporated into the contractor's quality program or detail inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Fuze, PD, M745 (Less Booster and Lead)	1 OF 1	11927103
			NEXT HIGHER ASSEMBLY: 11927102

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	S&A in the armed position	100%	3.3	Gage/Probe
2	Premature function during ballistic test	(a) (b)	3.4	4.5.2
Major				
101	Overall length	Level III	3.3	Gage
102	Worm shaft drive and alternator shaft not engaged	Level III	3.3	Radiograph
103	Ballistic - Charge 0, 45 + 10 deg QE	(a) (c)	3.4	4.5.2
104	Ballistic - Charge 1, 45 + 10 deg QE	(a) (c)	3.4	4.5.2
105	Ballistic - Charge 4, 45 + 10 deg QE	(a) (c)	3.4	4.5.2
Minor				
201	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

(a) After loading with boosters and leads, fifty-four (54) samples shall be fired at Charge 4, thirty-six (36) at Charge 0 and eighteen (18) at Charge 1 at a Government approved proving ground. For Charge 4, 18 each at -50 F, 70 F and 145 F. For Charge 0, 18 each at 70 F and 145 F. For Charge 1, 18 at -50 F.

(b) Any premature function shall be cause for immediate test suspension for failure analysis and lot rejection.

(c) A total of three (3) or more duds or an early function from the three groups (combined) shall be cause for lot rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.2	Pin, Firing	SHEET 1 OF 1	11722595
			NEXT HIGHER ASSEMBLY: 11927108

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of pin	Level III	3.3	Gage
102	Flatness of pin tip	Level III	3.3	Gage
103	Pin tip angle	Level III	3.3	Gage
Minor				
201	Diameter of pin	Level V	3.3	Gage
202	Diameter of pin head	Level V	3.3	Gage
203	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Cover, Fuze Base	1 OF 1	11722976
			NEXT HIGHER ASSEMBLY: 11927108

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.200 tab width	Level III	3.3	Gage
Minor				
201	.110 thickness	Level V	3.3	Gage
202	Zig-zag hole diameter	Level v	3.3	Gage
203	.206 center hole diameter	Level V	3.3	Gage
204	.020 flat	Level V	3.3	Gage
205	Radius at section F-F	Level V	3.3	Gage
206	Small outer diameter	Level V	3.3	Gage
207	Firing pin hole diameter	Level V	3.3	Gage
208	Firing pin head cavity diameter	Level V	3.3	Gage
209	Firing pin head cavity outer diameter	Level V	3.3	Gage
210	Length of firing pin head cavity	Level V	3.3	Gage
211	.040 tab	Level V	3.3	Gage
212	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Jackscrew	1 OF 1	11722986
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Overall length	100%	3.3	Gage
102	Width of flats	Level III	3.3	Gage
103	.090 diameter	Level III	3.3	Gage
104	Pitch diameter	Level III	3.3	Gage
105	Major diameter	Level III	3.3	Gage
106	Thread length	Level III	3.3	Gage
107	.270 length	Level III	3.3	Gage
Minor				
201	Evidence of poor wormanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Checklist source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Wheel, Jackscrew	1 OF 1	11722987
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Large outer diameter	Level V	3.3	Gage
202	Overall length	Level V	3.3	Gage
203	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20 10:43:02
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Shaft, Wheel and Worm	1 OF 1	11722988
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Shoulder to shoulder length	Level V	3.3	Gage
202	Diameter of ends (2 places)	Level V	3.3	Gage
203	Gear composite error	Level V	3.3	Gage
204	Worm composite error	Level V	3.3	Gage
205	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Shaft, Worm Drive	1 OF 1	11722989
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Tip angles (2 places)	Level III	3.3	Gage
102	Large outer diameter	Level III	3.3	Gage
103	Small outer diameter	Level III	3.3	Gage
104	Concentricity	Level III	3.3	Gage
105	Overall length	Level III	3.3	Gage
Minor				
201	Operating diameter	Level V	3.3	Gage
202	Axial pitch	Level V	3.3	Gage
203	Outside diameter	Level V	3.3	Gage
204	Root diameter	Level V	3.3	Gage
205	Total composite error	Level V	3.3	Gage
206	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Spring, Gear Latch	1 OF 1	11723011
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Overall length	Level III	3.3	Gage
102	Length from coil center to bend	Level III	3.3	Gage
103	Bend radius (2 places)	Level III	3.3	Gage
Minor				
201	.055 bend offset	Level V	3.3	Gage
202	Height of coils	Level V	3.3	Gage
203	10 degree angle	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Body, Zig Zag	1 OF 1	11723018
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width of track	Level III	3.3	Gage
102	Length of front body	Level III	3.3	Gage
103	Cam track layout	Level III	3.3	Gage
104	Diameter of front body	Level III	3.3	Gage
Minor				
201	Diameter of rear body	Level V	3.3	Gage
202	Length of rear body	Level V	3.3	Gage
203	Inner diameter	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Cover, Rotor	1 OF 1	11723019
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.112 width of notch	Level III	3.3	Gage
102	Center hole inner diameter	Level III	3.3	Gage
Minor				
201	Rotor spring tab thickness	Level V	3.3	Gage
202	Outer diameter	Level V	3.3	Gage
203	Flatness of bottom	Level V	3.3	Gage
204	Location of .098 tab (2 places)	Level V	3.3	Gage
205	Width of .198 tab (2 places)	Level V	3.3	Gage
206	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Nose, Ogive	1 OF 1	11723020
			NEXT HIGHER ASSEMBLY: 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outer diameter	Level III	3.3	Gage
Minor				
201	.466 inner diameter	Level V	3.3	Gage
202	1.445 inner diameter at base	Level V	3.3	Gage
203	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Barrier, Fuze Base	1 OF 1	11723028
			NEXT HIGHER ASSEMBLY: 11927109

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Structual or process defects	Note (a)	3.3	Explosive test
102	Overall thickness	Level III	3.3	Gage
103	Lead charge hole diameter	Level III	3.3	Gage
104	Small outer diameter	Level III	3.3	Gage
105	True position of small outer diameter	Level III	3.3	Gage
106	Center hole diameter	Level III	3.3	Gage
107	True position of center hole	Level III	3.3	Gage
Minor				
201	Knurl diameter	Level V	3.3	Gage
202	Knurl height	Level V	3.3	Gage
203	Presence of foreign matter	Level V	3.3	Visual (200 x mag)
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

(a) Twenty-five (25) samples each shall be conditioned to -50 degrees F and +145 degrees F for two hours minimum. The barrier shall be assembled into a loaded S&A (11927105) with a lead. The primary explosives shall be initiated with the rotor in the out-of-line position. Evidence of fragmentation, cracking or break through of the barrier, bulging in excess of .015" on the booster side face, or scorching of lead charge explosives shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Insert, Detonator	1 OF 1	11723031
			NEXT HIGHER ASSEMBLY: 11927107

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Large forward outer diameter	Level V	3.3	Gage
202	Small forward outer diameter	Level V	3.3	Gage
203	.115 length	Level V	3.3	Gage
204	.180 length	Level V	3.3	Gage
205	.083 length	Level V	3.3	Gage
206	M61 output hole diameter	Level V	3.3	Gage
207	M61 cavity diameter	Level V	3.3	Gage
208	Rear outer diameter	Level V	3.3	Gage
209	Flange diameter	Level V	3.3	Gage
210	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.14	Housing, Primer Cage	SHEET 1 OF 1	11723032
			NEXT HIGHER ASSEMBLY: 11927107

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Outer diameter	Level V	3.3	Gage
202	Large inside diameter	Level V	3.3	Gage
203	Small inside diameter	Level V	3.3	Gage
204	Overall length	Level V	3.3	Gage
205	.090 tab width	Level V	3.3	Gage
206	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 — Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Can, Rotor	1 OF 1	11723035
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Boss diameter	Level III	3.3	Gage
102	Location of boss	Level III	3.3	Gage
Minor				
201	Depth of scallop (view A-A)	Level V	3.3	Gage
202	1.082 diameter	Level V	3.3	Gage
203	Location of 1.082 diameter	Level V	3.3	Gage
204	Location of .062 diameter hole	Level V	3.3	Gage
205	Flatness	Level V	3.3	Gage
206	Diameter of cam hole	Level V	3.3	Gage
207	Location of cam hole	Level V	3.3	Gage
208	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assistdla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Rotor	1 OF 1	11723036
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of primer cage output hole	Level III	3.3	Gage
102	Location of primer cage output hole	Level III	3.3	Gage
103	Diameter of rotor lock hole	Level III	3.3	Gage
104	Location of rotor lock hole	Level III	3.3	Gage
105	Gear latch slot width	Level III	3.3	Gage
106	Diameter of zig zag cavity	Level III	3.3	Gage
107	Location of zig zag cavity	Level III	3.3	Gage
Minor				
201	Parallelism of top surface	Level V	3.3	Gage
202	Overall height	Level V	3.3	Gage
203	Outer diameter	Level V	3.3	Gage
204	.310 depth	Level V	3.3	Gage
205	.281 diameter of jackscrew cavity	Level V	3.3	Gage
206	Location of jackscrew cavity	Level V	3.3	Gage
207	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Plate, Switch	1 OF 1	11723038
			NEXT HIGHER ASSEMBLY: 11927106

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of alignment holes (3 places)	Level III	3.3	Gage
102	True position of alignment holes	Level III	3.3	Gage
103	Diameter of semi-perf (2 places)	Level III	3.3	Gage
104	Location of semi-perf (2 places)	Level III	3.3	Gage
105	Distance from center hole to tab end	Level III	3.3	Gage
106	.192 length of tab	Level III	3.3	Gage
Minor				
201	Tab width	Level V	3.3	Gage
202	Thickness	Level V	3.3	Gage
203	Outer diameter	Level V	3.3	Gage
204	Flatness	Level V	3.3	Gage
205	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Spring, Bias	1 OF 1	11723048
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Load at compressed length of .526	Level III	3.3	Gage
Minor				
201	Inside diameter	Level V	3.3	Gage
202	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-26 10:43:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Spring, Stab Primer	1 OF 1	11723093
			NEXT HIGHER ASSEMBLY: 11927107

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Incapable of working in .312 diameter hole	Level V	3.3	Gage
202	Incapable of working over a .268 diameter rod	Level V	3.3	Gage
203	Load at compressed length of .234"	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assistdocs.mil - Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Cam	1 OF 1	11723105
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Strength of arm	Note (a)	3.3	Force Test (a)
102	Perpendicularity	Note (a)	3.3	Gage
103	Height from top of arm to cam bottom	Level III	3.3	Gage
104	Length of arm	Level III	3.3	Gage
Minor				
201	Diameter of cam	Level V	3.3	Gage
202	Overall height	Level V	3.3	Gage
203	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

(a) A sample of fifty (50) shall be tested in accordance with Note 5 of Dwg. 11723105. Any fracture or deformation exceeding perpendicularity requirement shall be classed defective and shall be cause for rejection.

Source: http://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Pin, Groove	1 OF 1	11723117
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of ends (2 places)	Level III	3.3	Gage
102	Diameter of knurl	Level III	3.3	Gage
Minor				
201	Surface finish (2 places)	Level V	3.3	Gage
202	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.22	Spring, Rotor	1 OF 1	11723119
			NEXT HIGHER ASSEMBLY: 11723120

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Torque at 345 degrees	Level III	3.3	Torque test
102	Torque at 525 degrees	Level III	3.3	Torque test
Minor				
201	Free outside diameter	Level V	3.3	Gage
202	Incapable of working over .186 diameter rod	Level V	3.3	Gage
203	.220 length (2 places)	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Spring, Lock	1 OF 1	11723120
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Length of arm	Level III	3.3	Gage
Minor 201	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2020-10-20T04:00Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23.1	Lock, Rotor	1 OF 1	11723131
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.107 diameter	Level III	3.3	Gage
102	.186 width	Level III	3.3	Gage
103	.103 diameter	Level III	3.3	Gage
104	.200 length	Level III	3.3	Gage
Minor				
201	.420 length	Level V	3.3	Gage
202	.070 diameter	Level V	3.3	Gage
203	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.24	Rotor Lock Spring	1 OF 1	11723132
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Outer diameter	Level V	3.3	Gage
202	Working over a .072 diameter rod	Level V	3.3	Gage
203	Load at compressed length of .215	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20 04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Post, Center	1 OF 1	11736664
			NEXT HIGHER ASSEMBLY: 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Large base outer diameter	Level V	3.3	Gage
202	Small base outer diameter	Level V	3.3	Gage
203	.440 diameter	Level V	3.3	Gage
204	.378 width	Level V	3.3	Gage
205	.386 width (2 places)	Level V	3.3	Gage
206	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Spring, Grounding	1 OF 1	11736666
			NEXT HIGHER ASSEMBLY: 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width of kick-ins (3 places)	Level III	3.3	Gage
102	.055 height (2 places)	Level III	3.3	Gage
103	.035 height	Level III	3.3	Gage
104	Improper plating	Level III	3.3	Gage
Minor				
201	Outer diameter	Level V	3.3	Gage
202	Thickness	Level V	3.3	Gage
203	Radius of kick-ins (3 places)	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assistdocs.mil... Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.27	Grease Lubricating Mixture	1 OF 1	11737592
			NEXT HIGHER ASSEMBLY: 11927122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Proportion of grease to freon	100%	3.3	(a)
Minor	None defined			

NOTES:

(a) Draw a sample of the mixture immediately after lubrication. One sample must be drawn for each batch of parts lubricated. Weigh sample at 75 ± 10 degrees F and place in an approved evaporation dish of known weight to a depth of no greater than .030 inch. Place in oven set at 180 degrees ± 10 degrees F for two hours. Weight of residue shall be between 11.3% & 13.6% of the original weight. Alternate methods must be approved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.28	Cage, Detonator	1 OF 1	11927081
			NEXT HIGHER ASSEMBLY: 11927107

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Large inside diameter	Level III	3.3	Gage
102	Detonator output hole diameter	Level III	3.3	Gage
103	Shoulder diameter	Level III	3.3	Gage
104	.303 length	Level III	3.3	Gage
105	Small inside diameter	Level III	3.3	Gage
Minor				
201	.268 outer diameter	Level V	3.3	Gage
202	.042 length	Level V	3.3	Gage
203	Small outer diameter	Level V	3.3	Gage
204	.005 x 45 degrees Chamfer (3 places)	Level V	3.3	Gage
205	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.29	Safety and Arming Device (Loaded)	1 OF 1	11927105
			NEXT HIGHER ASSEMBLY: 11927103

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Zig zag body not in the safe position (up, into the hole of fuze base cover assembly)	100%	3.3	Probe
2	Non-locking of rotor assembly in safe position by jackscrew (Note 3 of 11927105)	100%	3.3	Manual/Probe (rotor remains in safe position with with zig-zag down)
3	Jackscrew setting	100%	3.3	Gage
Major				
101	Worm drive shaft gap too small	Level III	3.3	Gage
102	Rotor spring missing	Level III	3.3	See note (3) on Dwg. 11927105
103	Primer housing assembly height excessive	Level III	3.3	Gage
104	Primer housing assembly improperly oriented in keyed hole in rotor	Level III	3.3	Probe
Minor				
201	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.30	Alternator and Switch Plate Assembly	1 OF 1	11927106
			NEXT HIGHER ASSEMBLY 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Shaft protrusion	Level V	3.3	Gage
202	Improper heat staking	Level V	3.3	Visual
203	Location of switch plate	Level V	3.3	Gage
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.31	Primer Housing Assembly	1 OF 1	11927107
			NEXT HIGHER ASSEMBLY: 11927105

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Stab primer spring missing	Level III	3.3	Inversion Test (a)
102	Improperly oriented or missing M61 detonator	Level III	3.3	Visual
103	Improperly oriented or missing M55 detonator	Level III	3.3	Visual
104	M55 detonator above surface A	Level III	3.3	Probe/Visual
105	Improper staking of M55 detonator	Level III	3.3	Force test (b)
106	Binding of loaded primer cage	Level III	3.3	Manual
107	Improper staking of M61 detonator	Level III	3.3	Force test (b)
Minor				
201	Improper crimping of primer cage housing to detonator insert	Level V	3.3	Torque test (b)
202	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

(a) Detonator cage shall not slide downward when the output end is in the upward position.

(b) See notes on Drawing 11927107.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.32	Fuze Base Cover Assembly	1 OF 1	11927108
			NEXT HIGHER ASSEMBLY: 11927120

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Firing pin protrusion	Level III	3.3	Gage
102	Firing pin not retained or immobilized	Level III	3.3	Force test (a)
Minor				
201	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:
(a) See note 2 on Drawing 11927108.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.33	Fuze Base Assembly	1 OF 1	11927109
			NEXT HIGHER ASSEMBLY 11927120

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Location of lead hole to slot	Level III	3.3	Gage
102	Depth of fuze base barrier from shoulder	Level III	3.3	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.34	Safety and Arming Device (Unloaded)	1 OF 1	11927120
			NEXT HIGHER ASSEMBLY: 11927105

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
A	Spring gear latch test (non-destructive)	32 (a)	3.6.1.1	4.5.4.1
B	Acceleration sensor (non-function)	32 (a)	3.6.1.2	4.5.4.2
C	Acceleration sensor (function)	32 (a)	3.6.1.3	4.5.4.3
D	Arming time (70 degrees F)	32 (a) (b)	3.6.1.4	4.5.4.4
E	Arming time (-50 degrees F)	32 (a) (b)	3.6.1.4	4.5.4.4
F	Spring gear latch test (destructive)	20 (c)	3.6.1.5	4.5.4.5
Major	None defined			
Minor	None defined			

NOTES:

(a) One (1) or more defectives shall be cause for rejection of the lot. Same samples to be used on Test A, B, C, D and E. Samples may be returned to lot after being dried out at 90 degrees for 4 hours.

(b) Mean arming time not within the limits as specified in 3.6.1.4 shall be cause for lot rejection. Samples shall be temp. conditioned for 4 hours min.

(c) Twenty (20) new samples. One (1) or more defectives shall be cause for rejection of the lot

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.35	Rotor Assembly	1 OF 1	11927122
			NEXT HIGHER ASSEMBLY: 11927120

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special A	Jackscrew length less than .497	100%	3.3	Gage
Major				
101	Groove pin protrusion	Level III	3.3	Gage (prior to assembly of zig zag)
102	Misalignment of rotor can and rotor subassembly	Level III	3.3	Gage (a)
103	Lock spring missing	Level III	3.3	Visual
104	Rotor lock missing	Level III	3.3	Visual
105	Rotor lock spring missing	Level III	3.3	Visual
Minor				
201	Rotor can crimp	Level V	3.3	Visual
202	Height of flange top to rotor bottom	Level V	3.3	Gage
203	.603 Crimp height	Level V	3.3	Gage
204	.782 Maximum height	Level V	3.3	Gage
205	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:
(a) See note 9 of Drawing 11927122.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.36	Head Assembly	1 OF 1	11927123
			NEXT HIGHER ASSEMBLY: 11927103

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Depth of switch plate	Level V	3.3	Visual
202	Molding compound not visible in vent hole	Level V	3.3	Visual
203	Excessive molding compound above surface of ogive nose	Level V	3.3	Visual
204	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.37	Nose, Insert	1 OF 1	11927124
			NEXT HIGHER ASSEMBLY: 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	.462 diameter	Level V	3.3	Gage
202	Rear outer diameter	Level V	3.3	Gage
203	.312 diameter	Level V	3.3	Gage
204	.446 diameter	Level V	3.3	Gage
205	Overall length	Level V	3.3	Gage
206	Length to front shoulder	Level V	3.3	Gage
207	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.38	Base, Fuze	1 OF 2	11927125
			NEXT HIGHER ASSEMBLY: 11927109

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Flange diameter	Level III	3.3	Gage
102	Location of center of lead hole radius	Level III	3.3	Gage
103	Fuze intrusion length	Level III	3.3	Gage
104	Thread pitch diameter	Level III	3.3	Gage
105	Thread major diameter	Level III	3.3	Gage
106	1.410 diameter	Level III	3.3	Gage
107	Run out of 1.410 diameter	Level III	3.3	Gage
108	1.529 diameter	Level III	3.3	Gage
109	True position of 1.529 diameter	Level III	3.3	Gage
110	.970 diameter	Level III	3.3	Gage
111	True position of .970 diameter	Level III	3.3	Gage
112	Rotor cavity diameter	Level III	3.3	Gage
113	.258 depth	Level III	3.3	Gage
114	.650 depth	Level III	3.3	Gage
115	.204 slot	Level III	3.3	Gage
116	Location of .204 slot	Level III	3.3	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.38	Base, Fuze	2 OF 2	11927125
			NEXT HIGHER ASSEMBLY: 11927109

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Booster cap crimping diameter	Level V	3.3	Gage
202	.100 Length of crimping diameter	Level V	3.3	Gage
203	Length from barrier shoulder to rear end	Level v	3.3	Gage
204	.749 radius	Level V	3.3	Gage
205	.030 flange thickness	Level V	3.3	Gage
206	.980 diameter	Level V	3.3	Gage
207	Booster cavity diameter	Level V	3.3	Gage
208	.280 depth	Level V	3.3	Gage
209	.075 depth	Level V	3.3	Gage
210	.160 length	Level V	3.3	Gage
211	.085 depth	Level V	3.3	Gage
212	1.225 diameter	Level V	3.3	Gage
213	1.355 diameter	Level V	3.3	Gage
214	True position of 1.355 diameter	Level V	3.3	Gage
215	.030 depth	Level V	3.3	Gage
216	.062 depth	Level V	3.3	Gage
217	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-70807A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.39	Base, Ogive	1 OF 2	11927134
			NEXT HIGHER ASSEMBLY: 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Characters improper	Level III	3.3	Visual
102	Leg width (3 places)	Level III	3.3	Gage
103	Location of legs	Level III	3.3	Gage
104	Diameter to inner face of leg	Level III	3.3	Gage
105	Plating	Level III	3.3	Gage
106	.100 keying slot width	Level III	3.3	Gage
107	.250 keying slot width	Level III	3.3	Gage
108	.193 Groove centerline (3 places)	Level III	3.3	Gage
109	Height of longer legs (2 places)	Level III	3.3	Gage
110	Height of shorter leg	Level III	3.3	Gage
111	1.625 inner diameter	Level III	3.3	Gage
112	1.530 inner diameter	Level III	3.3	Gage
113	1.431 diameter	Level III	3.3	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.39	Base, Ogive	2 OF 2	11927134
			NEXT HIGHER ASSEMBLY: 11927123

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major (Cont'd)				
114	.706 depth	Level III	3.3	Gage
115	.770 depth	Level III	3.3	Gage
Minor				
201	Diameter to outer face of leg	Level V	3.3	Gage
202	Diameter of fill hole (2 places)	Level V	3.3	Gage
203	Base outer diameter	Level V	3.3	Gage
204	1.204 inner diameter	Level V	3.3	Gage
205	1.501 inner diameter	Level V	3.3	Gage
206	1.370 inner diameter	Level V	3.3	Gage
207	Evidence of poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article Inspection Flow Chart and Quality Conformance Inspection Classification of Characteristics.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.2 herein.

4.4.4.1 Special test equipment.

4.4.4.1.1 Safety and arming device tester. The S&A device tester shall be designed to mount the S&A under a stack load of 60 +/- 20 lbs, to provide the required air flow, to provide a calibrated M745 turbine alternator in a dummy nose or equivalent, and the necessary monitoring facilities to test the various S&A device tests. The air flow shall be such that the difference in indicated pressure at the test assembly input between a stopped and running T/A shall not be greater than 5%. The T/A used in the tester shall be checked, as a minimum once every 50 arming tests to assure meeting the T/A calibration requirements.

4.4.4.1.2 Centrifuge equipment. The centrifuge shall be of a type which will allow the unit under test to be positioned at a minimum distance of 10.0 inches from the center of rotation of the centrifuge to the center of the zig-zag body. Rotational speed of the centrifuge shall be capable of being measured to an accuracy of ± 1%.

4.5 Methods of inspection.

4.5.1 Materials, components and process. Compliance with all requirements of section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed. Certificates of Conformance shall contain sufficient information and test data to determine compliance to all specified requirements.

4.5.2 Ballistic test. The fuzes shall be assembled to 60mm, WP, M722 or 60mm, HE, M720 cartridges. All conditioned rounds shall be fired as soon as practical after removal from the conditioning chamber. Rounds conditioned at -50 F shall not be removed from the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

individual containers for longer than 15 seconds prior to firing to prevent frosting. The fuzed rounds shall be fired from a 60mm, Light Weight Company Mortar Systems (LWCMS), M224 at appropriate quadrant elevations (QE) and charges.

4.5.3 Environmental tests.

4.5.3.1 Temperature and humidity. Twenty (20) complete fuzes (live lead and inert booster) shall be subjected to the Temperature and Humidity Test in accordance with Test C1 of MIL-STD-331B. After completion of the laboratory test, ten (10) fuzes shall be assembled into inert 60mm Cartridges (M720 or M722) and ballistically fired from an M224 mortar tube at Charge 4, 145 F. If any fuze fails to function on impact, it shall be classed as a defect. Two (2) or more defective fuzes shall be cause for the first article to be rejected. Any premature function, metal parts separation of the fuze, or early functioning shall be classed a critical defect and the first article shall be rejected.

4.5.3.2 Transportation handling and vibration. Twenty-four (24) complete fuzes (live lead and inert booster) shall be subjected to the Transportation Handling and Vibration Test (Packaged Fuzes) in accordance with Tests A5 and B2 of MIL-STD-331B. The complete fuzes shall be assembled to inert loaded 60mm, M720 or M722 cartridges and packaged in fiber containers (8) and outer metal boxes (3). For each temperature (160 F, 70 F, and -65 F), the following tests are to be conducted in sequence.

Secured Packaged Vibration, Procedure 5.1 of Test B2 (6 hrs)

3 Foot Drop, Procedure 5.2.2 of Test A5 (6 drops)

Unsecured Package Vibration, Procedure 5.2 of test B2 (30 mins)

Visual and radiographic inspections shall be used to verify the condition of the safety features of the fuze. If the fuzes and cartridge components (projectile bodies, ignition cartridges, propellant charges and fins) are in usable condition, ten (10) fuzed assembles shall be fired from a 60mm, LWCMS, M224 weapon at Charge 4, 800 + 50 mils at -50 F. Two (2) or more fuze duds shall be cause for the rejection of the first article. Any premature function, metal parts separation of the fuze, or early functioning shall be classed a critical defect and the first article shall be rejected.

4.5.4 Safety and arming device tests. The following S&A device tests shall be conducted without explosives.

4.5.4.1 Spring gear latch (non-destructive). The S&A device shall be placed in the S&A tester of 4.4.4.1.1. With the zig zag

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

body in the forward position, apply an air pressure of .206 +.000/ -.006 psig for a minimum of 3 seconds. The S&A assembly shall meet the requirement of 3.6.1.1.

4.5.4.2 Acceleration sensor non-function. The S&A device shall be mounted on the centrifuge equipment in 4.4.4.1.2 and spun to achieve an acceleration of 215g minimum axially on the zig-zag body toward the booster end of the S&A. The S&A assembly shall meet the requirement of 3.6.1.2.

4.5.4.3 Acceleration sensor function. The S&A device shall be mounted on the centrifuge equipment in 4.4.4.1.2 and spun to achieve an acceleration of 395g maximum axially on the zig-zag body toward the booster end of the S&A. The S&A assembly shall meet the requirement of 3.6.1.3.

4.5.4.4 Arming time. The S&A device shall be placed in the S&A tester in 4.4.4.1.1. A dummy conductive detonator may be used for this test. With the zig-zag body in the locked down position, and with the turbine restrained from turning, apply an air pressure of .206 psig +.000/-.006 psig. Release the turbine and start a timer. The timer shall be stopped when the rotor reaches the fully armed position. This measured time shall meet the requirement of 3.6.1.4. For all arming time tests, both the calibrated M745 turbine alternator and the input air shall be at a temperature of 70 ± 10 F.

4.5.4.5 Spring gear latch (destructive). The S&A device shall be placed in the S&A tester in 4.4.4.1.1. With the zig-zag body in the forward position, apply an air pressure of 0.7 +/- .05 psig for a minimum of 3.0 seconds. The S&A assembly shall meet the requirement of 3.6.1.5.

5. PACKAGING

5.1 PACKING

5.1.1 Level A. Not applicable.

5.1.2 Level B. Not applicable.

5.1.3 Level C. The interplant shipment packing for fuzes shall be in accordance with drawing 9347415.

5.2 Marking. Marking of the fiberboard box shall be in accordance with drawing 9347415.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The M745 Fuze covered by this specification are intended to be use on Cartridges, 60mm, WP, M722; 120mm, WP, M929 and 120mm, HE, M933.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of the individual documents referenced (see 2.1.1).

c. Requirements for submission of first article sample.

6.3 Submission of contractor inspection equipment design for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: AMSTA-AR-QAA-C, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirement List, DD Form 1423 in the contract.

6.4 Submission of alternative quality conformance provisions. All contractor proposed alternative quality conformance provisions will be submitted to the Government for evaluation/approved as directed by the contracting activity.

6.5 Subject term (key word) listing.
Acceleration sensor, function and non-function tests
Arming time
Temperature and humidity
Transportation and handling test
Turbine alternator
Zig-zag

6.6 Special defects notification. An incident report must be forwarded to Commander, ARDEC, Attn: AMSTA-AR-QAA-C, Picatinny Arsenal, NJ 07806-5000, within twenty-four (24) hours of each occurrence of finding a special defect.

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1390-0810)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-F-70807A(AR)	941130

3. DOCUMENT TITLE: FUZE, PD, M745 (LESS BOOSTER AND LEAD)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: AMSTA-AR-EDE-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.