MIL-B-51254(MU)
AMENDMENT 2
2 February 1987
SUPERSEDING
AMENDMENT 1
21 March 1967

MILITARY SPECIFICATION

BREATHING APPARATUS, OXYGEN GENERATING, M20

This amendment forms a part of MIL-B-51254(MU), dated 12 December 1966, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1:

Under "SPECIFICATIONS" "FEDERAL" delete the following:

"NN-P-00515 - Plywood, Container Grade.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stay Material)."

Under "SPECIFICATIONS" "FEDERAL" add the following:

"L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin.
PPP-B-26 - Bag, Plastic, Polyethylene.
PPP-T-60 - Tape: Pressure-Sensitive, Adhesive, Waterproof, For Packaging.
PPP-F-320 - Fiberboard; Corrugated and Solid Sheet Stock (Container Grade); and Cut Shapes.
QQ-S-781 - Strapping, Steel, Flat and Seals."

Under "SPECIFICATIONS" "MILITARY" delete the following:

"MIL-P-116 - Preservation, Methods of."

PAGE 4

3.1.7: Delete "two type I canisters and one type II canisters (see 3.1.9)." and substitute "three type A-3 canisters (see 3.1.9)."

AMSC N/A FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.

3.1.9: Delete paragraph and substitute "Each apparatus shall be provided with three type A-3 canisters conforming to MIL-C-17671."

3.1.12: Delete paragraph and substitute with the following:

"3.1.12 Hood. One hood supplied as an accessory shall be Mine Safety Appliance Co. part no. D304157."

PAGE 8

4.3.3.3(b): Change category "103" to read: "Carrying case not inclosed in polyethylene wrap or bag as specified (5.1)."

PAGES 9 AND 10

Section 5: Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Packaging, level A. No preservative compounds or oils shall be applied to any portion of the breathing apparatus. The breathing apparatus, consisting of a facepiece and hose assembly, back-carry harness assembly, breathing bag assembly, anti-fogging kit, hood, canisters, spanner wrench and technical publications shall be placed inside the carrying case (see 3.1.7) in such a manner to prevent damage to the rubber components of the breathing apparatus. Internal cushioning, blocking, or bracing shall be used as necessary to prevent movement of the breathing apparatus or components within the carrying case. The cover shall be secured with the fasteners provided. The case shall be either inclosed in a wrap of polyethylene conforming to L-P-378, type II (folded ends taped with tape conforming to PPP-T-60, type IV), or in a polyethylene bag conforming to PPP-B-26, type II, style 1 or 2, 0.004 inch thick material. The bag, if used, shall be closed as follows: Style 1 bags shall be either heat sealed in accordance with the bag manufacturers recommendation, or the open end taped with tape conforming to PPP-T-60, type IV. Style 2 bags shall be closed with wire tie provided.

5.2 Packing. Level shall be specified (see 6.2).

5.2.1 Level A. The breathing apparatus, packaged as specified in 5.1, shall be packed in an overseas type, style optional, class A, cleated plywood box conforming to PPP-B-601. The box shall be minimum cube to contain the packaged breathing apparatus. Filler pads conforming to PPP-F-320, W6C, shall be used as necessary to ensure a tight pack. The box shall be closed and strapped in accordance with the appendix to PPP-B-601. Strapping and seals shall conform to QQ-S-781 (Strapping - type I (Regular Duty), Finish B, Grade 2 and Seals - type D, styles I or IV, finish B, Grade 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. The breathing apparatus, packaged as specified in 5.1, shall be packed in a weather resistant fiberboard box conforming to PPP-B-636, variety SW, grade V3C, type 1 load. The box shall be minimum cube to contain the packaged breathing apparatus. Filler pads fabricated of the same material as the box, or filler pads specified in 5.2.1, shall be used as necessary to ensure a tight pack. The box shall be closed in accordance with the Method V closure requirements and reinforced using nonmetallic strapping as tape banding in accordance with the reinforcing requirements in the appendix to PPP-B-636.

5.2.3 Level C. The breathing apparatus, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first receiving activity for immediate use or further processing. Shipping containers shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages (5.1) and shipping containers (5.2) shall be marked in accordance with MIL-STD-129.

5.4 Repair parts. When the components of this item are procured for storage and issue as a repair part, preservation, packaging, packing and marking shall be in accordance with the repair part packaging data sheet which is identified by the National Stock Number for the item."

PAGE 11

6.4: Delete paragraph in its entirety.

6.5: Delete paragraph in its entirety.

Preparing activity:

Army - EA

Project No. 4240-A892

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.