MILITARY SPECIFICATION

BALLISTICS COMPUTER SUBASSEMBLY: 8635276 (INPUT UNIT)

This amendment forms a part of Military Specification MIL-B-60122(MU), dated 28 May 1964.

Paragraph 2.1, Specifications: Delete "MIL-I-45208, Inspection System Requirements".

Paragraph 2.1, Drawings: Add "F8565556 - Pressure Tester - Two Station".

* Paragraph 3.4.1: Delete last sentence.

Paragraph 3.4.3: Delete and substitute:

"3.4.3 Sealing.- The input unit shall exhibit an internal pressure drop of less than 0.2 psig when pressurized to 5 ± 0.1 psig for a minimum of 2 hours".

Add the following paragraph:

"3.4.4 Flushing.- The input unit shall be flushed until the interior atmosphere contains nitrogen with a dewpoint at least as low as -25°F. The unit shall be sealed with an internal pressure of nitrogen of 3.0 ± .5 psig"

Add the following paragraph:

"3.4.5 Storage temperature.- The unit shall show no evidence of physical failure and shall meet all requirements of this specification at standard ambient temperature of 60° to 90°F. After having been exposed to and thermally stabilized at ambient temperature of -80°F and +160°F.

Paragraph 3.5.2: Delete "plus twice the rated voltage".

Paragraph 4.1.1: Delete and substitute:

"4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109"

* Add new paragraphs 4.1.2, 4.1.2.1, and 4.1.2.2

"4.1.2 First Article (Initial Production) Approval.- The requirement for first article approval and the responsibility (Government or contractor)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) input units manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government Testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor Testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

* Paragraph 4.2.2, Table II: Add the following characteristics:

"108.	Sealing	3.4.3	4.5.1.3
109.	Flushing	3.4.4	4.5.1.4
110.	Dielectric strength	3.5.2	4.5.3
111.	Insulation resistance	3.5.3	4.5.4"

* Paragraph 4.3: Delete "Control tests" and substitute "Special sampling".

* Paragraph 4.3.1, last sentence: Delete "control"; in tabulation heading delete "Control test" and substitute "Characteristic."

* Paragraph 4.3.2: Delete second sentence and substitute; "Each sample shall meet the following requirements and tests and shall then meet the requirements and tests in Table II"; Delete tabulation and substitute

"Characteristic	Requirement	Test Procedure
304. Storage temperature (-80° and + 160°F)	3.4.5	4.5.1.5
305. Torque	3.4.1, 3.6.1	4.5.1.1, 4.5.5
306. Range data	3.4.1, 3.6.2	4.5.1.1, 4.5.6
307. Output voltage- R201	3.4.1, 3.6.3	4.5.1.1, 4.5.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

308.	Output voltage R-202	3.4.1, 3.6.4	4.5.1.1, 4.5.8
309.	Illumination	3.4.1, 3.7	4.5.1.1, 4.5.9

Note: The tests for Characteristic 305 through 309 inclusive shall be conducted at -40° and + 150°F."

* Paragraph 4.3.3: Delete and substitute

"4.3.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirement, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and resubmitted items have been approved (see 4.2.3)."

Paragraph 4.4, first sentence: Delete "Measuring and Test Equipment requirement of MIL-I-45208 and all".

Paragraph 4.4.2, Item Number 2 description: Delete "1 megohm ± 10%" and substitute "1 megohm minimum"; Item Number 3 description: Delete and substitute "0-24 volts rms, 400 cps ± 1%, 2% maximum harmonic distortion"; Item Number 4 description: Delete and substitute "18-30 volts, maximum ripple 0.1 volt peak to peak, 300 millimapere output".

* Paragraph 4.5.1.2: Delete last sentence and substitute

"The input unit shall then be subjected to the tests specified in Table II to determine conformance with the applicable requirements referenced therein."

Paragraph 4.5.1.3: Delete and substitute:

"4.5.1.3 Sealing.- The special testing equipment to test sealing of the input unit shall conform to the internal pressure test requirements of Sheet 1 of Drawing F8565556, Pressure Tester - Two Station. Secure the poppet in Valve 10516717 in a closed position. The pressure shall be applied to the input unit through the input valve in the side of the unit. Pressurize the input unit with dry nitrogen gas to the value specified in 3.4.3, in accordance with the procedure for internal pressure testing on Sheet 1 of Drawing F8565556. The dry nitrogen gas shall have a dewpoint at least as low as minus 25°F. Retain the applied pressure in the input unit for a minimum of 2 hours. Within the first hour of this 2 hour time period, the input shaft and input crank shall be rotated one-half revolution clockwise then counterclockwise a minimum of 3 times. Any evidence of leakage in the input unit, at the end of the 2 hour time period, shall not exceed the tolerance specified in 3.4.3, as measured on the pressure gauge of the testing equipment. Upon completion of this, release poppet in Valve 10516717".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

Add the following paragraph:

"4.5.1.4 Flushing.- Perform this test in sequence to the test in 4.5.1.3. The special testing equipment specified in 4.5.1.3 shall be utilized in this test. A dew point tester, with an appropriate adapter to accommodate the Valve 10516717, shall be used to test the dew point of the interior atmosphere of the input unit. The input unit shall be flushed with dry nitrogen gas. The flushing shall continue until the nitrogen gas bled from the input unit has a dew point at least as low as minus 25°F, as measured with the dew point tester. The dew point tester shall be removed from the input unit. The internal pressure of nitrogen gas in the input unit shall be brought to a measured 3 psig ± 0.5 psig. The internal pressure of the input unit shall be monitored for a period of 5 minutes ± 15 seconds. At the end of the 5 minute period there shall be no evidence of leakage in the input unit as indicated on the pressure gauge of the testing equipment. The input unit shall conform to the requirements of 3.4.4".

Add the following paragraph:

"4.5.1.5 Storage temperature.- The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.4.5. The input unit shall be exposed to each temperature extreme specified in 3.4.5 for a minimum of 5 hours. After each temperature exposure the input unit shall be stabilized in an ambient temperature between 60° and 90°F and subjected to a visual, tactile and audible examination for evidence of physical failure. The input unit shall then be subjected to the tests in 4.5.1.1 through 4.5.8.2 inclusive to determine conformance to 3.4.5. Caution shall be exercised during the temperature cycling to avoid subjecting the input unit to thermal shock."

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A088

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.