INCH–POUND

MIL–DTL–60477B(EA)
w/ AMENDMENT 4
21 November 2006
SUPERSEDING
MIL–DTL–60477B(EA)
w/Amendment 3
7 March 2005

DETAIL SPECIFICATION

PROJECTILE, 155MM, SMOKE, WP, M110A2, LOADING AND ASSEMBLING

Reactivate for new design after 6 August 2002

This specification is approved for use by the U.S. Army Edgewood Chemical Biological Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense within the distribution limitations noted at the bottom of the page.

Comments, suggestions, or questions should be addressed to: U.S. Army Edgewood Chemical Biological Center, ATTN: AMSRD–ECB–ENA–S, 5183 Blackhawk Rd, Aberdeen Proving Ground, MD 21010–5424 or emailed to SpecsTeam@apgea.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A FSC 1320

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This specification covers the loading and assembling for one type of projectile designated as Projectile, 155MM, WP, M110A2.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to insure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

DEPARTMENT OF DEFENSE STANDARDS

MIL−STD−1916 – DOD Preferred Methods for Acceptance of Product
MIL−STD−1168 – Ammunition Lot Numbering and Ammunition Data Card

(Copies of these documents are available online at http://assist.daps.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111−5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. ARMY EDGEWOOD CHEMICAL BIOLOGICAL CENTER

DRAWINGS

9217030 – Projectile, 155MM: Smoke, WP, M110A2 Loading Assembly

(Copies are available from U.S. Army Edgewood Chemical Biological Center, ATTN: AMSRD−ECB−ENA−S, 5183 Blackhawk Road, Aberdeen Proving Ground, MD 21010−5424.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

U.S. ARMY TEST AND EVALUATION COMMAND

INTERNATIONAL TEST OPERATING PROCEDURE (ITOP)

ITOP 4−2−602 − FR/GE/UK/US Rough Handling Tests

(Copies are available from Commander, U.S. Army Test and Evaluation Command, ATTN: AMSTE−TM−T, Aberdeen Proving Ground, MD 21005−5055.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Design and construction.

3.2.1 Materials. All materials cited on Drawing 19203−9217030 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.2.2 Components. All components of the projectile shall conform to the specifications and drawings listed on Drawing 19203−9217030 and subsidiary drawings.

3.3 Manufacture and assembly. The projectile shall be manufactured and assembled as specified on Drawing 9217030 and subsidiary drawings.

3.4 Ballistic functioning. The projectile shall launch and fly to the target area with no evidence of leakage from the projectile and the projectile hardware shall remain intact until the fuze functions. Upon fuze function the burster shall function high order and the projectile shall produce a smoke signature visible across 4,000 meters of level terrain.

3.5 Safety. There shall be no premature burst or indication of metal parts separation in the gun bore or in flight, when fired with projectiles at +63˚C (+145˚F) and propellant adjusted to obtain a chamber pressure of 282.69 + 20.68 Megapascals (mPa) (41,000 + 3,000 pounds) per square inch (psi).

3.6 Physical integrity and functioning after sequential rough handling. The disc and cap assembly shall remain intact and secure, the projectile shall not leak and shall meet the functioning requirement of this specification after being subjected to sequential rough handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

3.7 Rotating band. The rotating band shall be free from the following damage or contamination:

(a) There shall be no damage that results in raised brass.
(b) There shall be no paint or foreign matter on the outer diameters.
(c) Nicks, gouges, scratches and other depressions on the lands not exceeding .063 cm (.025 inches) in depth are acceptable.
(d) Nicks, gouges, scratches and other depressions on the lands with depths greater than .063 cm (0.025 inches) and less than or equal to .127 cm (0.050 inches) are acceptable unless the damage extends longitudinally across more than half of the land width.
(e) "Washboard" or striated area if it extends longitudinally across more than half of the land width and the depth exceeds .063 cm (0.025 inches) at any point is a reject.
(f) Nicks, gouges, scratches and other depressions on the lands with depths greater than .127 cm (0.050 inches) are rejects.

3.8 Lot numbering and Ammunition Data Cards. Lot numbering and Ammunition data cards (see 6.2) shall be prepared in accordance with MIL−STD−1168.

3.9 Workmanship. All parts and assemblies shall be free from contamination (dirt, grease, rust, or foreign matter) and damage (cracks, burrs, chips). The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Care shall be exercised at all times to prevent damage (nicks or burrs) to the projectile rotating band. All required marking and painting shall not be marred or obliterated.

3.10 Metal defects. The disc and cap shall be free from cracks, splits, cold shuts, inclusions, porosity, laps, seams or other similar defects.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.2)
(b) Conformance inspection (see 4.3)

4.2 First article inspection.

4.2.1 Lot. The first article lot shall consist of 260 caps, discs, disc and cap assemblies and loaded projectiles. The first article lot shall be manufactured using the same methods, materials, equipment, processes, inspections, in−process tests and facilities as will be used during regular production and shall be submitted for inspection and approval in accordance with the terms of the contract (see 6.2).

4.2.2 Inspections to be performed. The first article sample items shall be examined and tested 100% for all drawing and specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.2.3 Acceptance criteria. If any first article sample item fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure to comply with any of the requirements. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

4.2.4 Sampling.

4.2.4.1 Sampling for examination and testing. Sampling for examination and testing shall be in accordance with Table I.

TABLE I.

EXAMINATION	**DRAWING**	**SAMPLE SIZE**
Projectile, 155MM; Smoke, WP, M11A2 Loading and Assembling	9217030	CRITICAL characteristics – 100% All other characteristics – 80*
Cap	10551965	80
Disc	11738708	80
Disc and cap assembly	11738709	80
BALLISTIC FUNCTIONING	**TEST**	**SAMPLE SIZE**
Safety	4.4.2	10
Rough handling	4.4.3	60
Ballistic functioning @ ambient temperature	4.4.1.3	110
Hot (ballistic @ +63° C)	4.4.1.2	40*
Cold (ballistic @ −54° C)	4.4.1.1	40*
Total ballistic rounds fired		260
*NOTE: The Examination sample of projectiles shall be used for the Hot and Cold ballistic testing.		

4.3 Conformance inspection.

4.3.1 Lotting. Inspection lots shall comply with the provisions of MIL−STD−1916 and MIL−STD−1168. In addition, each lot shall contain projectile filling assemblies of one interfix, from one manufacturer, and of one weight zone; and bursters and disc and cap assemblies of one interfix number and from one manufacturer.

4.3.2 Examination.

4.3.2.1 Sampling. Sampling shall be conducted in accordance with the classification of characteristics in 4.3.5. Samples shall be selected at random.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.3.2.2 Inspection procedure. Sample items shall be examined in accordance with the classification of characteristics in 4.3.5. Failure of any sample item to conform to any characteristic in the classification of characteristics based on the sampling and acceptance criteria specified therein shall be cause for rejection of the lot represented.

4.3.2.3 Critical characteristics. Unless otherwise specified in the classification of characteristics, the sampling and acceptance criteria for critical characteristics shall be in accordance with the **Critical characteristics** paragraph of MIL−STD−1916. If any critical defects are encountered the **Special reservations for critical nonconformance** paragraph of MIL−STD−1916 shall apply.

4.3.2.4 Classification of characteristics. Conformance examinations shall be as specified in the following classification of characteristics paragraphs. When verification levels (VLs) are specified for selection of sample sizes and acceptance criteria, the attributes sampling plan of MIL−STD−1916 shall apply unless otherwise specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(a)	Projectile, 155MM: Smoke, WP, M110A2 Filling Assembly, as received from WP fill plant	SHEET 1 OF 1	9217031

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical				
1	No WP leakage or contamination	4.3.2.3	3.2	VI
Major				
101	Depth to burster casing correct	VL IV	3.2	AIE
102	No foreign matter in fuze and burster cavity	VL IV	3.9	VI
Minor				
201	Workmanship	VL II	3.9	VI

NOTES:

AIE – Acceptance inspection equipment
VI – Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(b)	Projectile burster M54A1, assembly – prior to assembly to projectile	SHEET 1 OF 1	19203–10551965

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Burster plug and closure present	VL IV	3.2	VI
Minor				
201	Workmanship correct	VL II	3.9	VI

NOTES:

VI – Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(c)	Projectile, prior to assembly of cap and disc assembly	SHEET 1 OF 1	9217030

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical				
1	Projectile burster not inverted	4.3.2.3	3.2	VI
Major				
101	Projectile burster evident	VL IV	3.2	VI
Minor				
201	Locking compound applied to cap threads	VL II	3.2	VI
202	Burster closure evident	VL II	3.2	VI
203	Workmanship correct	VL II	3.9	VI

NOTES:

AIE – Acceptance inspection equipment

VI – Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(d)	Projectile prior to assembly of lifting plug	SHEET 1 OF 1	9217030

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Depth of fuze well	VL IV	3.2	AIE
102	Disc and cap assembly fully seated on burster tube	VL IV	3.2	Manual
Minor				
201	Compound applied to threads	VL III	3.2	VI
202	Disc evident and correctly assembled	VL III	3.2	VI
203	Workmanship	VL III	3.9	VI

NOTES:

AIE – Acceptance inspection equipment

VI – Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(e)	Projectile, 155MM: Smoke, WP, M110A2 Loading Assembly	SHEET 1 OF 1	9217030

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical				
1	Projectile zone weight correct	4.3.2.3	3.2	AIE
2	Stencilling and punching correct	4.3.2.3	3.2	VI
Major				
101	Disassembly torque of lifting plug assembly	VL IV	3.2	AIE
102	Diameter of bourrelet not greater than maximum (applicable after retouching of paint)	VL IV	3.2	AIE
103	Lifting plug and packing evident and undamaged	VL IV	3.2	AIE
104	Weight zone punch marks adequate	VL IV	3.2	VI/AIE Tactile
105	Rotating band correct	VL IV	3.7	VI/AIE*
Minor				
201	Grommet evident, undamaged and correctly assembled	VL II	3.2	VI
202	Protective coating undamaged (total damaged area not greater than 1/4 square inch)	VL II	3.2	VI
203	Marking evident and correct (except zone markings)	VL II	3.2	VI
204	Ammunition data card complete and correct	1; Acc 0, Rej 1	3.8	VI
205	Workmanship correct	VL II	3.9	VI

NOTES:

*Inspect immediately prior to final installation of the grommet. Pin/wire gages shall be used for depth

VI – Visual inspection

AIE – Acceptance inspection equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(f)	Cap	SHEET 1 OF 1	10551965

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical				
1	No metal defects	100%	3.10	VI
Major				
101	Thread and positional tolerance correct	VL IV	3.2	AIE
102	Small I.D. and positional tolerance correct	VL IV	3.2	AIE
103	Large I.D. correct	VL IV	3.2	AIE
104	Width and depth of slots correct	VL IV	3.2	AIE
105	Total length correct	VL IV	3.2	AIE
106	Shoulder thickness correct	VL IV	3.2	AIE
Minor				
201	Radii or chamfer correct	VL II	3.2	VI
202	Protective coating correct	VL II	3.2	VI
203	Workmanship correct	VL II	3.9	VI

NOTES:

VI – Visual inspection
AIE – Acceptance inspection equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.4(g)	Disc	SHEET 1 OF 1	11738708

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical				
1	No metal defects	100%	3.10	VI
Major				
101	Diameter correct	VL IV	3.2	AIE
Minor	None defined			

NOTES:

VI – Visual inspection
AIE – Acceptance inspection equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.3.2.5 (h)	Cap and disc assembly	SHEET 1 OF 1	11738709

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Sealing compound evident and correct	VL IV	3.2	VI
102	Disc assembled correctly	VL IV	3.2	VI
Minor	None defined			

NOTES:

VI – Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.3.3 Testing.

4.3.3.1 Safety (Critical) and Ballistic functioning – initial production. Beginning with the first lot produced and continuing until three consecutive lots have been accepted for compliance to specification requirements, the Government will randomly select 32 projectiles from each lot to conduct these tests. Projectiles shall be tested as follows:

(a) Sixteen projectiles for ballistic functioning using the M119A2 propelling charge (eight at −54˚C [−65˚F] and eight at +63˚C [+145˚F])
(b) Fifteen projectiles for safety
(c) One projectile available for replacement or retest

4.3.3.1.1 Projectile replacement or retest. One projectile is available for replacement or retest if a fuze dud occurs during ballistic functioning or a safety test round fails to meet the minimum pressure. Fuze duds shall not be considered as cause for rejection of a projectile lot. If a fuze dud occurs, the test director may fire a replacement projectile. If the available projectile is not required for replacement or retest, it shall be processed in accordance with the standing operating procedure of the test site.

4.3.3.1.2 Retest. If, for any reason, the test director considers that test conditions have affected all or part of the test results, the test director shall declare the affected results invalid and perform new tests on additional projectiles, as required.

4.3.3.1.3 Acceptance criteria. The lot represented by the sample shall be rejected if any projectile fails to comply with the safety requirement or any of the following events occur during ballistic functioning testing: premature burst; separation of metal parts prior to initiation of the fuze or upon impacting the ground; or projectile fails to function in accordance with the ballistic functioning requirements of this specification.

4.3.3.2 Safety (Critical) and Ballistic functioning – regular production. After three consecutive acceptance lots have met the criteria of 4.3.3.1.3, the Government shall randomly select 16 projectiles from each lot for these tests. Projectiles shall be tested as follows:

(a) Eight projectiles for ballistic functioning using the M119A2 propelling charge (four at −54˚C [−65˚F] and four at +63˚C [+145˚F])
(b) Seven projectiles for safety
(c) One projectile available for replacement or retest

4.3.3.2.1 Projectile replacement or retest. One projectile is available for replacement or retest if a fuze dud occurs during ballistic functioning or a safety test round fails to meet the minimum pressure. Fuze duds shall not be considered as cause for rejection of a projectile lot. If a fuze dud occurs, the test director may fire a replacement projectile. If the available projectile is not

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

required for replacement or retest, it shall be processed in accordance with the standing operating procedure of the test site.

4.3.3.2.2 Retest. If, for any reason, the test director considers that test conditions have affected all or part of the test results, the test director shall declare the affected results invalid and perform new tests on additional projectiles, as required.

4.3.3.2.3 Acceptance criteria. The lot represented by the sample shall be rejected if any projectile fails to comply with the safety requirement or any of the following events occur during ballistic functioning testing: premature burst; separation of metal parts prior to initiation of the fuze or upon impacting the ground; or projectile fails to function in accordance with the ballistic functioning requirements of this specification. If a lot fails ballistic testing, the lot shall revert to 4.3.3.1.

4.3.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is specified in the Inspection Method column in the classification of characteristics paragraphs. The contractor shall design inspection equipment, as required (see 6.2), and these designs require Government approval prior to use.

4.4 Test methods and procedures. PRECAUTION: This specification covers inspection of chemical, toxic or explosive materials which are potentially hazardous to personnel. All safety rules, regulations, and procedures must be followed in the handling and processing of these materials. Unless otherwise specified, the following tests shall be conducted at a Government test site:

4.4.1 Ballistic functioning. These tests shall be conducted at a Government test site, at the specified zone, using weapons, equipment methods, and procedures in accordance with appropriate acceptance test procedures. The round shall be fitted with a fuze approved for the M110A2. Tubes used for this test shall not have less than 25 percent remaining tube life based on current gun tube condemnation criteria. If approved for air burst, the cannon Quadrant Elevation (QE) and fuze shall be adjusted to provide an air burst height below 200 meters.

4.4.1.1 Conditioning at −54°C. The sample of projectiles and the M119A2 propelling charges shall be temperature conditioned at −54° + 2.8°C (−65° + 5°F) for not less than 24 hours. The projectile, maintained within 2.8°C (5°F) of the conditioning temperature, shall be fired using a suitable mounted M185 or M199 series cannon. The fuzes shall be maintained at ambient temperature. Observation shall be made for failure to comply with the ballistic functioning requirements specified herein.

4.4.1.2 Conditioning at +63°C. The sample of projectiles and the M119A2 propelling charges shall be temperature conditioned at +63° + 2.8°C (+145° + 5°F) for not less than 24 hours. The projectile, maintained within 2.8°C (5°F) of the conditioning temperature, shall be fired using a suitable mounted M185 or M199 series cannon. The fuzes shall be maintained at

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

ambient temperature. Observation shall be made for failure to comply with the ballistic functioning requirements specified herein.

4.4.1.3 Conditioning at ambient. The sample of projectiles, fuzes and the M119A2 propelling charges shall be temperature conditioned at +21˚ + 2.8˚C (+70˚ + 5˚F) for not less than 24 hours. The projectile, maintained within 2.8˚C (5˚F) of the conditioning temperature, shall be fired using a suitable mounted M185 or M199 series cannon. Observation shall be made for failure to comply with the ballistic functioning requirements specified herein.

4.4.1.4 Ballistic test records. Pressure−time traces, differential pressures, and muzzle velocities shall be obtained, for information only, by means of a spindle tap in the breech of the cannon and a piezo gage at the projectile base location for each projectile fired. Adequate photographic and instrumental coverage shall be provided to assure compliance with requirements. Fuze settings, range, and deflections shall be recorded for informational purposes only. In the event of any abnormal condition, as observed by personnel or instrumentation, an attempt shall be made to recover and examine the metal parts for informational purposes only. An observer shall be stationed 4,000 ± 200 meters from the edge of the impact area to record burster functioning and the presence of a smoke signature.

4.4.2 Safety (Critical). The sample projectiles shall be temperature conditioned at 63˚ + 2.8˚C (145˚ + 5˚F) for not less than 24 hours. The fuzes shall be maintained at ambient temperature. The projectiles shall be maintained within 2.8˚C (5˚F) of the conditioning temperature shall be fitted with fuzes approved for the M110A2 set for airburst, and fired with M119A2 propelling charges adjusted to obtain the required pressure and fired in an M185 or M199 series cannon with a tube life of not less than 25 percent remaining. Camera coverage shall be provided to observe the projectiles in flight in order to record any malfunctions. Applicable ballistic records specified in 4.4.1.4 shall be required for information only.

4.4.3 Physical integrity and functioning after sequential rough handling. The sample projectiles shall be tested in accordance with ITOP 4−2−602, figure 1, maintained within 2.8˚ C (5˚F) of the test temperatures, examined for security and integrity of the disc and cap assembly and leakage and shall be ballistically functioned as specified in 4.4.1.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in−house personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD−ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The projectile, 155MM, WP, M110A2, Loading Assembly is intended for use in 155MM cannons.

6.2 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) First article:
(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract when testing is performed by the Government.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.
(4) When a new or partial first article is required (see 6.3).
(c) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced.
(d) Requirements for contractor acceptance inspection equipment (AIE) design approval (see 6.4).
(e) Data Item Description, Army Electronic Product Support (AEPS) access information, Governmental Agency Responsible for Acceptance (GARA) information, and the distribution for the MIL−STD−1168 ammunition Data Cards (see 6.5).
(f) Packaging requirements (see drawing 9217030).
(g) Requirements for Ammunition lot numbering (see 3.8).

6.3 Occurrences requiring a new first article inspection. Any change of vendors, methods, materials, equipment, facilities, or lot interfix or if there is a 6 month break in production requires a new full or partial first article inspection.

6.4 Submission of inspection procedures and equipment (AIE) designs for approval. Submit inspection procedures and equipment designs, as required, to Director, U.S. Army ECBC, ATTN: AMSRD−ECB−END−S(RI), Rock Island, IL 61229−7390. This address will be specified on the Contractor Data Requirements List, DD Form 1423 in the contract.

6.5 Ammunition Data Card distribution. In addition to the automated distribution; one hard copy with each shipment to each destination, one copy to Director, U.S. Army ECBC, ATTN: AMSRD−ECB−END−S, Aberdeen Proving Ground, MD 21010−5424.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

6.6 Acceptance Inspection Equipment (AIE). Any measuring or test device that is traceable to national or international standards used to assure conformance of material to the contract requirements.

6.7 Subject term (key word) listing.

Ballistic
Bourrelet
Burster
Fuze
Plug, lifting

6.8 Changes from previous issues. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsover for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate requirements of this document based on the entire content irrespective of the marginal notations.

6.9 Standard operation procedures. The Standard Operating Procedures (SOP) or any equivalent document having to do with the management and control of the operating process, shall have a section dedicated to policies and procedures to prevent, control, and dispose of substances harmful to the environment, all in accordance with Federal and State environmental laws and regulations.

Custodian:

Army – EA

Review activity

Army – AR

Preparing activity:

Army – EA

(Project 1320–2006–002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the Assist Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.