INCH-POUND
MIL-DTL-0060982C (AR)
05 April 2004
USED IN LIEU OF
MIL-C-63063 (AR)
29 March 1976
MIL-C-63062 (AR)
29 March 1976
MIL-C-60982B (AR)
17 November 1980

DETAIL SPECIFICATION

CASE CARTRIDGE, 40MM - M169

This specification is approved for interim use by the U.S. Army Armament Research, Development and Engineering Center (ARDEC). Other activities in the Department of Defense may use this interim revision or may continue using MIL-C-63063 (AR), MIL-C-63062 (AR), and MIL-C-60982B (AR).

1. SCOPE

1.1 Scope. This specification contains one type of case cartridge designated as Case Cartridge, 40MM: M169.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 or 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements of documents cited in sections 3 or 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to: Commander, US Army ARDEC, ATTN: AMSRD-AAR-QES-E, Picatinny, New Jersey 07806-5000, or e-mailed to ardec-stdzn@pica.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil

AMSC N/A FSC 1310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-A-8625 - Anodic Coatings for Aluminum and Aluminum Alloys
MIL-A-70625 - Automated Acceptance Inspection Equipment Design, Testing and Approval of

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1168 - Ammunition lot numbering and Ammunition data card
MIL-STD-1916 - DoD Preferred Methods for Acceptance of Product

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract (see 6.2).

U.S. ARMY (ARDEC) DRAWINGS (see 6.4)

PRODUCT AND PACKING DRAWINGS

8886332 - Plug, Base
8886329 - Case, cartridge, 40MM: M169
9206911 - Cup, Closing

INSPECTION EQUIPMENT DRAWINGS

9202576 - Tensile strength
9202967 - Coating thickness measuring instrument
9202532 - Gage, Automatic
8841561 - Gage, Concentricity
8827872 - Snap gage

(Copies of these drawings may be requested online at drawing-request@pica.army.mil, or from U.S. Army ARDEC, ATTN: AMSRD-AAR-AIS-TD, Picatinny NJ 07806-5000.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those cited in the solicitation or contract (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS INTERNATIONAL (ASTM)

ASTM B117 - Standard Method of Salt Spray (Fog) Testing
ASTM E18 - Standard Methods of Test for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

ASTM E8 - Tension Testing of Metallic Materials, Methods of

(Copies of this document are available online at www.astm.org or from the ASTM International, 100 Barr Harbor Drive, Conshohocken, PA 19428-2959)

2.4 Order of precedence. In the event of a conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First Article. When specified in solicitation or the contract order (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.

3.2 Materials. Materials, parts and assemblies shall comply with requirements specified on the applicable drawings and referenced specifications.

3.3 Hardness. The hardness of the area near the mouth shall be 62 + 12 on the Rockwell 30T scale. The hardness of the base of the cartridge case shall be 64 + 10 on the Rockwell 30T scale.

3.4 Coating thickness. The thickness of the anodic coating shall be a minimum of 3 mil (.0003 inches).

3.5 Tensile properties. Each specimen must exhibit a minimum tensile strength of 50,000 psi and a yield strength of 45,000 psi to 55,000 psi.

3.6 Ammunition lot numbering. Ammunition lot numbers shall be assigned in accordance with MIL-STD-1168.

3.7 Salt Fog. The salt solution for the salt fog test shall be five (5) percent.

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.8.1 Ultrasonic inspection of barstock. The aluminum bar shall be free of internal defects such as pipe inclusions and laminations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirement/Inspection Cross Reference Matrix

Method of inspection
N/A – Not Applicable (N/A)
1 – Analysis
2 – Demonstration
3 – Examination
4 – Test

Classes of inspection
A – First article
B – Conformance

SECTION 3 REQUIREMENT	INSPECTION METHODS					INSPECTION CLASS		SECTION 4 INSPECTION METHOD
	N/A	1	2	3	4	A	B	
3.1			X	X	X	X		4.3
3.2			X	X	X	X	X	4.4, 4.5.4
3.3					X	X	X	4.5.2
3.4				X	X	X	X	4.5.6
3.5					X	X	X	4.5.5
3.6				X		X	X	4.5.1
3.7				X	X	X	X	4.5.3
3.8				X		X	X	4.5.8/4.5.8.1

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (see 4.3)
b. Conformance Inspection (see 4.4)

4.2 Inspection conditions. Unless otherwise specified, all inspection shall be performed in accordance with the test conditions specified in section 4.5.

4.3 First article. When specified in solicitation or the contract, a sample of the M169 cartridge case and subcomponents shall be subjected to first article inspection in accordance with Table II and 4.3.1.

4.3.1 First article quantity. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Cartridge Case	8886329	25
Base Plug	8886332	50
Closing Cup	9206911	50

4.3.2 Inspection to be performed. The first article inspection shall be 100% examination of all drawing characteristics (listed and unlisted) including poor workmanship requirements for the parts and assemblies listed in 4.3.1 and the tests specified in Table II herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.3 First article rejection. If any item of the sample fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon failure of an assembly, component or test specimen to comply with any of the requirements.

TABLE II. First Article Inspection

EXAMINATION OR TEST	NO. OF SAMPLE UNITS	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Cartridge Case (Dwg. 8886329)			
Hardness	25	3.2	4.5.2
Salt fog	5	3.7	4.5.3
Tensile properties	6	3.5	4.5.5
Diameter of vent holes	25	3.2	Gage
Base Plug (Dwg. 8886332)			
Salt fog	10	3.7	4.5.3
Notes:			

4.4 Conformance inspection.

4.4.1 Inspection lot formation. Lot formation shall be in accordance with MIL-STD-1916. For the components identified below, each inspection lot of cartridges shall be produced with components complying with the following constraints:

a. Metal parts or components from one interfix number, from one manufacturer

4.4.2 Classification of characteristics.

a. Sampling requirements. Inspection sampling requirements for Critical, Major, and Minor characteristics are defined in MIL-STD-1916. Unless specified otherwise, Verification Level IV shall be used for all characteristics defined as Majors and Verification Level II for all Minor characteristics; Critical characteristics shall be addressed in accordance with MIL-STD-1916.

b. Conformance inspection. Conformance inspection shall be performed in accordance with paragraph 4.4.2.1 through 4.4.2.3. For all conformance inspections the same sample specimen may be used for all non-destructive examinations or tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

Conformance Inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.1	Case Cartridge (Note 3)	SHEET 1 OF 2	8886329
			NEXT HIGHER ASSEMBLY 8886327

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
CRITICAL				
1	Three (3) or more vent holes blocked or missing	100%	3.2	AAIE/4.5.7
MAJOR				
101	One (1) or two (2) vent holes blocked or missing	100%	3.2	AAIE/4.5.7
102	Diameter of vent holes	Level IV	3.2	Gage
103	Hardness	Level IV	3.3	4.5.2
104	Burr in vent hole	Level IV	3.2	Gage
105	Salt fog	1/	3.7	4.5.3
106	Tensile properties	2/	3.5	4.5.5
107	Concentricity of flange diameter with second largest diameter	Level IV	3.2	Gage (see 6.6)
108	Concentricity of largest inside diameter open end with second largest outside diameter	Level IV	3.2	Gage
109	Concentricity of base plug cavity with second largest outside diameter	Level IV	3.2	Gage
110	Concentricity of propellant charge cavity with base plug cavity	Level IV	3.2	Gage
111	Diameter of propellant charge cavity, straight portion	Level IV	3.2	Gage
112	Diameter of base plug cavity	Level IV	3.2	Gage
113	Depth of base plug cavity	Level IV	3.2	Gage
114	Second largest outside diameter	Level IV	3.2	Gage (see 6.6)
115	Parallelism of open end to base	Level IV	3.2	Gage (see 6.6)
116	Perpendicularity of base to second largest outside diameter	Level IV	3.2	Gage
117	Diameter of flange	Level IV	3.2	Gage
118	Diameter below flange	Level IV	3.2	Gage
119	Total length	Level IV	3.2	Gage
120	Largest inside diameter, open end	Level IV	3.2	Gage (see 6.7)
121	Location of large datum diameter, propellant cavity	Level IV	3.2	Gage
122	Location of small datum diameter, propellant cavity	Level IV	3.2	Gage
123	Thickness through node	Level IV	3.2	Gage

NOTES:
1/ Sampling and rejection shall be in accordance with MIL-A-8625.
2/ Number of samples will be 6 with accept on zero, reject on one.
3/ See 6.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

Conformance Inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER 8886329
4.4.2.1	Case Cartridge (Cont.)		NEXT HIGHER ASSEMBLY 8886327

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
124	Thickness of flange	Level IV	3.2	Gage/8827872
125	Depth of sealing tip	Level IV	3.2	Gage
126	Location of large datum diameter on node	Level IV	3.2	Gage
127	Location of vent holes	Level IV	3.2	Gage
128	Metal defective (see 6.8)	Level IV	3.3	Visual
129	Process control inspection of bath temperatures	5/	3.2	4.5.4
130	Ultrasonic Inspection of Bar Stock	100% 4/	3.8.1	4.5.8.1
131	Thickness of anodic coating	Level IV	3.4	4.5.6/9202967
MINOR				
201	Protective coating with bare spot, except anodic rack marks	Level II	3.2	Visual
202	Color incorrect	Level II	3.8	Visual
203	Length of chamfer	Level II	3.2	Gage
204	Evidence of poor workmanship	Level II	3.8	Visual/4.5.8

NOTES:
4/ This shall be performed at the bar stock level.
5/ Continuous monitoring inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

Conformance Inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Base Plug			8886332
				NEXT HIGHER ASSEMBLY 8886327
CATEGORY	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**PARAGRAPH REFERENCE / INSPECTION METHOD**
CRITICAL				
1	Depth of primer cavity	100%	3.2	Gage
MAJOR				
101	Salt Fog	1/	3.7	4.5.3
102	Largest outside diameter	Level IV	3.2	Gage
103	Concentricity of smallest outside diameter with largest outside diameter	Level IV	3.2	Gage
104	Concentricity of primer cavity diameter with largest outside diameter	Level IV	3.2	Gage
105	Smallest outside diameter	Level IV	3.2	Gage
106	Diameter of primer cavity	Level IV	3.2	Gage
107	Location of small datum diameter	Level IV	3.2	Gage
108	Location of large datum diameter	Level IV	3.2	Gage
109	Diameter of flash hole	Level IV	3.2	Gage
110	Radius of intersection of primer cavity missing	Level IV	3.2	Visual
111	Process control inspection of bath temperature for anodic coating	2/	3.6	4.5.4
MINOR				
201	Second largest outside diameter	Level II	3.2	Gage
202	Length from primer end to far side of shoulder	Level II	3.2	Gage
203	Protective coating with bare spot except anode rack marks	Level II	3.2	Visual
204	Finish improper	Level II	3.8	Visual
205	Color incorrect	Level II	3.8	Visual
206	Evidence of poor workmanship	Level II	3.8	Visual/4.5.8

NOTES:
1/ Sampling and rejection shall be in accordance with MIL-A-8625.
2/ Continuous monitoring inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

Conformance Inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Cup, Closing		9206911
			NEXT HIGHER ASSEMBLY 8886327

CATEGORY	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
CRITICAL	None defined			
MAJOR				
101	Height	Level IV	3.2	Gage
MINOR				
201	Outside diameter	Level II	3.2	Gage
202	Evidence of poor workmanship	Level II	3.8	Visual/4.5.8

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Ammunition lot numbering. Visually verify that an ammunition lot number has been applied to each lot as described in MIL-STD-1168.

4.5.2 Hardness. The cartridge case shall be subjected to a Rockwell Hardness Test in accordance with ASTM E18. Three (3) readings shall be taken approximately 120° apart. The average of these readings shall meet the requirements of paragraph 3.3. If any individual reading at the mouth of the case is a below 60 that case shall be considered a reject. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.3 Salt fog. The cartridge case shall be subjected to the salt fog test in accordance with ASTM B117. This test shall be conducted for 72 hours. Salt solution shall be specified in 3.7. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.4 Process control inspection of bath temperature for anodic coating. Continuous monitoring inspection shall be conducted for bath temperature requirement specified in 3.2. If the bath temperature for a batch of parts does not comply with the applicable drawing requirement, the batch shall be suitably identified, classed defective and removed from the lot.

4.5.5 Tensile properties of cartridge case. The shape of the specimen for determining tensile strength shall be as specified on dwg. 9202576. The specimen shall be taken prior to trimming and anodizing from a 0.75 inch wide hoop, 0.125 to 0.25 inch in from the mouth of the cartridge case. The hoop shall be split, unrolled and cut to the required shape. The ends of reduced section shall not differ in width by more than 0.002 inches. There may be a gradual taper in width from the ends to the center but the width at either end shall not be more than 0.005 inch greater than the width at the center. The ends of the specimen shall be symmetrical with the center line of the reduced section within 0.05 inch. The test shall be conducted in accordance with ASTM E8. Requirements are in accordance with section 3.5.

4.5.6 Anodic coating thickness. The equipment used to measure the thickness shall be a permascope, type EC or equivalent and a measuring probe, type Ta or equivalent. Requirements are in accordance with section 3.4. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.7 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the Inspection Method Column in the tables starting with paragraph 4.4.2.1. Inspection equipment used for acceptance of product shall be capable of repeatable measurements, by various experienced inspection/test personnel, to an accuracy of 10% or better of the total tolerance of the characteristic being inspected. Any automated acceptance inspection equipment (AAIE) prove-out shall be performed in accordance with MIL-A-70625 (see 6.8).

4.5.8 Workmanship. Visually verify that all parts and assemblies meet requirements of paragraph 3.8.

4.5.8.1 Ultrasonic inspection of barstock. The test procedures, acceptance/rejection criteria and equipment design shall be submitted for approval in accordance with 6.10.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

performed by DOD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The components covered by this specification are intended for use with the Cartridge 40MM: M169.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Title, number (w/revision level) and date of all reference documents.
c. ASSIST Online to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see Section 2).
d. Requirements for submission of first article sample.
e. Requirement for submission of design verification sample, if applicable.
f. Requirement for submission of inspection equipment designs.
g. Applicable national stock number.
h. Packaging requirements, if other than specified in Section 5.
i. Serialization requirements, if applicable.
j. Certificate of conformance for each lot or shipment of product, if applicable.
k. Government-Furnished Material or equipment, if applicable.
l. Provisions for critical characteristics controls.
m. Critical Inspection Equipment Requirement (See 6.8)

6.3 Ammunition lot numbers. Ammunition requires ammunition data cards in accordance with MIL-STD-1168.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Definitions.

6.5.1 Metal defective. Nick, crack, dent or sharp edge which might interfere with the proper assembly or end item performance of the item.

6.5.2 Critical defect. A critical defect is a defect that judgment and experience indicate is likely to result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product; or a defect that judgment and experience indicate is likely to prevent performance of the tactical function of a major end item such as a ship, aircraft, tank, missile, or space vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.5.3 Major defect. A major defect is a defect, other than critical, that is likely to result in failure or to reduce materially the usability of the unit of product for its intended purpose.

6.5.4 Minor defect. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose or is a departure from established standards having little bearing on the effective use or operation of the unit.

6.6 Dimensional check. If the requirement cannot be met in the free state, the "'go" inside diameter plug gage may be inserted in the cartridge case while inspecting the "go" and "no go" second largest outside diameter. If the "go" inside diameter plug is utilized, the data cards shall be annotated accordingly.

6.7 Diameter check. If the requirement cannot be met in the free state, a confining fixture may be utilized while inspecting the "go" and "no go" largest inside diameter. If the confining fixture is utilized, the data cards shall be annotated accordingly.

6.8 Critical Inspection Equipment

6.8.1 System Reliability. The contractor shall provide for each defect identified as critical, a manufacturing and inspection system that assures no more than one in a million contain the defect. This shall be assured by controlling the maximum defect rate produced and the error rate of the inspection equipment such that the product of the two terms is less than one in a million.

6.8.2 Maximum defect rate produced. The maximum defect rate produced shall be defined as the largest defect rate expected for the characteristic of concern on a monthly or lot basis. The contractor shall establish the maximum defect rate, however, it may not exceed one percent without approval of the procuring contracting officer. Once established, the contractor shall monitor the defect rate to assure it does not exceed the maximum rate allotted. If the established maximum defect rate is exceeded, the production of that feature shall be terminated until the cause is determined and corrected. Additionally, all products for that period of time shall be rejected and re-inspected.

6.8.3 Maximum error rate of the inspection system. The error rate of the inspection equipment shall be defined as the expected ratio of the number of defective parts accepted to the number of defective parts inspected by the equipment. The contractor, to meet the system reliability as defined in 6.8.1, defines the maximum error rate allowed. However, it may not exceed 1/500 without approval of the procuring contracting officer. Based on the maximum error rate defined for the equipment, the contractor shall develop a demonstration test procedure to demonstrate the error rate of the equipment. The test shall be performed using defective parts or reject standards. No part or standard shall be accepted during the test. If a part or standard is accepted, the cause for failure shall be isolated and corrected and the test rerun. Unless otherwise specified in the detailed item specification, the minimum number of test samples to be run shall be equal to 0.7 divided by the error rate (e.g. If the required error rate is 1/1000, the sample size would be 0.7 divided by (1/1000) = 700.)

6.8.4 Periodic verification. Periodic verification of the system error rate shall be performed.

6.8.5 Redundant inspection equipment. The contractor may elect to use redundant inspection equipment in lieu of using a single piece of equipment with a very low error rate. Where redundant equipment is used, the inspection system error rate is defined as the error rates of the multiple pieces of equipment multiplied together.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.8.6 Automated acceptance inspection equipment. Equipment for which no, or minimal, human involvement is required in the acceptance determination. This would include equipment employing probes/sensors/transducers that are automatically manipulated to perform measuring and detection functions. If readout is provided, the equipment will be categorized as automated even if operator interpretation is needed in the accept/reject decision.

6.9 Dimensional control of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production. If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action. All tools removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing they present objective evidence to the Contracting Officer to substantiate the request.

6.10 Submission of inspection equipment designs for approval. Test procedures and equipment designs will be submitted to Commander, ARDEC, ATTN: AMSRD-AAR-QEM-D, Picatinny, NJ 07806-5000. Request letter of submittal should state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph. Inspection equipment, inspection method and the frequency of inspection should be submitted for approval to ARDEC, ATTN: AMSRD-QEM-D, Picatinny, NJ 07806-5000.

6.11 Subject term (key word) listing.

M385A1 Cartridge (TP)
M918 Cartridge (TP)

6.12 Revisions/Amendments History. The following is a record of changes incorporated into this document:

ECP	Description	Date Approved
R04Q2015	Initial release of M169 MIL-DTL Specification	Aug 2004

6.13 Interim Revision This interim revision has been prepared at Program Manager request to document in ASSIST Online the version of a draft specification that was placed on contract in 2004. This interim revision has been dated to match the date of the draft specification that was placed on contract. It has been modified slightly to comply with MIL-STD-961 requirements for format, but not content. A fully coordinated revision, compliant with both MIL-STD-961 format and content requirements, will be approved for publication.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.14 Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issues due to the extensiveness of the changes.

Preparing activity:

Army-AR

(Project 1310-2006-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.