INCH-POUND

MIL-P-48698 (AR)
AMENDMENT 2
28 November 1988
SUPERSEDING
AMENDMENT 1
5 October 1987

MILITARY SPECIFICATION

PROBE AND S&A ASSEMBLY, TOW-2/E6

This Amendment forms a part of Military Specification MIL-P-48698 (AR), dated 27 April 1987, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1 Between MIL-STD-105 and DOD-STD-2000, add the following:

"MIL-STD-1169 Packaging, Packing and Marking for Shipment of Inert Ammunition Components"

PAGE 3

3.6, Line 3: Delete "is."

PAGE 4

3.18, Lines 2 and 6: Delete "0.5 ohms" and substitute "1.0 ohms."

PAGE 6

4.3.2, Line 4: Delete "byu" and substitute "by."

PAGE 41

* 4.4.2.31, Major 114: Delete paragraph in its entirety.

* 4.4.2.31, Major 115: Change paragraph to the following, "Height of tab straight shear, (.015 min.), (See Note 1)"

PAGE 42

4.4.2.31, Minor 208: Delete "3.2" and substitute "3.23."

AMSC N/A

FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

PAGE 46

* 4.4.2.33, Major 124: Delete paragraph in its entirety.

* 4.4.2.33, Major 125: Change paragraph to the following: "Height of tab straight shear, (.015 min), (See Note 1)"

PAGE 50

4.4.2.35, Minor 211: Delete "3.2" and substitute "3.23."

PAGE 53

4.4.2.37, Minor 206: Delete "3.2" and substitute "3.23."

PAGE 76 & 77

4.4.2.60: Next Higher Assembly: Delete "9398046" and substitute 9388046."

PAGE 77a

* 4.4.2.61, Add new paragraph as included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-48698 (AR)
Amendment 2

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.61	Mechanism Assembly	1 OF 1	9388005
			NEXT HIGHER ASSEMBLY 9387141

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Leaf spring in proper position		100%	3.2	Visual
102	Presence of shoulder washers		100%	3.2	Visual
103	Presence of piston actuator spacer		100%	3.2	Visual
MINOR					
201	Evidence of poor workmanship		1.00%	3.23	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

PAGE 82

4.5.2, After the last sentence add: "(See 6.8)."

4.5.3, After the last sentence add: "(See 6.8)."

PAGE 90

4.5.14.2.a, After the first sentence add the following:

"This test shall be conducted prior to continuity circuit tests described in 4.5.15 (Table V). The test circuit shall not exceed 40 microamperes."

TABLE IV. Delete in its entirety and substitute the following:

"TABLE IV - Open circuit tests

TEST	Resistance ≥ 1.0 megohm FROM (+)	TO (-)
1. Detonator switch*	red cable	inner tip
2. Tip switch	inner tip	black cable
3. Ogive switch	base contact	ogive (or rivet)

*WARNING: If test 1 fails STOP immediately. The S&A is unsafe and should be removed from the lot and disposed of."

4.4.15.2.a, Line 2: Delete "40 microamperes" and substitute "2 milliamperes."

PAGE 91

Table V, Column 3: Delete "0.5 ohms" and substitute "1.0 ohms."

5. PACKAGING., Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Preservation and packaging. The probe and its associated components shall be preserved and packaged in accordance with MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing of the probe and its associated components shall be in accordance with MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

5.4 Shipping. The probe and its associated components shall be shipped in the stowed condition in accordance with notes 16 and 17 of Dwg. 9387141."

PAGE 93

6.8 Add new paragraph as follows:

"6.8 Tip assembly. Upon insertion of the inert charge assembly, inner tip assembly, and crush ring, apply tip assembly to the probe with 30 ±1 in-lb torque and cure at ambient for 24 hours before commencing first article or lot quality confirmation testing."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A581)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.