MILITARY SPECIFICATION

PROPELLANT M30 FOR USE IN CARTRIDGE 105MM, APFSDS-T, M735, M735A1, AND XM774

This Amendment forms a part of Military Specification MIL-P-63105B (AR) dated 24 June 1980 and is approved for use by the US Army Armament Research and Development Command.

PAGE 1

Title: Add "(M774)" after "XM774" and wherever referenced in this specification.

PAGE 2

2.1: DRAWINGS (see 6.4): Delete "(see 6.4)".

3.1, Line 3: Delete "(see 2.1)".

PAGE 3

3.3, Line 1: Delete "(IMP)".

PAGE 5

4.4.2.4: Delete in its entirety, and substitute the following:

"4.4.2.4 Velocity uniformity (70°F) (see 3.3.1). - If the product of the velocity standard deviation times the factor 0.73 of the rounds tested in accordance with 4.5.1.2 exceeds the applicable requirement, apply referral criteria in accordance with 4.5.1.4.

PAGE 7

4.5.1.1.2, Line 10: Delete "th" and substitute "the".

PAGE 8

4.5.1.3b, Line 3: Delete "charges" and substitute "rounds".

FSC 1376

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

4.5.1.4b: Delete in its entirety and substitute the following "calibration correction exceeds 25 fps."

Custodian:
Army-AR

Preparing Activity
Army-AR
Project (1376-A194)

Source: https://assist.dla.mil -- Downloaded: 2026-04-23T02:11Z
Check the source to verify that this is the current version before use.