INCH-POUND

MS24287D
w/Amendment 1
21 April 2023
SUPERSEDING
MS24287D
14 July 2005

DETAIL SPECIFICATION SHEET

MATED ASSEMBLY, CONNECTOR RACK AND PANEL, MINIATURE

Inactive for new design after 8 June 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83733.

The Qualified Products List (QPL) associated with this inactive for new design specification will be maintained until acquisition of the product is no longer required, where upon the specification and QPL will be canceled.





FIGURE 1. Connector mating and mounting details.


AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:51Z
Check the source to verify that this is the current version before use.



PANEL CUT-OUT
(FIXED MOUNT)



PANEL CUT-OUT
(FLOATING MOUNT)

Dimension	Shell size		
	A	B	C
D	3.875	2.445	2.000
E	3.454	2.025	1.580
F	3.388	1.959	1.528
G	3.375	1.945	1.516


Inches	mm	Inches	mm
.002	0.05	1.081	27.46
.043	1.09	1.516	38.51
.097	2.46	1.528	38.81
.125	3.18	1.580	40.13
.146	3.71	1.945	49.40
.210	5.33	1.959	49.53
.243	6.17	2.000	50.80
.530	13.46	2.025	51.44
.562	14.27	3.375	85.73
.639	17.60	3.388	86.06
1.015	25.78	3.454	87.73
		3.875	98.43

Mating and mounting details of MS24285R, MS24286R, and MS27399 connectors for service or test.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm).

FIGURE 1. Connector mating and mounting details - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:51Z
Check the source to verify that this is the current version before use.



Dimension	Shell size		
	A	B	C
D	3.875	2.445	2.000
E	3.454	2.025	1.580
F	3.388	1.959	1.528
G	3.375	1.945	1.516

FIGURE 2. Connector mating and mounting details.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:51Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.002	0.05	1.528	38.81
.043	1.09	1.580	40.13
.097	2.46	1.945	49.40
.125	3.18	1.959	49.53
.146	3.71	2.000	50.80
.210	5.33	2.025	51.44
.562	14.27	2.445	62.10
.639	17.60	3.375	85.73
1.015	25.78	3.388	86.06
1.081	27.46	3.454	87.73
1.516	38.51	3.875	98.43

Mating and mounting details of MS24285R, MS24286H, and MS27399 connectors for service or test.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm).

FIGURE 2. Connector mating and mounting details – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:51Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration see figure 1.

This is a design specification. Not to be used a part number.

Part or Identifying Number (PIN): N/A

Referenced documents: In addition to MIL-DTL-83733 this document references the following:

MS24285	MS27399
MS24286	NASM24693
MS24695	
MS24700	

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

CONCLUDING MATERIAL

Custodians:
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2023-032)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:51Z
Check the source to verify that this is the current version before use.