MIL-E-1/1659(NAVY)
AMENDMENT 1
24 April 1969

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, MICROWAVE, NEGATIVE GRID

TYPE 5767

This amendment forms a part of Military Specification Sheet MIL-E-1/1659(NAVY), 6 March 1969.

Page 4

Figure 1: Add the following notes:

"1. Diameter "H" to be concentric with respective diameters as follows:

DIA. "A"	.040 T.I.R.
DIA. "G"	.030 T.I.R.
DIA. "K"	.030 T.I.R.
DIA. "B"	.060 T.I.R.

2. Diameter "A" to be concentric with diameter "G" within .030 T.I.R.

3. Total indicator reading includes out-of-roundness and plane tile of components.

4. Surface "F" must be clean and free of glass.

5. All external metal surfaces shall be silver plated, except from the end of the heater pin to a maximum of one half of its length. This portion shall be soldered."

User activities:
Navy - AS, OS, MC, CG, SH

Preparing activity:
Navy - EC
(Project 5960-N823)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-519/A-6521

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:14Z
Check the source to verify that this is the current version before use.