INCH-POUND

MIL-PRF-1/1655E
26 April 2005
SUPERSEDING
MIL-E-1/1655D
30 April 1988

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6080WC

This specification sheet is inactive for new design after 11 August 2000.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-1.

DESCRIPTION: Twin triode, low Mu

Outline - - - See figure 1.

Base - - - B8-98 (glass-bonded mica).

Envelope - - - T12.

Cathode - - - Coated unipotential.

Base connections:

Pin No. - - -	1	2	3	4	5	6	7	8
Element - - -	2g	2a	2k	1g	1a	1k	h	h

ABSOLUTE-MAXIMUM RATINGS:


Parameter:	Ef	Eb	Ec	Ehk	Rk/k	Rg/g	Ic/g	Ik/k	Pp/p	TE	Alt
Unit:	V	V dc	V dc	v	Ohms	Meg Ω	mA dc	mA dc	W	°C	ft
Maximum:	6.6	250	0	450	---	(see note 1)	5.0	200	13	300	(see note 2)
Minimum:	6.0	---	---	---	---	---	---	---	---	---	
Test conditions:	6.3	135	0	---	250	---	---	---	---	---	---

GENERAL:

Qualification: Not required.

AMSC N/A FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions in inches with metric equivalents (mm) in parentheses			
	Minimum		Maximum	
Conformance inspection, part 1				
A	---	---	4.063	(103.20)
B	---	---	1.719	(43.66)
C	3.125	(79.38)	3.500	(88.90)
D	1.438	(36.53)	1.563	(39.70)

FIGURE 1. Outline drawing of electron tube type 6080WC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.

TABLE I. Test conditions.

MIL-STD-1311	Requirement or test	Notes	Conditions	Acceptance level (see note 13)	Symbol	Limits		Unit
						Min	Max	
Method	Qualification inspection							
1216	Base material insulating quality		Glass-bonded mica, zone 5 minimum	---	---	---	---	---
1031	Variable-frequency vibration	4	Ec1 = -7 V dc; Rk = 0; Rp = 2,000 ohms	---	Ep	---	500	mV ac
	Conformance inspection, part 1							
1256	Electrode current (1) anode	6,7,8		0.4	Ib	100	150	mA dc
1266	Total grid current	4,8	Rg = 1.0 MegΩ; Rk = 125 ohms	0.4	Ic	0	-1.0	µA dc
1301	Heater current			0.4	If	2.25	2.65	A
1306	Transconductance (1)	6,7,9		0.4	Sm	6,000	8,200	µmhos
1336	Heater-cathode leakage	8	Ehk = +450 V dc; Ehk = -450 V dc	0.4	Ihk	---	50	µA dc
1201	Short and discontinuity detection			0.4	---	---	---	---
	Conformance inspection, part 2							
1211	Insulation of electrodes	6		2.5	R	200	---	MegΩ
1256	Electrode current (2) (anode)	6,7	Eb = 250 V dc; Ec = 250 V dc	2.5	Ib	---	10	µA dc
1306	Transconductance (2)	6,7,9	Ef = 5.7 V	2.5	$\frac{\Delta Sm}{Ef}$	---	10	%
1316	Amplification factor	6,7,9	Rk = 250 ohms	---	Mu	1.5	2.5	---

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.

TABLE I. Test conditions - Continued.

MIL-STD-1311	Requirement or test	Notes	Conditions	Acceptance level (see note 13)	Symbol	Limits		Unit
						Min	Max	
Method	Conformance inspection, part 2 -Continued							
1256	Electrode current (1) (anode) difference between sections			2.5	ΔIb	---	25	mA dc
1031	Sweep-frequency vibration	4,10	Rk = 0; Rp = 2,000 ohms; Ec = -7 V dc; F = 50 to 500 Hz; 2.5 G	6.5	Ep	---	500	mV ac
1101	Secureness of base, cap, or insert			---	---	---	---	---
1111	Base pin solder depth			---	---	---	---	---
1041	Shock	3,4	450 G; Ehk = +450 V dc; Ec = -7 V dc; Rp = 2,000 ohms; Rk = 0	---	---	---	---	---
1031	Sweep-frequency vibration fatigue	10	F = 50 to 500 Hz; 2.5 G; Ef = 6.3 V; no other voltages applied (except t = 48 hours)	6.5	---	---	---	---

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.

TABLE I. Test conditions - Continued.

MIL-STD-1311	Requirement or test	Notes	Conditions	Acceptance level (see note 13)	Symbol	Limits		Unit
						Min	Max	
Method	Conformance inspection, part 2 -Continued							
---	Post-shock and sweep-frequency vibration fatigue-test end points:							
1031	Sweep-frequency vibration			---	Ep	---	500	mV ac
1336	Heater-cathode leakage			---	Ihk	---	75	µA dc
1306	Transconductance (1)			---	ΔSmt	---	10	%
1266	Total grid current			---	Ic	0	-1.5	µA dc
1261	Electrode voltage (anode)	6	Rk = 0; Ec = 0; Eb/Ik = 200 mA dc	---	Eb	---	70	V dc
1131	Metallic base sleeve quality			---	---	---	---	---
1105	Permanence of marking			---	---	---	---	---
	Conformance inspection, part 3							
1506	Heater-cycling life		Ef = 7.5 V; Ehk = 300 V ac; Eb = Ec = 0; 1 min "on" 4 min "off"	---	---	---	---	---
---	Heater-cycling life-test end points:							
1336	Heater-cathode leakage			---	Ihk	---	75	µA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.

TABLE I. Test conditions - Continued.

MIL-STD-1311	Requirement or test	Notes	Conditions	Acceptance level (see note 13)	Symbol	Limits		Unit
						Min	Max	
Method	Conformance inspection, part 3 -Continued							
1516	Stability life	6	Eb = 150 V dc; Ehk = 300 V ac; Rk/k = 400 ohms; TA = room	---	---	---	---	---
---	Stability life-test end point (1 hour):							
1306	Transconductance (1) change of individual tubes			---	ΔSmt	---	10	%
1501	Intermittent life	5,12	Stability life-test conditions; TE = +250°C (min)	---	---	---	---	---
---	Intermittent life-test end points (1,000 hours):							
---	Inoperatives			---	---	---	---	---
1266	Total grid current			---	Ic	0	-5	μA dc
1306	Transconductance (2)			---	ΔSmEf	---	10	%
1336	Heater-cathode leakage			---	Ihk	---	50	μA dc
1301	Heater current			---	If	2.25	2.75	A
1306	Transconductance (1) change of individual tubes			---	ΔSmt	---	15	%
1211	Insulation of electrodes			---	R	100	---	MegΩ

See footnotes at top of next page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.

TABLE I. Test conditions - Continued.

NOTES:

1. Maximum grid-circuit resistance:

   a. 1.0 megohm for cathode-bias operation.

   b. 0.1 megohm for fixed-bias operation.

   c. 0.1 megohm for combined fixed and cathode-bias operation.

2. See "Reduced pressure (altitude) rating" and altitude, maximum peak voltage in the basic document.

3. A grid resistor of 0.1 megohm shall be added to each section; however, this resistor shall not be used when a thyratron-type short indicator is employed.

4. Tie 1k to 2k; 1g to 2g; and 1a to 2a.

5. Envelope temperature (TE) requirements, when measured in accordance with the temperature by conduction-band measurement (MIL-STD-1311, method 1226), will be satisfied if a tube having bogey Ib (±5 percent) under normal test conditions, is determined to operate at or above minimum specified temperature at any position in the life-test rack.

6. Test each unit separately.

7. Both units shall be operating.

8. This test to be performed at the conclusion of the holding period.

9. Rk bypassed with 1,000 µF capacitor.

10. Sweep-frequency vibration and fatigue-test procedure:

    (a) This test shall be performed with an average acceleration level equal to the specified value while being swept continuously during a time of approximately 1 minute through the frequency range of 50 to 500 Hz and back to 50 Hz.

    (b) The total excitation time for the test shall be not less than 3 minutes. The tube shall be mounted in each of three planes X, Y, and Z for one-third of the total excitation time. In each mounting plane, the tube shall experience at least one complete frequency sweep.

11. This test shall be conducted on the initial lot and thereafter on a lot approximately every 12 months. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. When one lot has passed, the 12-month rule shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.

TABLE I. Test conditions - Continued.

12. The life-test sample shall consist of 20 tubes per lot and no tube failure shall be permitted. In the event of rejection of the first sample, due to failure of any tube, a second sample of 20 tubes shall be selected from the lot. Acceptance shall then be based on the second samples.

13. This specification sheet uses accept on zero defect sampling plan in accordance with MIL-PRF-1, table III.

NOTE: Referenced documents. In addition to MIL-PRF-1, this document references the following:

MIL-STD-1311

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR
Navy - AS, CG, MC, OS
Air Force - 99

Preparing activity:
DLA - CC

(Project 5960-3759)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:13Z
Check the source to verify that this is the current version before use.