MIL-N-60211(MU)
AMENDMENT 2
18 August 1967
SUPERSEDING
AMENDMENT 1
31 May 1966

MILITARY SPECIFICATION

NETWORK C: 10526476

This amendment forms a part of Military Specification MIL-N-60211(MU), dated 3 March 1965.

Paragraph 3.4.7.3 (b): Delete in its entirety.

Paragraph 3.4.7.3 (d): Delete in its entirety and renumber remaining paragraphs of 3.4.7.3.

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926 except that the humidity shall be maintained at 92 to 97 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period the board shall be capable of performing the tests of 4.5.2.1.5, 4.5.2.4.3.4, 4.5.2.5.2.3, 4.5.2.6.3 and 4.5.2.7.5.2. In order to demonstrate this capability, the tests of 4.5.2.1.5, 4.5.2.4.3.4, 4.5.2.5.2.3, 4.5.2.6.3 and 4.5.2.7.5.2 shall be performed a minimum of once each 6 hours of the 24 hour period. The final test shall be conducted during the final portion of the 24 hour period. Between tests, the board must be electrically energized as described in Table IV and using the loads specified in 4.5.2.1.2.1,4.5.2.4.1.1, 4.5.2.5.2.1, 4.5.2.6.2 and 4.5.2.7.5.1."

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F., using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2."

Paragraph 4.5.1.5: Delete the second sentence in its entirety and substitute: "While at the operating temperatures of 3.3.3.1, the network shall be tested in accordance with 4.5.2.1.5, 4.5.2.4.3.4, 4.5.2.5.2.3, 4.5.2.6.3 and 4.5.2.7.5.2 to determine compliance with the requirements as specified in 3.3.3.1."

Table IV, Item No. column, line 14: Delete "21" and substitute "20".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.1.3.1: Delete the second sentence in its entirety and substitute: "The voltage measured from pin 17B to ground shall be plus 112 ± 15 volts dc."

Paragraph 4.5.2.4.3, line 3: Delete "- ± 1 to" and substitute "0 ± 1 volt to".

Paragraph 4.5.2.4.3.2, line 4: Delete "at 1.5" and substitute "at minus 1.5".

Table X: Delete Column C, Volts dc, in its entirety and substitute:

C Voltage less positive than
+0.3 vdc
+0.8 vdc
+0.7 vdc

Paragraph 4.5.2.6.2, line 5: Delete "4.10.2, item 20" and substitute "4.4.1.1, item 19".

Paragraph 4.5.2.7.2.1, line 2: Delete "90.0" and substitute "90.9". Also in line 8: Delete "between".

Paragraph 4.5.2.7.3.3: Delete in its entirety.

Paragraph 4.5.2.7.4 (a), line 5: Delete "micro seconds" and substitute "Milliseconds".

Figure 6A: Delete time base numbers of 0, 5, 10, 15, 20 and substitute time base numbers of 0, 10, 20.

Figure 7: Delete "-40°F +0 +140°F" and substitute "-40°F +0 +135°F".

Paragraph 4.5.2.5.2.3, line 3: Delete "4B" and substitute "4A".

Paragraph 4.5.2.7.3.3: Delete in its entirety and substitute:

"4.5.2.7.3.3 Disconnect the plus 35 volts from the module. The voltage from pin 5B to pin 24A shall be less than 1 volt. Remove power connections from pin 15A and pin 12B."

Paragraph 4.5.2.7.4 (a), line 2: Delete "6V ± 1.2 Volts" and substitute "10 ± 1.2 Volts".

Paragraph 4.5.2.7.4 (a), line 3: Delete "6 to 0" and substitute "10 to 0".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

Figure 6, Inverter Output at Pin 5B: Delete "-6 ± 1.2V" and substitute "-10.0 ± 1.2V".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A053

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.