MILITARY SPECIFICATION

TELESCOPE: XM126

This amendment forms a part of Military Specification MIL-T-60237(MU), dated 11 October 1965.

Paragraph 3.3.2: Delete "-65°" and substitute "-40°".

Paragraph 3.13: Delete "2 percent" and substitute ".2 mil".

Paragraph 3.16.1: Delete and substitute:

"3.16.1 Diopter adjustment torque.- The torque required to rotate the disengaged diopter knob shall be 2 ± 1 inch-pounds at standard ambient temperature (+60° to +90°F) and shall be 3 ± 2 inch-pounds at -40° and +150°F."

Add the following paragraph.

"3.16.1.1 Diopter knob disengagement.- The force required to disengage the diopter knob from its normal position shall be 4 ± 2 pounds at standard ambient temperature (+60° to +90°F) and shall be 6 ± 4 pounds at -40° and +150°F."

Paragraph 3.16.2 and 3.16.3: Delete "-65°" and substitute "-40°".

Paragraph 3.16.4: Delete "6 ± 2 pounds at -65° and +150°F" and substitute "6 ± 4 pounds at -40° and +150°F".

Paragraph 3.16.4.1: Delete "5 ± 2 inch pound at -65° and +150°F" and substitute "4 ± 3 inch pounds at -40° and +150°F".

Paragraph 4.3.2, Table 1: Add the following characteristic:

"131. Diopter knob disengagement 3.16.1.1 4.6.8.1"

Paragraph 4.5.2.3.4, 1st sentence: Delete "minimum range from zero to seventy-five pounds feet" and substitute "minimum range from zero to one hundred foot pounds."

Paragraph 4.5.2.3.5: Change paragraph number from "4.5.2.3.5" to "4.5.2.3.6".

Add new paragraph:

"4.5.2.3.5 Force requirements (disengagement).- Testing equipment for measuring direct force (pull) with a minimum range of zero to fifteen

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:22Z
Check the source to verify that this is the current version before use.

pounds, the accuracy of which shall be plus or minus two ounces throughout the entire zone of excursion, shall be utilized. The testing equipment shall be equipped with suitable adapters to accommodate testing of the diopter knob and boresight knobs."

Paragraph 4.6.5, 4th sentence: Delete "period of 5 minutes ± 15 seconds" and substitute "period of not less than 5 minutes".

Paragraphs 4.6.8, 4.6.10 and 4.6.12: Delete "4.5.2.3.3" and substitute "4.5.2.3.4".

Add new paragraph:

"4.6.8.1 Diopter knob disengagement.- Testing equipment conforming to the requirements of 4.5.2.3.5 shall be utilized for this test. The force (pull) required to disengage the diopter knob from its normal position shall be within the values specified in 3.16.1.1 for the temperature indicated."

Paragraph 4.6.9: Delete "-65°F" and substitute "-40°F".

Paragraph 4.6.11: Delete and substitute:

"4.6.11 Boresight knobs disengagement.- Testing equipment conforming to the requirements of 4.5.2.3.5 shall be utilized for this test. The force required to disengage each boresight from its normal position shall be within the values specified in 3.16.4 for the temperature indicated."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A056

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:22Z
Check the source to verify that this is the current version before use.