NOT MEASUREMENT SENSITIVE

MIL-T-62079E
15 August 1989
SUPERSEDING
MIL-T-62079D
14 July 1983

MILITARY SPECIFICATION

TRUCK, PANEL: POLICE PATROL CONVERSION, 8,000 POUNDS GVW, 4x2, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a gasoline engine driven, four-wheel, two-rear wheel drive, forward control type, commercial panel or window van truck converted to a police patrol wagon with a rear compartment for confined occupants. The vehicles have a minimum gross vehicle weight (GVW) of 8,000 pounds. Vehicles procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

	W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting, and Starting.
*	ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving, this document should be addressed to: US Army Tank-Automotive Command. ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

*	ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).

MILITARY

	MIL-B-46176	- Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative.

STANDARDS

FEDERAL

*	FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

	MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.
	MS51317	- Light, Warning, Vehicular, Rotating, D.C.

DRAWINGS

ARMY

	7261674	- Cover, with Chain, Radio Receptacle, Assembly.
	7722352	- Radio Receptacle Assembly.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

2.1.2 Other Government documents drawings and publications. The following other Government documents drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DODISS	- Department of Defense Index of Specifications and Standards.

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093).

DEPARTMENT OF TRANSPORTATION (DOT)

Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

* (Application for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.

(Application for copies of EPA publications should reference the Code of Federal Regulations 40 CFR and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

SAE, INC.
SAE Standards and Recommended Practices

J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J1349	- Engine Power Test Code – Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

(Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.4, the vehicle, components, assemblies and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer’s current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.2 Rusptroofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be provided.

3.1.1.3 Silicone brake fluid. When specified (see 6.2), and if available as the manufacturer's standard or optional brake fluid, silicone brake fluid conforming to MIL-B-46l76 shall be provided in the hydraulic brake system. A tag shall be placed near the master cylinder stating “CAUTION: USE SILICONE BRAKE FLUID ONLY, MIL-B-46176.”

3.1.1.4 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and cab, with all attachments, accessories and equipment; body and full complement of fuel, lubricants and coolant.

* 3.2.5 Gross vehicle weight. The gross vehicle weight (GVW) shall consist of curb weight, driver and assistant driver weight (computed at 175 pounds each), and a payload of not less than 2,000 pounds distributed evenly over the vehicle load area to provide not less than 8,000 pounds GVW.

3.2.6 Ratings. Vehicle and component ratings shall be the manufacturer's published ratings. Vehicular and component ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity.

3.2.7 Wheelbase. The wheelbase shall be not less than 123 inches.

* 3.2.8 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.9 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

3.3 Performance.

3.3.1 Speeds and gradeability. The vehicle shall maintain a high speed of not less than 58 miles per hour (mph) on smooth, approximately level, hard surfaced roads. The vehicle shall be capable of ascending grades of at least 20 percent in low speed range. Speed and gradeability requirements shall be met with the vehicle loaded to specified GVW.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to the specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.3.3 Parking brakes. A hand or foot actuated parking brake shall be furnished in addition to the service brakes. When a foot actuated parking brake is furnished, a hand lever shall be furnished to release the parking brake. The vehicle parking brake shall be capable of holding the vehicle loaded to the specified GVW on a 30 percent grade.

3.4 Chassis components.

* 3.4.1 Engine. The engine shall be a liquid cooled, internal combustion, four-stroke cycle, gasoline type, with not less than six cylinders. The engine shall develop not less than 110 net brake horsepower at the manufacturer's recommended governed speed. The engine net horsepower rating shall be in accordance with SAE J1349. The engine shall develop the specified horsepower when operated on unleaded fuel with a research octane rating of 91. The engine shall be capable of warranted operation on unleaded fuel. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

* 3.4.1.1 Oil filter. A full flow oil filter shall be furnished.

* 3.4.1.2 Cooling system. The cooling system shall maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F). A coolant level indicator consisting of an unbreakable translucent reservoir shall be provided in a position readily visible for checking the coolant level. The translucent reservoir shall be part of the coolant recovery system.

* 3.4.1.3 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided.

* 3.4.1.4 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling. The fan clutch shall be asbestos free.

3.4.1.5 Power plant heaters. When specified (see 6.2), coolant and battery heaters shall be provided. The heaters shall operate on 110-volts alternating current (ac), and shall be wired through a junction block, including a fuse or a circuit breaker, to a single three pronged (male), weatherproof, slave receptacle for receiving external power and grounding the vehicle. A three wire connecting cable, 25 feet long and of adequate line capacity to supply power for the heater

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard, three pronged (two power plus one ground) male connector at the other end. All electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. A carrier for the connecting cable shall be mounted within the cab or engine compartment and shall provide positive cable retention during vehicle operation. Heaters shall be furnished as follows:

(a) A coolant heater, l500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. An engine thermostat with an operating range of l70°F to 195°F shall be installed
(b) The battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than l0°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

3.4.2.1 Ignition system. An ignition system of 12-vo1t direct current (dc) potential shall be furnished. An alternator of not less than 55 amperes dc output shall be furnished. The maximum constant electrical load, including the radio, shall not exceed 80 percent of the maximum output capacity of the alternator furnished. The vehicle radio electrical load is established at 7 amperes for monitor and 18 amperes for transmission. The using activity will furnish and install the radio.

3.4.2.2 Battery. The battery shall be of 12-volt potential. The reserve capacity rating, measured in accordance with SAE J537, shall be not less than 80 minutes. The cold cranking rating at 0°F, measured in accordance with SAE J537, shall be not less than 350 amperes. The battery shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-13l.

3.4.2.3 Auxiliary 24 volt system with radio outlet. When specified (see 6.2), an auxiliary 24 volt system with a shielded wiring harness and radio outlet with cover shall be furnished. The receptacle and cover shall conform to Drawings 7722352 and 7261674, and shall be marked with a pressure sensitive label: “24-VOLT RADIO OUTLET.” The receptacle shall be located on the side opposite the driver, on the instrument panel in the cab. The shielded wiring harness shall be connected to the receptacle and to a 12-volt to 24-volt converter. The converter shall operate from the 12-volt battery (see 3.4.2.2) and shall have an output capacity of not less than 25 amperes.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T01:15Z
Check the source to verify that this is the current version before use.

* 3.4.2.4 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67 (except compliance with 393.67(c), subparagraphs (1), (4), (ii), (8), (9), (11), 393.67(d) and 393.67(f) is not required).

3.4.3.1 Air cleaner. An air cleaner shall be furnished.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. The exhaust shall discharge to the atmosphere to the rear of the vehicle or to the side behind the rear wheels.

3.4.5 Gear train.

3.4.5.1 Transmission. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.5.2 Automatic transmission. Unless otherwise specified (see 3.4.5.3), the contractor's current standard automatic transmission, having not less than three forward gear ratios and one reverse gear ratio, shall be furnished.

3.4.5.3 Manual transmission. When specified (see 6.2), a manual transmission shall be provided. The transmission shall have not less than three forward speeds and one reverse speed. The transmission shall provide for maximum ease of shifting with synchronized shift in all gear ranges.

* 3.4.5.3.1 Clutch. The clutch shall be the largest capacity clutch offered for the type of vehicle and engine furnished with the clutch torque capacity exceeding the maximum delivered engine torque. The clutch lining shall be asbestos free.

3.4.6 Driveline Components. The driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Suspension. The vehicle shall be equipped with a suspension system, with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to the specified GVW. When the suspension is rated at the spring pads, the unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at each wheel. When specified (see 6.2), heavy duty springs and shock absorbers, front and rear, shall be furnished. Heavy duty is defined as having

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

a rated capacity equal to the load imposed, plus at least 5 percent, with the vehicle loaded to the specified GVW. Suspension stabilizer devices shall be furnished when available for the model chassis furnished, when heavy duty springs and shock absorbers are specified.

3.4.8 Axles. Axle ratings and independent front suspension ratings, when furnished, shall be at least equal to the load imposed on each component, measured at the ground, with the vehicle loaded to the specified GVW. A single reduction rear axle shall be furnished.

3.4.8.1 Positive-traction differential. When specified (see 6.2), a rear axle with positive-traction, limited-slip or automatic locking differential shall be furnished.

* 3.4.9 Wheels, rims, tires and tubes. The vehicle shall be equipped with single front and rear wheels. Rims shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Multi-piece rims shall not be furnished. Rims and disc wheel sizes shall be the same for all wheels on the vehicle. Tire size and load range (ply rating) shall be the same for all tires on the vehicle.

* 3.4.9.1 Tires. Steel belted radial ply or, when specified (see 6.2), bias ply tires shall be furnished. Unless otherwise specified (see 6.2), tires shall be of the tubeless type with highway tread. Tires shall have a rating of not less than load range D (8-ply rating). The tires shall have a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to the specified GVW. Tires shall conform to Tire and Rim Association recommendations, or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

* 3.4.9.2 Inner tubes. When tube type tires are specified in procurement documents, the inner tubes shall be of proper size for the tires furnished. When mounted on other than drop center rims, tire flaps shall be installed in accordance with Tire and Rim Association recommendations.

* 3.4.9.3 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier design shall permit easy removal or mounting of the spare wheel assembly using only the tools specified in 3.4.14. If the carrier is located in the rear passenger compartment, it shall be provided with a lock and key to secure the spare wheel or rim or spare tire assembly.

3.4.9.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified (see 3.4.9.5), a spare wheel or rim shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.4.9.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the vehicle.

* 3.4.10 Brakes. The manufacturer's standard power brakes shall be furnished. Brake linings shall be of nonasbestos material.

3.4.11 Steering. Power steering shall be furnished.

3.4.12 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and washers. Windshield wipers shall be of the multispeed type and operated by electric motor(s).

3.4.13 Bumpers. Front and rear bumpers shall be provided.

3.4.13.1 Rear bumper. When side facing seats in the rear compartment and a rear entrance door are furnished (see 3.5.1, 3.5.4.1 and 3.5.4.3), the rear bumper shall be a heavy duty channel type, with a safety-tread step. The step shall be not less than 8 inches deep and shall extend not less than the full width of the rear door(s). The step height shall be approximately half the distance between the ground level and the body floor height.

3.4.14 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging the mounted tire assembly with the spare assembly and shall include at least a jack, a jack handle, and a wheel nut wrench. The jack shall be of such closed height as to permit its location under the axle or other satisfactory lift point, at any wheel with a tire flat. The jack, without blocking, shall be capable of raising any wheel of a loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly. The tools shall not be stowed in the rear passenger compartment.

3.4.15 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to the windshield defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver. A rear compartment heater shall be furnished and protected with a cover to prevent damage to the heater by the occupants. The heater control shall be located in the driver’s compartment in a location readily accessible to the driver.

3.4.15.1 Air conditioning. When specified (see 6.2), a driver's area air conditioning system shall be furnished. A tinted safety glass windshield shall be furnished. When specified (see 6.2), a rear compartment air conditioning system shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

* 3.4.16 Controls and operating mechanism. The vehicle shall be of the forward control type. All controls and operating mechanisms shall be located for left-hand drive. The controls shall be complete and conveniently operable by the driver. The lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. All instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. The instruments shall be panel mounted. All instruments shall be visible to the driver when seated in the driving position.

3.4.17 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, voltmeter, or charging indicator
(c) Fuel gage
(d) Oil pressure gage or red indicator warning light
(e) Engine temperature gage or indicator
(f) Speedometer with recording odometer
(g) Ash receptacle, permanently attached
(h) Two padded sunvisors
(i) Driver's compartment ventilator, other than window,

3.4.17.1 Rearview mirrors. An inside rearview mirror shall be furnished. An outside rearview mirror shall be provided on each side. The outside rearview mirrors shall be of the Junior West Coast or low mount type incorporating a wide angle viewing system. The upper mirror shall have a flat reflective area of not less than 35 square inches. The lower mirror shall have a convex reflective area of not less than 20 square inches. The mirror assembly heads shall be adjustable and mounted to minimize obstruction of forward lines of vision.

3.4.18 Horn. The manufacturer’s standard electric horn shall be furnished.

3.5 Cab and body. The panel truck, with integral cab, shall consist of a driver's compartment (cab), a partition, and a rear compartment as specified herein.

3.5.1 General construction. The integral cab and body unit shall be of all metal construction having provisions for doors and windows specified herein. Drip rails shall be installed above the doors. The driver’s compartment shall be separated from the rear compartment by a full width and full height partition. At the manufacturer’s option, the vehicle shall conform to one of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

(a) Rear doors in accordance with 3.5.4.1, side facing bench seats in accordance with 3.5.4.3, and a body with steel side panels without side windows; or
(b) A curbside door in accordance with 3.5.4.2, forward facing bench seats in accordance with 3.5.4.4, and a body with or without side windows in accordance with 3.5.4.5.

3.5.2 Driver's compartment. The driver's compartment (cab) shall have the manufacturer's current standard doors on each side. The doors shall be equipped with crank-regulated, safety glass windows. The doors shall be furnished with locks, operable from inside the vehicle with mechanical linkages with at least the curbside door equipped with an external key-operated lock. Individual upholstered driver's and auxiliary seats shall be furnished. The driver's seat shall be adjustable. Seat belts shall be furnished for both seats. A domelight and ventilator(s) shall be provided. A full headliner shall be provided in the driver's compartment.

3.5.3 Partitions. At the manufacturer's option, either a two- or three-section partition separating the driver's compartment from the rear compartment shall be provided. The intent of the partition is to provide maximum security with provisions for emergency exit for the rear compartment passengers. The partition shall be fabricated of not less than 16 gage (0.0598 inch) steel or fiberglass reinforced plastic plywood panel. The plywood shall be not less than 3/4 inch in thickness covered on each side with white fiberglass to form a total thickness of approximately 0.835 inch.

3.5.3.1 Two-section partition. The partition section behind the driver shall be stationary and permanently secured to the sides, roof, and floor of the body. The partition section behind the assistant driver shall slide to the driver's side in channel guides, in front of the stationary section. The sliding partition shall be equipped with fastening devices in the driver's compartment and shall be such as to prevent opening from the rear compartment. The forward end of the sliding door track shall be covered to prevent possible injury to the front seat passenger in case of a sudden jolt to the vehicle.

3.5.3.2 Three-section partition. The partition section at the right and left sides of the vehicle shall be permanently secured to the sides, roof, and floor of the body. The center section shall be a door not less than 18 inches in width and extending from the floor to as near the ceiling as possible. The door shall clear the cab headliner when in a fully open position. The door shall be secured to the left partition with a piano type hinge on the driver's seat side of the front compartment and shall open toward the driver's seat. The door shall be equipped with a minimum of three nonspring-loaded fastening devices on the auxiliary seat side of the driver's compartment, one at the top; one in the center; and one on the bottom; all arranged to prevent opening the door from the rear compartment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.5.3.3 Partition openings. On a two-section partition, the stationary and sliding section shall each have an opening located to provide a view of the rear compartment by both the driver and the assistant driver. On a three-section partition, the center door shall have one such opening. Each opening shall be approximately 15 inches long by 8 inches high. Each opening shall be screened with steel screen of 1/8-inch minimum diameter having a maximum of 3/8-inch mesh opening or shall be screened with flattened, expanded metal of equivalent strength. The screens shall be welded or otherwise permanently attached to the partition. The screen installations shall prevent passengers in the rear compartment from knocking out or kicking out the screens. A side-sliding heavy duty metal panel shall be provided on the driver compartment side to allow closing of each of the screen openings. The partition and sliding panels shall be reinforced, as necessary, to prevent a drumming or oil canning effect when pushed by the passengers hand(s).

3.5.4 Rear compartment. The rear compartment loadspace at the floor level in back of the partition shall be not less than 95 inches in length and not less than 52 inches in height. The length shall be measured at the floor level between the compartment partition and the rear doors. The rear compartment side of the partition shall be smooth and free of any sharp edges or corners which could result in injury to passengers either willfully or accidentally. The rear compartment interior roof lining and roof bows shall be fabricated and installed to prevent occupants from manually pulling down or damaging the bows and liner.

3.5.4.1 Rear doors. When side facing bench seats are provided, double rear doors, hinged at the sides, shall be provided. The doors shall be provided with clear (not one-way privacy type) safety glass in the upper section of each door. The windows shall be completely covered on the inside with steel screen as specified in 3.5.4.6. Both rear doors shall have latches on the outside only, both capable of being opened from the outside, and shall be such as to prevent opening from the inside. Door checks shall be provided to hold doors in the full open position. Grab handles shall be provided on the inside of the doors.

3.5.4.2 Side door. When forward facing bench seats are provided, an entrance door located on the curbside of the rear compartment shall be furnished. The door may be of either the sliding or hinged type. The door shall have latches on the outside only, capable of being opened from the outside, and shall be such as to prevent opening from the inside. In addition to the side door, rear door(s), if provided as the manufacturer's standard, shall be rendered incapable of being opened. Clear (not one-way privacy type) safety glass windows shall be provided in the upper section at the rear. Windows shall be completely covered on the inside with steel screen in accordance with 3.5.4.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.5.4.3 Side facing seats. When rear entrance doors are provided, a bench seat extending the full length of the rear compartment shall be provided on each side of the body for seating passengers. The bench frames shall be of all metal construction with slat type hardwood back rests and seats. The bench height measured from the floor to the front edge of the bench shall be 13 inches plus or minus 1 inch.

3.5.4.4 Forward facing seats. When a side entrance door is provided, forward facing bench type fiberglass seats in the normal configuration for 15-passenger vans shall be furnished. Seat belts shall be furnished for each passenger and shall meet the requirements of Federal Motor Vehicle Safety Standards 208, 209, and 210.

3.5.4.5 Rear compartment windows. When a rear entrance door and side facing bench seats are provided, no side windows shall be provided in the rear compartment. When a side entrance door and forward facing bench seats are provided, side windows shall be of the one-way privacy type or no side windows shall be provided, at the manufacturer's option. When side windows that normally would open are furnished, they shall be screened to prevent opening.

3.5.4.6 Covering for rear compartment windows. All windows in the rear compartment shall be screened with steel screen of 1/8-inch minimum diameter having a maximum of 3/8-inch mesh opening or shall be screened with flattened, expanded metal of equivalent strength. The screen shall be welded or otherwise permanently attached to the body. The screen installations shall prevent passengers from knocking out or kicking out the screens.

3.5.4.7 Roof ventilators. Two roof type powered ventilators with rainproof covers shall be installed in the rear compartment at the approximate centerline of the vehicle. Each ventilator shall be of the power intake type having a capacity of not less than 200 cubic feet per minute. A variable speed control for the ventilators shall be mounted on the instrument panel. The ventilators shall be covered on the inside with heavy wire screen of at least 14 gage wire with 1/4 square inch openings. Screen installation shall prevent passengers from knocking in or pulling down the screen with their hands. All wiring shall be completely inclosed to preclude tampering.

3.5.4.8 Domelight. A domelight shall be installed in the rear compartment operable from a switch mounted on the instrument panel and by a rear or side door operated switch. The light shall be tamper proof; electric wiring shall be enclosed inside body framing or installed in metal conduit. The light shall be protected with a heavy wire screen or expanded metal cage. The cage construction and installation shall prevent passengers from both knocking in or pulling down the cage with their hands.

3.5.4.9 Insulation. Insulation shall be provided in the exterior doors, walls, and ceiling of the body and shall provide resistance to transfer of heat equivalent to the protection afforded by a l-inch thick batt having a thermal conductivity (k) of 0.24 in normal ambient air temperatures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

The insulation shall be either flexible or batt type, asbestos free fibrous or cellular material, having a moisture absorption capacity of less than 2 percent by weight. Materials shall be odorless and fire-retardant. The insulation shall neither breed nor promote the growth of fungus and shall neither cause nor accelerate corrosion of steel, copper or aluminum. The insulation shall be cemented to the inner side of external walls and provided with means to retain insulation under all operating conditions. The cement shall be waterproof and the resulting bond shall provide a shear strength sufficient to prevent sag of the insulation when the assembled vehicle is operated at speeds up to 55 mph over improved roads. All insulation, to the maximum practicable extent, shall be installed prior to the closing of spaces in the body sides, front and rear panels, ends, doors, upright body members, roof, roof bows, and other parts.

3.6 Warning light. Unless otherwise specified (see 3.6.1 and 3.9.2), a rotating red warning light conforming to MS51317-2 shall be mounted, with reinforcement at the point of attachment on the cab roof, on the vehicle centerline. It shall be so located as to present minimum interference with the spotlight beam sweep (see 3.8). The light shall be operated by means of a separate switch located on the instrument panel in a location readily accessible to the driver. Illumination of the switch shall be provided by the instrument panel lighting system. The switch shall be marked to indicate switch function and "on" and "off" positions. The light shall be so mounted as to afford 360-degree visibility to all approaching traffic. At the option of the manufacturer, or when specified (see 6.2), the light shall be removed for shipment after the first production vehicle inspection (see 4.3). When removed, the light and mounting devices shall be packaged and stowed within the vehicle, and the roof opening shall be provided with a weather-tight cover. Provisions for reinstalling the light, including access to the light wiring, shall be provided.

3.6.1 Strobe light. When specified (see 6.2), in lieu of the warning light specified in 3.6, a strobe type warning light shall be furnished. The warning light shall be an integral solid-state unit, having a xenon tube peak output rating of not less than 1,000,000 candlepower and a flash rate of 90 $\pm$ 15 flashes per minute. The strobe light unit shall include a xenon flash tube with optic lens, mounted in a weatherproof housing, with protective clear or colored dome and corrosion-resistant metal base. The housing shall be not less than 8-1/2 inches high and 8-3/4 inches base diameter. The warning light color shall be red. The mounting, installation, wiring and switch shall be as specified in 3.6.

3.7 Grille mounted warning lights. When specified (see 6.2), two red flashing warning lights shall be mounted behind the front bumper in the vicinity of the vehicle's front grille. The warning lights shall be installed on a horizontal plane through the centerline of the headlights. The warning lights shall be sealed beam lamps, 6 inches in diameter, with a minimum output

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

rating of 200 candlepower. The two grille lights shall have a combined flash rate of not less than 80 flashes per minute. The grille mounted warning lights shall be operated by means of a separate switch, with a red indicating light, located on the instrument panel and marked to indicate the function of the switch.

3.8 Spotlight. A spotlight shall be provided and mounted with reinforcement at the point of attachment, for remote operation by the assistant driver. The light shall be mounted so as to provide maximum light beam sweep to both sides of the highway. The spotlight beam shall receive minimum interference from the warning light bar. The spotlight operating controls shall in no way obstruct operator vision through the windshield or other glass surfaces, nor shall they present any hazardous condition.

3.9 Siren system. When specified (see 6.2), an electronic siren system with selector controls for siren, public address and radio amplification through an external speaker shall-be provided. The system shall be a Federal PA-20A, Dietz 14-450 or Unity SPR 73 Model or equivalent. The system shall have a sound intensity of not less than 98 decibels at a distance of 100 feet from the speaker, using a reference pressure of 0.0002 microbar. The amplifier and its controls shall be installed inside the vehicle in a location accessible to the driver and assistant driver. A microphone of the magnetic noise cancelling type, connected by a coiled cord, shall be provided and located in a position convenient for use by both the driver and the assistant driver. Microphone stowage shall be provided on the instrument panel. The system shall permit the broadcasting of routine and emergency radio announcements from an on-board vehicle radio to be installed by the Government. The siren shall be capable of being actuated by both a foot operated switch and the standard horn actuator. A separate dash mounted switch for driver preselection of horn or siren operation shall be provided. The amplifier unit shall include volume control and selection of “Radio,” “P.A.,” and “Manual,” “Yelp,” “Wail,” and “Hi-Lo” (European) siren modes. The switch positions shall be identified.

3.9.1 Speaker. Unless otherwise specified (see 3.6), when a siren system is specified (see 3.9), an external speaker with a weatherproof driver shall be installed on the centerline of the cab roof in a location that will not obstruct light from or movement of the roof mounted spotlight. The speaker shall be of the low silhouette type, designed for roof mounting. The speaker shall be metal with a chrome finish, or fiberglass painted to match the vehicle exterior color. A gasket not less than 1/16 inch thick shall be furnished between the speaker mounting bracket and the vehicle to minimize drumming. When necessary to prevent deflection and drumming, reinforcements shall be provided on the vehicle at the point of attachment of the speaker. The speaker location shall permit servicing of the vehicle without removing the speaker.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.9.2 Warning light bar with integral speaker. When specified (see 6.2), in lieu of the warning light specified in 3.6 and the speaker specified in 3.9.1, a warning light bar with integral speaker shall be furnished. The light bar shall include 2 red warning lights, one on each end, and shall be located so as to present minimum interference to any spotlight beam sweep (see 3.8). Control illumination and visibility shall be as specified in 3.6. At the option of the manufacturer, or when specified (see 6.2), the warning light bar shall be removed for shipment after the first production vehicle inspection (see 4.3). When removed, the light and mounting devices shall be packaged and stowed within the vehicle. Provisions for reinstalling the light bar, including access to light wiring shall be provided. The integral speaker shall be of weatherproof design.

3.10 Servicing and adjusting. Prior to acceptance of the vehicle by the Government, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of the engine, electrical, and brake systems; filling and charging of the battery; alinement of the front wheels; inflation of all tires; complete lubrication of the chassis, engine, and running gear with grades of lubricants recommended for the ambient temperature at the vehicle delivery point; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

3.11 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however this does not authorize submission of known

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance with the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract. Failure of the first production vehicle to meet the requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles until corrective action has been taken.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on the front and rear axles. The total imposed loading on front and rear axles shall be computed by the contractor and verified by the Government, using the curb weight, the operator and assistant weights at 175 pounds each, and the payload required to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet the contract requirements.

* 4.3.2 Road test. To determine conformance to 3.3.1, the vehicle shall be loaded to the specified GVW and shall be operated on smooth, hard surfaced roads for not less than 50 miles at speeds up to not less than 55 mph.

* 4.3.3 Body treatment and painting. The certification regarding the body cleaning, treating, prime painting and salt spray resistance testing, as required by MIL-STD-1223, shall be made to Government representatives at the first production vehicle inspection.

4.3.4 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

4.3.5 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.10 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicle covered by this specification is intended for general nontactical use by the Government for police patrol activities and for transporting confined occupants.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(c) Identification of appropriate service for painting and marking (see 3.1.1.1).
(d) Concealed markings, if required (see 3.1.1.1).
(e) Rustproofing, if required (see 3.1.1.2).
(f) Tropical rustproofing, if required (see 3.1.1.2).
(g) Silicone brake fluid, if required (see 3.1.1.5).
(h) Power plant heaters, if required (see 3.4.1.1).
(i) Auxiliary 24-volt system, if required (see 3.4.2.3).
(j) Manual transmission, if required (see 3.4.5.3).
(k) Heavy duty springs and shock absorbers, if required (see 3.4.7).
(l) Positive-traction, limited slip or automatic locking differential, if required (see 3.4.8.1).
(m) Bias ply or other type tires, if required (see 3.4.9.1).
(n) If spare tire carrier is not required (see 3.4.9.3).
(o) Spare wheel or rim, if required (see 3.4.9.4).
(p) Spare tire assembly, if required (see 3.4.9.5).
(q) Tools, if required (see 3.4.14).
(r) Air conditioning, if required (see 3.4.15.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

(s) Rear air conditioning, if required (see 3.4.15.1).
(t) Removal of warning light, for shipment, if required (see 3.6).
(u) Strobe type warning light, if required (see 3.6.1).
(v) Grille mounted warning lights, if required (see 3.7).
(w) Siren system, if required (see 3.9).
(x) Warning light bar with integral speaker, if required (see 3.9.2).
(y) Removal of light bar for shipment, if required (see 3.9.2).

* 6.3 Subject term (key word) listing.

Driver's compartment partition
Siren system
Strobe light
Truck, commercial
Truck, police patrol conversion
Warning light.

6.4 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Navy - YD

Preparing activity:
Army - AT

Project No. 2320-0419

Review activities
Army - CR, ER
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.