NOT MEASUREMENT SENSITIVE


MIL-D-3943/168
5 June 1995

MILITARY SPECIFICATION SHEET

DECORATION, ACHIEVEMENT AWARD, OFFICE OF PROTECTION SERVICES, SMITHSONIAN INSTITUTE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:

DIAMETER: 1-3/8 inches (3.49 cm) (REF)

THICKNESS (At Edge): 0.125 inch ± 0.010 inch (0.318 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T01:14Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lettering shall be incised on the reverse.

3. Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XV, Style 6 with a Class 1 or 1A pad.

4. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/386.

5. The lapel button shall conform to MIL-L-11484/228.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0811)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:14Z
Check the source to verify that this is the current version before use.