NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/169A
1 May 1997
SUPERSEDING
MIL-D-3943/169
5 June 1995

DETAIL SPECIFICATION SHEET

DECORATION, DIRECTOR'S AWARD, OFFICE OF PROTECTIVE SERVICES, SMITHSONIAN INSTITUTE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Red Brass

FINISH: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER: 1-3/8 inches (3.49 cm) (REF)
THICKNESS (At Edge): 0.125 inch ± 0.010 inch (0.318 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:14Z
Check the source to verify that this is the current version before use.

SUSPENSION BAR:
HEIGHT: 9/32 inch ± 1/64 inch (0.71 cm ± 0.04 cm)
WIDTH: 1-15/32 inches ± 1/64 inch (3.73 cm ± 0.04 cm)
THICKNESS (At Edge): 0.100 inch ± 0.010 inch (0.254 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The suspension ring shall have an outside diameter of 3/8 inch ± 1/64 inch (0.95 cm ± 0.04 cm) and finished to match the pendant and suspension bar.

3. Enameled areas shall be Green as indicated. The color shall conform to the TIOH color chip number 11 or the standard sample.

4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

5. Lettering shall be incised on the reverse.

6. Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type XV, Style 6 with a Class 1 or 1A pad.

7. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/387.

8. The lapel button shall conform to MIL-DTL-11484/229.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:14Z
Check the source to verify that this is the current version before use.