NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/172A
1 May 1997
SUPERSEDING
MIL-DTL-3943/172
19 October 1995

DETAIL SPECIFICATION SHEET

DECORATION, EXCEPTIONAL SERVICE AWARD, DEPARTMENT OF ENERGY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



OBVERSE

REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER:
-1: 1-1/2 inches (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:15Z
Check the source to verify that this is the current version before use.

HEIGHT (Including Lug):
-1: 1-11/16 inches ± 1/64 inch (4.29 cm ± 0.04 cm)
-2: 27/32 inch ± 1/64 inch (2.14 cm ± 0.04 cm)

THICKNESS (At Thickest Point):
-1: 0.140 inch ± 0.010 inch (0.356 cm ± 0.025 cm)
-2: 0.095 inch ± 0.010 inch (0.241 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lug shall be cut into the working die.

3. For Dash No. -1, the lug shall be 7/32 inch ± 1/64 inch (0.56 cm ± 0.04 cm) in diameter, 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) thick with a 3/32 inch ± 1/64 inch (0.24 cm ± 0.04 cm) hole. The lug shall be flush with the reverse.

4. For Dash No. -2, the lug shall be 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm) in diameter, 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) thick with a 3/32 inch ± 1/64 inch (0.24 cm ± 0.04 cm) hole. The lug shall be flush with the reverse.

5. The suspension link ring for Dash No. -1 shall be fabricated from 0.062 inch (0.155 cm) nominal diameter brass wire with the same finish as the pendant. The finished link shall have an outside diameter of 1/4 inch ± 1/64 inch (0.14 cm ± 0.04 cm).

6. The suspension link ring for Dash No. -2 shall be fabricated from 0.036 inch (0.091 cm) nominal diameter brass wire with the same finish as the pendant. The finished link shall have an outside diameter of 1/8 inch ± 1/64 inch (0.14 cm ± 0.04 cm).

7. The decoration set shall consist of a regular size medal, a miniature size medal, a service ribbon and a rosette. The presentation case shall be as specified by the procuring agency.

8. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/469.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Civil Agency Coordinating activities:
DOE

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:15Z
Check the source to verify that this is the current version before use.