INCH-POUND

MIL-DTL-3943/174B
18 July 2012
SUPERSEDING
MIL-DTL-3943/174A
1 May 1997

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS SERVICE AWARD, U.S. DEPARTMENT OF ENERGY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
- 2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C- 230).

FINISH (-1 and -2): Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:16Z
Check the source to verify that this is the current version before use.

-1: 1-1/2 inches (REF)
-2: 3/4 inch (REF)

HEIGHT (Including lug):
-1: 1-11/16 inches ± 1/64 inch
-2: 27/32 inch ± 1/64 inch

THICKNESS (At thickest point):
-1: 0.140 inch ± 0.010 inch
-2: 0.095 inch ± 0.010 inch

LUG & SUSPENSION LINK RING:

1. The lug shall be cut into the working die.

2. The lug for -1 shall be 7/32 inch ± 1/64 inch in diameter, 1/16 inch ± 1/64 inch thick with a 3/32 inch ± 1/64 inch hole. The lug shall be flush with the reverse.

3. The lug for -2 shall be 1/8 inch ± 1/64 inch in diameter, 1/16 inch ± 1/64 inch thick with a 3/32 inch ± 1/64 inch hole. The lug shall be flush with the reverse.

4. The suspension link ring for -1 shall be fabricated from 0.062 inch nominal diameter brass wire with the same finish as the pendant. The finished link shall have an outside diameter of 1/4 inch ± 1/64 inch.

5. The suspension link ring for -2 shall be fabricated from 0.036 inch nominal diameter brass wire with the same finish as the pendant. The finished link shall have an outside diameter of 1/8 inch ± 1/64 inch.

DECORATION SET: Decoration set shall consist of a regular size medal, a miniature size medal, a service ribbon. The presentation case shall be as specified by the procuring agency.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape and service ribbon is MIL-DTL-11589/470.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:16Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army – IH

(Project No. 8455-2012-043)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:16Z
Check the source to verify that this is the current version before use.