NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/178C
16 March 2020
SUPERSEDING
MIL-DTL-3943/178B
9 February 2015

DETAIL SPECIFICATION SHEET

DECORATION, JOINT DISTINGUISHED CIVILIAN SERVICE AWARD, CHAIRMAN OF THE JOINT CHIEFS OF STAFF

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER: 1-3/8 inches (REF)
THICKNESS (At thickest point): 0.125 inch $\pm$ 0.005 inch

DECORATION SET: Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XV, Style 6 with a Class 1 or 1A pad.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:17Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape and for the service ribbon is MIL-DTL-11589/489.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/244.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-229)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:17Z
Check the source to verify that this is the current version before use.