MILITARY SPECIFICATION

ANTENNA AS-1735/SRC

This amendment forms a part of Military Specification MIL-A-24233A(EC), dated 7 January 1977.

PAGE 1

2.1, After MIL-STD-105, add "MIL-STD-108, Definitions of and Basic Requirements for Enclosures for Electronic Equipment".

PAGE 2

Following 3.5.9, add the following as paragraph 3.5.10:

"3.5.10 Moisture leakage. The antenna feeder system assembly shall be of vapor tight construction to prevent antenna performance degradation due to ingress of moisture into the feeder system. Assembly of coaxial cables, connector fittings and parts shall be vapor sealed at ends and junctions as specified in MIL-STD-108. The antenna feeder system vapor seals shall be acpable of withstanding a minimum test pressure of 4.0 pounds per square inch gage (PSIG)".

PAGE 4

TABLE I, Following "Vibration" add the following:

"Moisture Leakage"	"3.5.10"	"4.5.11"

PAGE 5

Following 4.5.10, add the following as paragraph 4.5.11:

"4.5.11 Moisture leakage. Moisture leakage shall be tested by pressurizing the feeder system to 4.0 PSIG. The antenna shall then either be submerged in water, in which case there shall be no evidence of air leaks, or if the antenna is not submerged, the pressure at the end of a 24 hour period shall not have dropped below 3.6 PSIG."

Preparing activity:
Navy - EC
(Project 5985-N492)

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:21Z
Check the source to verify that this is the current version before use.