INCH-POUND

MIL-S-24236B
SUPPLEMENT 1B
20 DECEMBER 1989
SUPERSEDING
SUPPLEMENT 1A
17 April 1978

MILITARY SPECIFICATION

SWITCHES, THERMOSTATIC, (METALLIC AND BIMETALLIC)
GENERAL SPECIFICATION FOR

This supplement forms a part of Military
Specification MIL-S-24236B, dated 26 April 1972

SPECIFICATION SHEETS

MIL-S-24236/1 - Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 5 Amperes.

MIL-S-24236/2 - Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 5 Amperes.

MIL-S-24236/11 - Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 1 Ampere.

MIL-S-24236/13 - Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 1 Ampere.

MIL-S-24236/15 - Switch, Thermostatic, (Metallic), Type II, Hermetically Sealed, Overheat Detector, Adjustable, Single Terminal, 3 Amperes.

MIL-S-24236/16 - Switch, Thermostatic, (Metallic), Type II, Hermetically Sealed, Overheat Detector, Adjustable, Dual Terminal, 3 Amperes

MIL-S-24236/19 - Switches, Thermostatic, (Bimetallic), (Subminiature), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 1 Ampere.

MIL-S-24236/20 - Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 2 Amperes and Low Level

MIL-S-24236/24 - Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Double Throw (SPDT), 2 Amperes.

MIL-S-24236/25 - Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), 2 Amperes

MIL-S-24236/26 - Switches, Thermostatic, (Bimetallic), Type I, Hermetically Sealed, Single Pole, Single Throw (SPST), and Single Pole, Double Throw (SPDT), 2 Amperes.

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:27Z
Check the source to verify that this is the current version before use.

Application cross-reference

MIL-S-24236/	Temperature range °F		Vibration	Shock type	Altitude (maximum)	Probe configuration	28 V dc rating amperes	Low level capability
	Low	High						
1	-75	+500	10-500 Hz 10 G 10-2000 Hz 20 G	75 G 6ms 100 G 6ms	80,000 ft.	No	5 amperes	No
2	-75	+500	10-2000 Hz 20 G 10-2000 Hz 30 G	100 G 6ms	70,000 ft.	Yes	2 amperes 5 amperes	No
11	-10	+350	5-2000 Hz 30 G	100 G 6ms	70,000 ft	Yes	1 ampere	No
13	-30	+365	5-2000 Hz 30 G	100 G 6ms	70,000 ft.	No	1 ampere	No
15	+135	+900	10-2000 Hz 10 G	100 G 6ms	70,000 ft.	Yes	3 amperes	No
16	+135	+900	10-2000 Hz 10 G	100 G 6ms	70,000 ft.	Yes	3 amperes	No
19	-30	+400	10-2000 Hz 30 G	100 G 6ms	100,000 ft.	No	1 ampere	No
20	-10	+400	10-2000 Hz 10 G	100 G 6ms	70,000 ft.	No	2 amperes	Yes
24	-65	+400	10-2000 Hz 10 G	100 G 6ms	80,000 ft.	No	2 amperes	No
25	-10	+400	10-2000 Hz 10 G	100 G 6ms	70,000 ft.	Yes	2 amperes	No
26	+100	+600	10-2000 Hz 10 G	100 G 6ms	70,000 ft.	Yes	2 amperes	No

CONCLUDING MATERIAL

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5930-1425)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:27Z
Check the source to verify that this is the current version before use.