MIL-C-23884(OS)
Amendment 1
20 August 1968

MILITARY SPECIFICATION

CONTROL PANEL MARK 264 MOD 1

This amendment forms a part of Military Specification MIL-C-23884(OS) of 3 October 1963 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

By this change basic specification MIL-C-23884(Wep) is changed to MIL-C-23884(OS).

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command"; also delete "BUWEPS" and substitute "NAVORD".

Page 1, paragraph 1.1. Delete and substitute:
"1.1 Scope. This specification establishes requirements for the procurement of Control Panel Mk 264 Mod 1, NAVORD LD 620251, which presets and controls the firing of Torpedoes Mk 44 all Mods and Mk 46 all Mods, launched from Torpedo Tube Mk 32 Mods 5, 6, or 10."

Page 2, under "DRAWINGS": Delete "BUWEPS LD 162136" and substitute "NAVORD LD 620251".

Page 3, paragraph 3.1: In line 4 delete "Mark 46 Mod 0" and substitute "Mk 46 all Mods"; in line 5 delete "Torpedo Tubes Mark 32 Mods 0, 1, and 2" and substitute "Torpedo Tubes Mk 32 Mods 5 or 6".

Page 3, paragraph 3.2.2: Delete "BUWEPS LD 162136" and substitute "NAVORD LD 620251".

Page 3, paragraph 3.2.3: Delete "BUWEPS LD 162136" and substitute "NAVORD LD 620251".

Page 4, paragraph 3.2.4: Delete "BUWEPS LD 162136" and substitute "NAVORD LD 620251".

Page 4, paragraph 3.2.5: Delete "BUWEPS LD 162136" and substitute "NAVORD LD 620251".

FSC 1260

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:10Z
Check the source to verify that this is the current version before use.

Page 4, paragraph 3.2.7: Delete "and the NOT-GO gaging practice shall be as set forth in the aforementioned handbook".

Page 5, paragraphs 3.3.2 and 3.3.2.1. Delete and substitute:

"3.3.2 Standby-firing circuit. The standby-firing circuit is energized only after the torpedo has been preset. This condition being met, the control panel shall be capable of transmitting signals of sufficient voltage and frequency to cause detonation of the torpedo squib and firing of the torpedo itself, in that order.

"3.3.2.1 Time delay. The time lapse between the squib detonating signal and torpedo firing signal shall be not less than 100 milliseconds. The torpedo firing voltage shall be held for 1 second plus or minus 10 milliseconds before dropping out."

Page 5, Table I: Under "Power" column delete "850" and substitute "350".

Page 9, paragraph 4.3.1. Delete and substitute:

"4.3.1 Oscilloscope with a high persistence screen capable of a 1 second and a 100 millisecond sweep time (Tektronix Model 502 or equivalent)."

Page 10, paragraph 4.4.4.4. Delete and substitute:

"4.4.4.4 Time delay and solenoid voltage hold. The time delay and solenoid voltage hold circuitry shall be tested according to NAVWEPS QAP 609 (Time delay test, Solenoid voltage hold test) to determine compliance with the requirements specified in 3.3.2.1."

Page 10, paragraph 4.4.4.7: Delete "limitations established in 3.3.5" and substitute "limitations established in 3.3.4".

Page 19, paragraph 6.1: Delete "Torpedo Tubes Mark 32 Mods 0, 1, and 2" and substitute "Torpedo Tubes Mk 32 Mods 5, 6, or 10".

Page 20. Delete "Notice" paragraph.

Preparing Activity
Navy - OS
Project No. 1260-N013

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:10Z
Check the source to verify that this is the current version before use.