[illegible]
[illegible]

MIL-T-23896F
14 MARCH 1991
SUPERSEDING
MIL-T-23896E
7 July 1985

MILITARY SPECIFICATION

TRUCKS, TIRE SERVICING: GASOLINE AND DIESEL ENGINE DRIVEN, 19,000 AND 24,000 POUNDS GVW, 4 BY 2, and 4 BY 4

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers gasoline and diesel engine driven, four-wheel, two-rear-wheel drive, and four-wheel, four-wheel drive tire servicing trucks, having minimum gross vehicle weight (gvw) of 19,000 and 24,000 pounds (lb).

1.2 Classification. Truck shall be one of the models, classes, and groups, as specified (see 6.2).

Model 4 by 2 - Four-wheel, two-rear-wheel drive.
Model 4 by 4 - Four-wheel, four-wheel drive.

Class A - 19,000 lb gvw.
Class B - 24,000 lb gvw.

Group G - Gasoline engine driven.
Group D - Diesel engine driven.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

4.4.2 (conditioning time and method [illegible] device shall meet the requirements of 3

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

W-B-131 - Battery, Storage, Vehicular, Ignition, Lighting and Starting.
GG-G-91 - Gage, Tire Pressure, Self Contained and Inflator Gage, Pneumatic Tire.
OO-G-669 - Grinder, Pneumatic, Horizontal and Vertical.

MILITARY

MIL-V 62038 - Vehicle, Wheeled, Preparation for Shipment and Storage of.

STANDARDS

MILITARY

MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking & Data Plate Standards.
MS51335-2 - Pintle Assembly, Towing, 18,000 Lbs Capacity, Manual Release.

FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:14Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines: Certification and Test Procedures.
Interstate Motor Carrier Noise Emission Standards.
Motor Vehicle Air Pollution Standards.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

* 2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which is current on the date of the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII, Division I- Pressure Vessels.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

* SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices.

SAE J534 - Lubrication Fittings.
SAE J537 - Storage Batteries (DoD adopted).
SAE J551 - Performance Levels of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
SAE J560 - Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
SAE J588 - Turn Signal Lamps.
SAE J589 - Turn Signal Switch.
SAE J682 - Rear Wheel Splash and Stone Throw Protection (DoD adopted.)
SAE J683 - Tire Chain Clearance - Trucks, Buses, and Combination of Vehicles.
SAE J688 - Truck Ability Prediction Procedure (DoD adopted).
SAE J704 - Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-offs.
SAE J1349 - Engine Power Test Code- Spark Ignition and Diesel.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.
(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, Suite 304, OH 44313.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The truck shall be a four-wheel, two- or four-wheel drive chassis with cab having a gvw rating of not less than 19,000 or 24,000 lb. The truck shall be equipped with a gasoline-engine-driven air compressor unit located as specified herein. A fully hydraulic, articulated boom type crane shall be frame mounted on chassis frame. An open deck type body shall be located at the rear of the chassis frame.

3.2 First production vehicle. The contractor shall furnish a truck for first production vehicle inspection.

3.3 Standard truck, components, and accessories. Except as specified herein, the truck, components, and accessories shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the truck, components, and accessories being furnished. Truck, components, assemblies and accessories to be provided hereunder are standard or optional commercial products for the purpose of this specification. Such items shall be construed as commercial motor vehicle products, and shall comply with all Dot Federal Motor Vehicle Safety Standards and Regulations applicable, on the date of manufacture.

3.3.1 Drain plugs. Drain plugs installed in manual transmission, transfer case, and rear axle shall be of the permanent magnet type.

3.3.2 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded to gvw and operated at an altitude of 10,000 feet above sea level, or in an ambient air temperature of not less than 125 degrees Fahrenheit (^{o}F).

3.3.3 Coolant system and indicators. Coolant system shall include a de-aeration system, a surge tank or a coolant recovery reservoir of not less than 2-quart capacity. A low coolant level or high coolant temperature alarm buzzer and red indicator warning light shall be provided on the cab dash instrument panel.

3.3.4 Towing devices. Not less than two hooks or loops for towing the truck shall be furnished on the front of the truck.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

3.3.5 Trailer towing package. A trailer towing package consisting of a pintle; safety chain attachment devices; a lighting receptacle; and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the type conforming to MS51335-2. The pintle shall be installed on the chassis frame with reinforcements to transfer pintle loads directly to the chassis rails. The rear most portion of the pintle shall be forward, but not more than 4 inches forward, of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the gvw of the truck furnished. The attachment devices shall be capable of accommodating a standard grab hook 2-3/16 inches wide, 47/64 inches thick, 31/64-inch throat with 3/8 inch chain. The lighting receptacle, conforming to SAE J560 with its conductors connected and color coded as specified herein, shall be mounted in a readily accessible location near the pintle.

3.3.6 Splash guards and shields. Rear wheels shall have rigid splash shields ahead of the wheels and splash guards to the rear. Splash and stone throw protection shall be in accordance with SAE J682.

3.3.7 Engine hour meter. An engine hour meter, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to insure continuous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

3.3.8 Air pollution control. Trucks shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, trucks destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.3.9 Sound level. The interior sound level shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

* 3.3.10 Radio Interference suppression. The truck shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the truck chassis.

3.4 Truck weights, ratings, and dimensions.

3.4.1 Curb weight. Curb weight shall include weight of chassis and cab, with all attachments, accessories, equipment, body, full complement of fuel, lubricant, and coolant.

3.4.2 Weight rating. The gvw rating shall consist of curb weight, operator weight (computed at 175 lb), and payload, to provide not less than the specified gvw.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T18:14Z
Check the source to verify that this is the current version before use.

3.4.3 Weight distribution. The distribution of the gvw for the purpose of establishing suspension, axle, and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.4.4 Ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. Minimum gvw shall be 19,000 lb for class A truck and 24,000 lb for class B truck.

3.4.5 Cab-to-axle dimension. The chassis shall have a cab-to-axle dimension of not less than 100 inches for class A truck and not less than 120 for class B truck.

3.4.6 Overall width. The overall width of the vehicle, exclusive of mirrors, lights, reflectors, and tires shall not be over 100 inches.

3.5 Performance. Trucks shall meet the following performance requirements. For 4 by 4 model trucks, performance requirements shall be met with front wheel drive disengaged and with front wheel driving hubs unlocked, except that truck equipped with interaxle compensating devices shall meet performance with front wheel drive engaged.

3.5.1 Speeds and gradeability. High and low speed requirements shall be met with truck loaded to specified gvw.

3.5.1.1 High speed gradeability. The truck shall ascend a continuous grade of 1.5 percent for class A truck and 1.0 percent for class B truck at 50 miles per hour (mph). Gradeability requirement shall be met with the main transmission in direct drive. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.4)

3.5.1.2 Low speed. Low speed shall be calculated with engine operating at not less than 35 percent of recommended governed speed, and shall provide a truck speed of not more than 3 mph.

3.5.1.3 Maximum geared speed. Maximum geared speed, 4 by 2 only, at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Engine governed speed}}{\text{Total geared reduction x tire factor}}$$

3.5.2 Brake performance. Service brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulation, section 393.52. Service brakes shall control and hold the truck, loaded to the rated gvw, headed either up or down the grade, without slipping on a 30 percent grade.

3.6 Chassis components.

3.6.1 Engine. Engine furnished for respective specified vehicle classes shall be the chassis manufacturer's standard, or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

3.6.1.1 Group G (gasoline). Group G vehicles shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speed not more than manufacturer's recommended operating speed. The gasoline engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. The rated net torque output of the engine for 4 by 2 model vehicle shall be not less than 265 pound-feet. For 4 by 4 model vehicles, rated net torque output of the engine shall be not less than 265 pound-feet for class A and not less than 295 pound-feet for class B. Engine net torque ratings and net horsepower (hp) figures used in performance prediction calculations shall be determined in accordance with SAE J1349.

3.6.1.2 Group D (diesel). Group D vehicles shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine with not less than four cylinders. Engine net hp figures used in performance prediction calculations shall be determined in accordance with SAE J1349.

3.6.1.3 Governor. An engine governor shall be furnished, set, and sealed to limit engine to engine manufacturer's maximum recommended operating speed.

3.6.1.4 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. For group D vehicles, control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters, or complete thermostatic control of all coolant flow through the radiator.

3.6.1.5 Silicone rubber hoses. When specified (see 6.2), silicone rubber radiator and heater hoses shall be furnished.

3.6.2 Electrical systems. Electrical systems shall be in accordance with DoT Federal Motor Carrier System Regulations, Sections 393.27 through 393.31 and 393.33.

3.6.2.1 Ignition system. For group G vehicles, 12-volt (V) direct current (dc) ignition system shall be furnished. Alternator of not less than 40 ampere (A) rated capacity and which provides not less than 16A (dc) output at normal engine idle speed shall be furnished.

3.6.2.2 Starting system. For group D vehicles, 12- or 24-volt (dc) starting system, with 12-volt lighting system, and not less than a 60-ampere alternator shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type, controlled from the driver's compartment, with a reservoir of not less than 12 fluid ounces, and shall be inoperative with the engine warm.

3.6.2.3 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.12, 393.19, 393.20 and 393.22 through 393.26. Lights and reflectors shall not be mounted on vertical surface of rub rails unless recessed and fully protected or mounted on vehicle bumpers.

Source: https://assist.dla.mil -- Downloaded: 20260-19T18:14Z
Check the source to verify that this is the current version before use.

3.6.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Vehicle shall be provided with double-faced front signal units and single-faced rear signal units installed in accordance with SAE J588 except that turn signals shall not be mounted on engine compartment hood. Turn signal operating units shall have visible and audible flash indicator.

3.6.2.5 Batteries. Each battery shall be of 12V potential. The total reserve capacity rating and total cold cranking ampere rating of 0°F, both measured in accordance with SAE J537, shall be not less than specified in table I. When specified (see 6.2), the battery shall be of the maintenance free type having the maintenance free characteristics listed in W-B-131.

TABLE I. Batteries.

Vehicle type and engine displacement	Reserve capacity (minutes)	Cold cranking (amperes)
Group G (all)	110	450
Group D (less than 400 cubic inches)	320	1200
Group D (400 cubic inches and over)	320	1200

3.6.3 Fuel system. Fuel system shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.65 and 393.67.

* 3.6.3.1 Air cleaner. Manufacturer's standard dry type air cleaner shall be furnished.

3.6.3.2 Fuel tanks. Fuel tank shall be manufacturer's standard for the model and class of vehicle specified with a total capacity of not less than 40 gallons. When more than one tank is furnished on a group C vehicle, a selector valve connecting either tank to engine fuel intake shall be provided. When more than one tank is furnished on group D vehicles, means shall be provided to assure equalized fuel level in both tanks.

3.6.4 Exhaust system. The exhaust system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.83. If furnished vertical exhaust mufflers capable of being reached easily by personnel entering or leaving either side of the cab shall be provided with a heat shield. Stacked exhaust systems shall be provided with a hinged rain cap.

3.6.4.1 Exhaust system safety shield. The exhaust system or hydraulic system shall be shielded so that, in the event of a hydraulic line rupture or hydraulic fluid leak, the hydraulic fluid will not come into contact with any part of the vehicle exhaust system.

3.6.5 Gear train.

3.6.5.1 Transmission. A manually shifted transmission shall be provided on the vehicle. Input torque capacity of transmission shall be at least equal

Source: https://assist.dla.mil -- Downloaded: 20260-19T18:14Z
Check the source to verify that this is the current version before use.

to the maximum torque delivered by the engine. Transmission shall have these requirements as called out in table II. Transmission shall provide for synchronized shift for at least the three highest forward speeds or for class B vehicle, constant mesh transmission may be provided. Gear ratios in transmission and axles shall be matched to provide a progressive shifting pattern throughout the complete range, and shall provide required vehicle performance (see 3.5.1). Transmission shall be provided with SAE J704 power takeoff openings at right and left sides. Transmission shall provide for maximum ease of shifting in all speeds as specified in table II. A caution plate reading "DO NOT OPERATE AT HIGHWAY SPEED WITH POWER TAKEOFF ENGAGED" shall be installed in a location readily visible to the driver when seated in the driving position.

TABLE II. Transmission requirements - minimum number of forward speeds.

Vehicle model	Vehicle class	Number of forward speeds
4 by 2	A	4
	B	5
4 by 4	A	8
	B	10

3.6.5.1.2 Transfer case. On 4 by 4 model vehicle, a two-speed transfer case shall be provided. Unless the transfer case is equipped with devices which compensate for differential torque and speeds between front and rear axles, transfer case shall provide for driver selection of either two-wheel or four-wheel drive. When furnished, interaxle compensating devices shall provide for positive transfer of power to all driving axles.

3.6.5.2 Drive hubs. When specified for 4 by 4 model truck (see 6.2), manually operated drive hub for disengaging front wheels from power train shall be provided, unless the truck is equipped with interaxle compensating devices between front and rear axles.

3.6.5.3 Clutch. Clutch shall be the largest capacity clutch offered for the model and class vehicle and engine furnished with torque capacity exceeding maximum delivered engine torque.

3.6.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.6.7 Frame. Chassis frame shall be manufacturer's standard for the truck furnished. Frame shall have reinforcement extending at least from the front suspension rear hanger bracket to the rear spring front hanger bracket. Reinforcements shall provide sufficient structural strength in the chassis frame through increased bending moment to at least equal the loads imposed. Chassis frame rails shall not project beyond the rear ends of the body.

3.6.8 Suspension. Truck shall be equipped with suspension system with components having a rated capacity at least equal to the loads imposed on each member, measured at the ground, with truck loaded to rated gvw. When suspension capacity is rated at the spring pads, unsprung pads and unsprung weight shall be

Source: https://assist.dla.mil -- Downloaded: 20261O-19T18:14Z
Check the source to verify that this is the current version before use.

deducted. Truck shall be equipped with hydraulic, double-acting, shock absorbers at the front wheels.

3.6.9 Axles. Axle rating shall be at least equal to the load imposed on each axle, measured at the ground, with truck loaded to rated gvw. Gear ratio shall provide performance specified in 3.5. A single-reduction rear axle shall be furnished.

3.6.9.1 Traction control. The vehicle shall be furnished with a traction control on the rear axle. The traction control shall actuate automatically to insure that power is transmitted to the wheels having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

* 3.6.10 Wheels, rims, and tires. Truck shall be equipped with single front and dual rear wheels. Rim and tire ratings shall conform to TRA specifications, for the type and size of tires furnished. Tire and rim sizes shall be the same for all wheels on each truck.

3.6.10.1 Tires. Tires shall be tube or tubeless type with highway tread on 4 by 2 model truck and for 4 by 4 model truck with nondirectional mud and snow tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with truck loaded to rated gvw.

3.6.10.2 Tire chain clearance. Clearance shall be provided for installation and use of tire chains in accordance with SAE J683. Allowance for spring deflection shall be included.

3.6.10.3 Spare wheel assembly. When specified (see 6.2), a spare wheel or rim shall be mounted on a carrier and installed on a readily accessible location on the truck. Carrier design shall enable removal or mounting of spare wheel assembly using only the tools specified in 3.6.17.1

3.6.10.4 Spare tire. When specified (see 6.2), an inflated spare tire mounted on the spare wheel or rim shall be furnished. The spare tire shall be of the same size, tread design, and load range as the other tires furnished on the truck.

3.6.11 Brakes. Brakes shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.42, 393.45 through 393.52, and as specified herein.

* 3.6.11.1 Service brakes. Truck shall be equipped with power assisted, hydraulic brakes or full air type brakes.

3.6.11.1.1 Split hydraulic brake system. When a power-hydraulic brake system is furnished, the system shall be arranged so as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage-type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. 'Pressure component' means any internal component

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except power assist components.

3.6.11.1.2 Indicator light. Split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating-pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means for testing by the vehicle operator to assure that the light bulb is operable.

3.6.11.1.3 Air brakes. When full air brakes are furnished, the braking system, complete with all necessary components, shall include:

a. Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7-1/4 cubic feet per minute (cfm).
b. Air storage reservoir(s), with not less than 2,000 cubic inches total capacity. Each tank shall be equipped with a drain. Safety and check valves shall be provided between the compressor and the last reservoir tank.
c. Foot control, suspended or treadle type.
d. Air control valves.
e. Air-pressure gage, visible and audible.
f. Low air-pressure warning, visible, and audible.
g. Service brake stop lamp switch.
h. Alcohol aspirator, with a transparent, unbreakable container.
i. Automatic moisture ejector.
j. Automatic slack adjusters.

3.6.11.2 Parking brake. Truck shall be equipped with parking brake.

3.6.12 Cab. Manufacturer shall furnish a standard full-width cab. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, with at least the curb side door equipped with external, key-operated lock. Drip rails shall be furnished above cab doors. Cab shall have upholstered, full-width, adjustable seat and back, or individual adjustable driver's seat, and individual passenger seat. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be furnished and installed. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.16). White upholstery shall not be furnished. Safety grips shall be provided on each side of cab to assist personnel in entering or leaving cab.

3.6.13 Steering. Manufacturer's standard power steering shall be furnished.

3.6.14 Windshield wipers and washers. Truck shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by electric motor(s).

3.6.15 Bumper. Unless the bumper is an integral part of the truck cab, channel type front bumper shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

3.6.16 Rear end protection. Rear end of truck shall be protected in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.86.

3.6.17 Tool stowage. Stowage space of sufficient size to accommodate vehicle jack, hand tools, antiskid chains, and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished inside the cab. When stowage space for these tools is located outside of cab, it shall be waterproof and shall provide for locking with padlock.

3.6.17.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging mounted tire assembly with the spare assembly, and shall include as a minimum a hydraulic jack, jack handle, and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.6.18 Heater and defroster. Hot water heater shall be provided. Heater shall have fresh air intakes. Discharge outlets shall be provided to direct air to floor and to defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver.

3.6.19 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.6.20 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

a. Key-operated ignition switch.
b. Ammeter, charging indicator, or voltmeter.
c. Fuel gage.
d. Oil pressure gage or indicator.
e. Speedometer with recording odometer.
f. Engine temperature gage or indicator.
g. Dual sunvisors.
h. Front door mounted armrest on driver's side.
i. Driver's compartment ventilator other than window.
j. Manufacturer's standard electric horn.
k. Tachometer (for group D truck).

3.6.21 Rearview mirrors. Outside rearview mirrors, each with at least three supporting arms, shall be mounted on each side of the cab. Combination (flat and convex) mirrors shall be furnished. Each combination mirror shall have at least 50 square inches of flat reflective area and a convex surface having at least 20 square inches of reflective area.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T18:14Z
Check the source to verify that this is the currentversion before use.

3.7 Truck body. A heavy-duty service body, open deck type with underslung storage compartment on both sides, shall be furnished. The deck shall be covered with a steel safety tread plate no less than 0.1345-inch (U.S. revised standard gage No. 10) thick. The body shall consist of an air compressor unit, crane section, and rear deck and shall be not less than 14 feet in length for class A truck, and not less than 16 feet in length for class B truck. The rear deck portion of the body shall be not less than 8 feet for class A truck, and not less than 10 feet of clear length for class B truck. The body shall be not less than 93 inches and not more than 96 inches in width. Storage compartments for stowing and securing tools and supplies shall have hinged doors. Hinges shall be continuous rod- or hem-type stainless steel hinge pins or sockets. Latches shall have recessed handles. Doors shall have cylinder type locks, with all locks operable by the same key. Inset steps of foldup type steps shall be provided to aid personnel in mounting the rear deck. Inset step openings in the body skirt and the foldup steps shall be not less than 6 inches wide, 5 inches high, and 5 inches deep. Steps shall be located one each side of the body forward of rear wheels and on each side to the rear of rear wheels.

3.8 Tire well. When specified (see 6.2), the deck shall incorporate a tire well located behind or between the truck rear wheels to position the tire longitudinally with the truck body. Contour radius of the well shall be not less than 42 inches. Width and depth shall be the maximum practicable without interfering with the chassis components. Attachments shall be provided to permit lashing tires, placed in an upright position in the well, to the truck.

3.9 Air compressor unit. An air compressor unit, consisting of a compressor with reciprocating action, gasoline engine, receiver, and all the necessary accessories shall be furnished. Compressor may be provided with air or water cooling. The unit shall be mounted on the forward part of the truck body located immediately behind the truck cab or behind the crane specified in 3.10. Operating personnel shall be protected from moving parts by the use of expanded metal guard. The air compressor shall be capable of satisfactory performance in ambient temperatures ranging from +120°F to -20°F, and at any angle up to 15° from the horizontal. The actual air delivery at continuous operating speed shall be not less than 35 cfm at not less than 175 pound-force per square inch gage (psig). Weight of the compressor unit, without accessories, shall not exceed 1,100 lb. Mounting of the air compressor shall be such as to minimize transfer of vibration.

3.9.1 Compressor engine. A commercial, 4-cycle, gasoline engine, of the size and rating recommended by the compressor manufacturer, shall be furnished. Engine shall be furnished complete, including electric cranking system, variable speed governor, and low oil level or high temperature shutoff device. The truck chassis battery may be utilized to start and run the engine providing the systems are the same voltage and polarity. A battery and charging system shall be furnished when chassis battery is not utilized. The engine shall be mounted in conjunction with the air compressor and air receiver tank. The engine exhaust and manifold shall be mounted or protected to preclude accidental contact by operating personnel.

3.9.2 Pressure control. An adjustable, pressure actuated, mechanical control shall be furnished to stop compression of air and reduce engine speed when pressure reaches 160 ±2 psig. When tank pressure has dropped to 150 ±2 psig, the control shall automatically accelerate the engine and start

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

air compression after engine has attained rated operating speed. A manual control shall be provided to override the idle control during unload periods.

3.9.3 Fuel tank. A fuel tank with a capacity to assure not less than 4 hours of continuous operation shall be furnished.

3.9.4 Air receiver tank. The receiver tank shall be of the horizontal type with sufficient capacity to meet the performance requirements specified herein. The tank shall be constructed in accordance with the ASME Boiler and Pressure Vessel Code, section VIII, Division I equipment shall include, as a minimum, a pressure relief valve, a discharge valve, a drain valve, and a shock proof pressure gage calibrated from 0 psig to not less than 200 psig in increments no greater than 10 psig.

3.9.5 Compressor accessories. The following accessories shall be furnished:

a. Seventy-five feet of 3/8-inch inside diameter (id) air hose with a burst pressure of not less than 700 psig. Hose shall be provided with manufacturer's standard fitting for connecting to the air receiver, and the other end shall be equipped with an inflator gage conforming to GG-G-91, type IV, style 3.
b. Seventy-five feet of 1/2-inch id pneumatic tool hose with quick-disconnect automatic valve type coupler.
c. Two 1/4-inch, quick disconnect, automatic, valve type coupler halves with 1/4-inch male American Standard Taper pipe threads.
d. Two 3/8-inch, quick disconnect, automatic valve type coupler halves with 3/8-inch male American Standard Taper pipe threads.
e. Two 3/8-inch, quick disconnect, automatic valve type coupler halves with 1/2-inch male American Standard Taper pipe threads.
f. One self winding reel to accommodate 3/8-inch hose and also one for the 1/2-inch hose.

3.10 Crane. A one man operated, fully hydraulic, articulated boom type crane shall be mounted on the truck frame forward of or to the rear of the compressor unit specified in 3.9. The boom shall be hydraulically operated and extendable not less than 15 feet. Double-acting hydraulic outriggers, independently controlled and integrally mounted to the crane base, shall be furnished. With the outriggers in the down position, the crane shall be capable of lifting the minimum loads at the radius specified in table III, for the class of truck, without causing the truck to become unstable. Truck shall be deemed unstable when anyone of the truck wheels lifts off the ground. The boom, when fully extended, shall have a vertical reach of 23 feet above ground level and shall rotate through a horizontal arc of not less than 360°. The boom shall fold to a nestable travel height approximately 78 inches above the truck chassis frame. Crane controls shall be provided on each side of the truck, crane, and outrigger controls shall be accessible from ground level. Each outrigger control shall be located on the same side of the truck as the outrigger. Each outrigger landing pad shall be not less than 140 square inches.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T18:14Z
Check the source to verify that this is the currentversion before use.

TABLE III. Lifting capacities.

Radius	12 Feet	15 Feet
Class A	3,000 lb	2,500 lb
Class B	6,000 lb	4,500 lb

3.10.1 Tire grasping device. When specified (see 6.2), a device designed to grasp and hold, while lifting or positioning, up to and including, off highway tires of 3,000 lb weight and 100 inches in diameter. The device shall incorporate the ability to rotate and tilt loaded to maximum capacity.

3.11 Hydraulic system. A hydraulic pump, driven from a power takeoff controlled from inside the truck cab, shall be provided to furnish power for the crane. The pump shall be of the positive displacement type and shall provide a working pressure of not less than 1,800 psig. Controls shall be of the self-centering, fail-safe type, with hydraulic bypass overload valves, and check valve type locking system in boom and outriggers to prevent load dropping due to hydraulic or power failure. Controls shall have fine metering qualities to provide infinitely variable raising, lowering, and rotating motions of the crane boom. Crane hydraulic system shall contain the following minimum safety features:

a. Check valve system in boom and outrigger system to prevent load drop due to hydraulic system failure.
b. Constant flow valve in hydraulic lines to preclude boom damage due to sudden load lowering stops.
c. Cushioning valves in boom rotating hydraulic system to preclude damage due to sudden stops.
d. Pressure relief valve to preclude loading beyond lifting capacity.
e. Signs with 1-inch lettering visible to the operator at both sets of controls: "OUTRIGGERS MUST BE IN PLACE BEFORE LIFT IS MADE".
f. Device(s) to limit vertical creep of payload to not more than one inch per hour.

3.11.1 Hydraulic fluid. Hydraulic fluid conforming to the manufacturer's standard or recommended requirements, shall be provided in the hydraulic system. A photo etched corrosion-resistant caution plate, located near the hydraulic system fill port, stating type of hydraulic fluid required, shall be furnished.

3.12 Jack. When specified (see 6.2), jacking unit of not less than 40-ton lifting capacity shall be furnished. The jacking unit shall consist of a hydraulic jack and an air powered hydraulic pump, with connecting hose lines and operating controls assembled on a one-wheel cart frame. The pump shall operate on any air pressure from 50 to 200 psig, developing the rated capacity at approximately 100 psig. Pump shall be equipped with a safety valve. The jack shall be manually operated by throttle valve and pressure release valve on the pump. Provisions for securing the jacking unit to the truck deck during travel shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

3.13 Mounting provision for tire demounter. When specified (see 6.2), provisions shall be made to secure a portable cone base type tire demounter to the deck. Attachment shall be of quick-connect type.

3.14 Mounting bracket for grinder. When specified (see 6.2), a mounting bracket to convert a portable pneumatic grinder to a bench grinder shall be furnished. Bracket shall be designed to accommodate a grinder conforming to OO-G-669, type I, size 6 inch. Bracket shall be attached to the body to facilitate grinding of tools and buffing tubes, and shall be located on the right rear corner of the body.

3.15 Floodlights. Two sealed-beam floodlights, not less than 4-1/2 inches in diameter, with swivel mounts, shall be mounted, one on each side of rear cab roof or front bulkhead, whichever is higher, for illuminating the work area.

3.16 Painting and marking. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, identification marking, and data plates shall be in accordance with MIL-STD-1223.

3.17 Rustproofing. When specified (see 6.2), truck cab, chassis frame, and chassis underside shall be rustproofed in accordance with FED-STD-297.

3.18 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

* 3.19 Servicing and adjusting. Prior to acceptance of the truck by the Government, the contractor shall service and adjust the truck and air compressor unit for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting and electrical systems.
d. Wheel alinement, (when required).
e. Adjustment of the engines to include tune-up, (when required).
f. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.
g. Cooling system filled to capacity with a clean solution of equal parts by volume of water and antifreeze (ethylene glycol).

The truck shall be conspicuously tagged to identify the lubricants and their temperature range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

3.20 Workmanship.

3.20.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.20.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.20.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.20.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

* 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the test of 4.4. The purpose of the inspection shall be to determine vehicle conformity with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its right under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4, and the packaging inspection of 4.7. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Examination. Each truck shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First production vehicle tests.

4.4.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axle shall be computed using the curb weight, the operator weight at 175 lb, and payload (see 3.4.2 and 3.4.3), to provide the specified gvw. The calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension, axles, and tires furnished are of adequate capacity to meet requirements of 3.6.8, 3.6.9, and 3.6.10.1.

4.4.2 Road test. The truck, loaded with all the equipment specified herein, and with payload to provide not less than rated gvw, shall be driven at speeds up to 50 mph over improved roads for not less than 10 miles. Upon completion of the road test, the crane and compressor shall be operated and the truck with all equipment inspected for malfunction or damage. Compartment doors shall shut tightly without evidence of distortion or racking of the body.

4.4.3 Lift tests. The following shall be performed to determine conformance to 3.10. A load shall be placed on the ground at the side of the truck 15 feet from the centerline of the crane base. The load shall be lifted and lowered on the deck; lifted again and lowered to the ground on the opposite side of the truck. Test shall be repeated with a load placed 12 feet from the centerline of the crane base. The specified test shall be performed at each radius with the weight shown in table IV for each class of truck. All hydraulic

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

controls shall be operated and maximum reach movements performed during these tests. Controls shall be tested not less than five times, and at least three simulated hydraulic failures shall be created in each hydraulic circuit during these tests to verify the reliability of the safety stop devices.

TABLE IV. Lifting capacities.

Radius	12 feet	15 feet
Class A	3,000 lb	2,500 lb
Class B	6,000 lb	4,500 lb

4.4.4 Compressor test. The compressor unit shall be operated for 1 hour with the truck on level ground, to determine conformance to 3.9 through 3.9.5. During the 1-hour period the unit shall be cycled not less than five times to determine conformance to 3.9.2.

4.4.5 Jack tests. When jack is required, a compressor hose shall be connected to the air-hydraulic pump of the jacking unit. A load of not less than 40 tons shall be lifted to the maximum height of the jack, held for not less than 5 minutes, and released, to determine conformance to 3.12. Test shall be repeated at least five times. Repeat five cycles of the above lifting tests with the jack raised to one-half of maximum lift height. Compressor and jacking unit shall then be examined for possible defects.

4.4.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under the contract until corrective action has been taken.

4.4.7 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and may be the last vehicle shipped on the contract. The first production vehicle shall be reconditioned, including replacement of abnormally worn parts and paint touch-up or repainting, prior to delivery to enable it to be accepted as a contract item. The contractor shall maintain the first production vehicle in a serviceable condition for the duration of the contract.

4.5 Production truck tests. The contractor's testing system shall, as a minimum, assure that the truck is capable of meeting performance requirements contained herein. At the point of final acceptance the contractor shall make available to the Government records acceptable to the Government indicating that the servicing and adjusting required by 3.19 has been accomplished.

4.6 Service and parking brake test. Service and parking brakes shall be tested and verified in accordance with DoT Federal Motor Carrier Safety Regulation 393.52.

4.7 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

Source: https://assist.dla.mil -- Downloaded: 20260-19T18:14Z
Check the source to verify that this is the current version before use.

* 5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packed in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved, packed, and marked in accordance with the mobile requirements of MIL-V-62038 with the level of preservation and packaged as specified (see 6.2).

* 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The trucks are intended for use as a maintenance truck equipped for tire servicing for buses, trucks, and applicable off-the-road vehicles.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Model, class, and group of truck required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When silicone rubber hoses are required (see 3.6.1.5).
e. When battery shall be of maintenance free characteristics is required (see 3.6.2.5).
f. When drive hubs for 4 by 4 model truck are required (see 3.6.5.2).
g. When spare wheel or rim and carrier are required (see 3.6.10.3).
h. When spare tire is required (see 3.6.10.4).
i. When spare wheel assembly tools are required (see 3.6.17.1).
j. When tire well is required (see 3.8).
k. When tire grasping device is required (3.10.1).
l. When jack is required (see 3.12).
m. When tire demounter is required (see 3.13).
n. When mounting bracket is required (see 3.14).
o. Identification of appropriate service for treatment, painting, marking, and data plates (3.16).
p. When rustproofing is required (see 3.17).
q. When vehicle shall be preserved, packed, and marked in accordance with MIL-V-62038 with the level of packaging required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of DoD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DoD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 Performance prediction. Completed copies of SAE J688 form and computation for speed requirements for each truck model furnished under contract

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

should be submitted as specified in the contract. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still dry air. The SAE Work Sheet Item 1 should include truck model number, wheel base, engine model number, transmission model number, and truck type. The factors to be used in predicting truck ability (see 3.5.1.1) are established as follows for the corresponding SAE J688 tables:

Table 1 -	Tire Factor. This factor relates to the size of tires furnished by the contract in accordance with this specification.	
Table 2 -	Altitude Factor.	1.00
Table 3 -	Rolling Factor.	1.613
Table 4 -	Area Factor.	0.173
Table 5 -	Velocity Factor.	250.0
Table 6 -	Altitude Factor.	1.00
Table 7 -	Chassis Friction Horsepower. Use applicable power unit gvw (to nearest, higher 1,000 lb) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For gvw and engine speed beyond the range of this table, factors shall be extrapolated.	
Table 8 -	Grade Factor.	0.75
Table 8A -	Correction Factor.	Not required
Table 9 -	Road Factor.	0.0

* 6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

* 6.6 Subject term (key word) listing.

Air compressor unit
Maintenance
Repairs

Custodian:
Navy - YD

Review Activity:
Army - AT

User Activity:
Navy - MC

Preparing Activity:
Navy - YD

(Project 2320-0451)

Source: https://assist.dla.mil -- Downloaded: 20260-19T18:14Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T18:14Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-23896F	2. DOCUMENT DATE (YYMMDD) 91-03-14

3. DOCUMENT TITLE
TRUCKS, TIRE SERVICING: GASOLINE AND DIESEL ENGINE DRIVEN, 19,000 AND 24,000 POUNDS GVW,

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*
4 BY 2, AND 4 BY 4

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (805) 982-5572	(2) AUTOVON 551-5572
ADDRESS (Include Zip Code) mmanding Officer (156) val Construction Battalion Center t Hueneme, CA 93043-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.

...ISTUE. THE CHAMBER PRESSURE WILL BE ATMOSPHERIC. ...OBTAINED TO BRACE TEST ITEMS ...

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:14Z
Check the source to verify that this is the current version before use.