MIL-C-43202A

3 May 1968
SUPERSEDING
MIL-C-43202(GL)
6 March 1964

MILITARY SPECIFICATION

CLEANER SHEETS, OFFSET PRINTING PRESS ROLLER

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for two styles of cleaner sheets for use in cleaning offset printing press rollers.

1.2 Classification.- The cleaner sheets covered by this specification shall be of the following styles, as specified (see 6.2):

Style A - Punched ends
Style B - Slotted ends

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-L-190	-	Linseed Oil, Boiled (For Use in Organic Coatings)
VV-K-211	-	Kerosene
PPP-B-636	-	Box, Fiberboard
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of specifications, standards, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications.- The following publications, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Technical Association of the Pulp and Paper Industry (TAPPI)
Publications:

T 401 m-60 Fiber Analysis of Paper and Fiberboard
T 402 m-49 Conditioning Paper and Paperboard for Testing
T 403 ts-63 Bursting Strength of Paper
T 409 os-61 Machine Direction of Paper
T 410 os-61 Basis Weight of Paper and Paperboard
T 411 os-44 Thickness and Density of Paper

(Copies of TAPPI testing methods may be obtained from the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, N. Y. 10017)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

3. REQUIREMENTS

* 3.1 Material.- The cleaner sheets shall be made from 100 percent bleached chemical wood fibers and additives necessary to meet the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

3.2 Dimensions.- The overall dimensions for style A cleaner sheets shall be 10-3/16 by 15-1/8 inches, style B sheets shall be 10-3/16 by 15-1/2 inches. A tolerance of ± 1/16 inch shall be permitted. The sheets shall be trimmed square and the difference in length between diagonals shall not exceed 1/16 inch.

3.3 Machine direction.- The machine direction of the sheet shall be in the longer dimension.

3.4 Construction.-

3.4.1 Style A.- Style A sheets shall be punched across the shorter dimension at both ends of the sheets. Punches shall be positioned in a manner to permit easy attachment to the standard pin type grips of the cylinder.

3.4.2 Style B.- Style B sheets shall be slotted across the shorter dimensions at both ends of the sheets. The slots shall be positioned in a manner to permit easy attachment to the standard finger type grips of the cylinder.

3.5 Cleanliness.- Cleaner sheets shall be clean and free from dirt and abrasive material.

* 3.6 Physical properties.- The physical properties of cleaner sheets shall comply with the requirements of table 1 when tested as specified in 4.3.2.

TABLE I.- Physical properties.

Basis weight, 19 by 24 inches, 1000 sheets, pounds	137 160	Minimum Maximum
Thickness, inch	0.0140 0.0175	Minimum Maximum
Bursting strength, points, average	46 1/	
Absorption (0.04 ml.), seconds	70	Maximum

1/ No value shall be less than 35 points.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

* 3.7 Instructions for use.- Each envelope (see 5.1.1, 5.1.2 and 5.3.1) shall be printed with the manufacturer's recommended instructions for use. Alternatively, the instructions may be printed on a sheet of paper and inserted in the envelope.

* 3.8 Workmanship.- Slots and punches, as applicable, shall be clean cut to the extent that no portion of the slotted or punched area adheres to the sheet. The cleaner sheet shall be suitable for its intended use.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter. For purposes of sampling, a lot shall consist of all end items of the same style and offered for inspection at one time.

* 4.2.1 Component and material inspection.- In accordance with 4.1, above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

* 4.3 Inspection of the end item.-

4.3.1 Examination of the end item.- The end item shall be examined for the defects in the applicable subparagraphs below at the inspection levels and acceptable quality levels (AQLs) set forth in 4.3.1.5. Random samples shall be drawn from each lot for examination of visual, dimensional, count and preparation for delivery defects. The lot size, for purposes of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of 20 cleaner sheets for the examination in 4.3.1.1, 4.3.1.2 and 4.3.1.3 and in units of shipping containers in the end item inspection lot for examination under 4.3.1.4.

4.3.1.1 Examination of end item for visual defects.- The sample unit for this examination shall be one sheet. Both sides of the sheet shall be examined. Defects of each type shall be scored only once within each sample unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

Examine	Defect
Construction	Not style specified. Not punched or slotted across shorter dimension at both ends of sheet. Punches or slots not positioned to allow easy attachment to the applicable cylinder grips. (This may be determined by fastening the sheet to an offset press or by placing an offset master sheet over the cleaner sheet and checking the punch or slot alignment, as applicable.)
Workmanship	Slots or punches not clean cut. Edges not clean cut, dusty. Sheet not clean. Presence of dirt or abrasive material.

4.3.1.2 Examination of dimensions.- The sample unit for this examination shall be one sheet.

Examine	Defect
Length:	
Style A	More than 15-3/16 or less than 15-1/16 inches.
Style B	More than 15-9/16 or less than 15-7/16 inches.
Width:	
Style A or B	More than 10-1/4 or less than 10-1/8 inches.
Squareness:	
Style A or B	Difference in length between two opposite corner diagonals exceeds 1/16 inch.

4.3.1.3 Examination for average net contents.- The sample unit for this examination shall be one envelope. The lot shall be unacceptable if the average count per envelope for all sample units examined is less than specified or indicated.

* 4.3.1.4 Examination of preparation for delivery.- An examination will be made to determine that markings, materials, workmanship, contents and weight comply with the requirements of section 5 of this specification. The sample unit shall be one shipping container, fully packed, selected just prior to the closing operation. Closed shipping containers fully prepared for delivery shall be examined for closure defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

Examine	Defect
Markings (exterior and interior)	Incorrect; incomplete; illegible, omitted; of improper size, location, sequence, or method of application. Not in accordance with contract requirements.
Materials	Any nonconforming component; component missing, damaged or otherwise defective.
Workmanship	Inadequate application of components such as: incomplete closure of container flaps, loose or inadequate sealing, strapping or stapling.
	Bulged or distorted container.
	Envelope not fabricated as specified, or improperly sealed.
Manufacturer's instructions	Missing, illegible, not printed on envelope or not on a separate sheet of paper in the envelope.
Contents	Number of envelopes per shipping container less than indicated.
Weight	Weight of contents greater than 65 pounds.

4.3.1.5 Inspection levels and acceptable quality levels (AQLs) for examination.- The inspection levels for determining the sample size and the acceptable quality levels (AQLs) expressed in defects per 100 units shall be as follows:

Examination paragraph	Inspection level	AQL
4.3.1.1	I	2.5
4.3.1.2	S-2	2.5
4.3.1.3	S-2	N.A.
4.3.1.4	S-2	4.0

* 4.3.2 Testing of the end item.- The end item shall be conditioned and tested for the characteristics in table II for each lot of material. TAPPI TEST METHOD T400 ts-64 shall not apply for sampling in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

The sample unit for testing shall be eight sheets. The sample size (sample units), determined as shown below, shall be randomly selected throughout the lot. For purposes of sampling for tests, the lot size shall be expressed in the units of 20 sheets each (when required, a suitable conversion to a 20 sheet per unit basis shall be made). The lot shall be unacceptable if there are any failures to meet the requirements applicable to the individual test unit or the lot average, as applicable. All test reports shall contain the individual values utilized in expressing the final result.

Lot size (Unit - 20 sheet units)	Sample size (Sample unit)
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

TABLE II

INSTRUCTIONS FOR TESTING OF THE END ITEM

CHARACTERISTIC	Specification Reference		Requirements Applicable To		Number Determinations Per sample unit	Results Reported As	
	Requirement	Test Method	Sample Unit	Lot Aver		Pass or Fail	Numerically to Nearest
Test conditions	4.3.2	T 402 m-49 1/	-	-			
Stock	3.1	T 401 m-60 1/	-	X	Average of 2 (on composite) 2/	-	percent
Bursting strength	3.6	T 403 ts-63 1/	-	X	10 (5 on each side)	-	point
Basis weight	3.6	T 410 os-61 1/	-	X	1	-	pound
Thickness	3.6	T 411 os-44 1/	-	X	10 (2 on each specimen)	-	0.0001 inch
Absorption	3.6	4.4.1	X	-	Average of 5	-	0.5 second
Machine direction of paper	3.3	T 409 os-61 1/	X	-	1	X	-

1/ Indicates test method of TAPPI.

2/ Composite samples shall consist of representative portions of small pieces selected from all sample units and combined into a single sample.

AMXRE Form 598
8 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

4.4 Tests.-

* 4.4.1 Oil absorption.- This method consists of measuring the time in which a drop of a solution of 70 percent by volume linseed oil conforming to TT-L-190 and 30 percent by volume kerosene conforming to VV-K-211 is absorbed by the specimen.

Apparatus - Pipette or dropper which delivers a 0.04 ml. drop of distilled water at 20° C.

Procedure - Place the test specimen on a non-absorptive horizontal surface. Fill the pipette or dropper with test solution at 73 F ± 3.5 F. Hold the pipette or dropper at an angle of about 30 degrees with the horizontal with the tip nearly in contact with the paper and allow one drop of solution to flow on the specimen. Measure with a stop watch the rate of absorption in seconds from the time the drop touches the surface until the drop is completely absorbed. Complete absorption is indicated by no further reflection of light from the drop when viewed at an angle.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

* 5.1.1 Level A.- Twenty cleaner sheets of one style only and the manufacturer's instruction sheet, when applicable (see 3.7), shall be packaged in a snug-fitting substance 28 brown kraft paper envelope. The envleope shall be securely sealed.

* 5.1.2 Level C.- Cleaner sheets and the manufacturer's instruction sheet, when applicable (see 3.7), shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B or C as specified (see 6.2).

* 5.2.1 Level A.- Cleaner sheets of one style only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-F-320. Each shipping container shall be closed, waterproofed and reinforced with strapping or tape banding in accordance with the appendix of the container specification. The weight of the contents of each shipping container shall not exceed 65 pounds.

* 5.2.2 Level B.- cleaner sheets of one style only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

conforming to style RSC-L, type CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-F-320. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification. The weight of the contents of each shipping container shall not exceed 65 pounds.

* 5.2.2.1 When specified (see 6.2), the shipping container shall be grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the box specification. The shipping container fiberboard material may also be grade V4s of PPP-F-320.

* 5.2.3 Level C.- Cleaner sheets, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery to destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

* 5.3.1 Manufacturer's instructions, when applicable (see 3.7).- Each envleope shall be plainly printed or stamped in black with the manufacturer's instructions for use of the cleaner sheets.

6. NOTES

6.1 Intended use.- Cleaner sheets covered by this specification are used to clean the ink rollers of an offset printing press. The sheet is attached to the grips of the master cylinder and absorbs all ink loosened from the ink rollers by a solvent.

* 6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Style required (see 1.2).
c. Quantity required.
d. Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - SA
Air Force - 84

Preparing activity:

Army - GL

Project No. 3610-0142

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-QS
Natick, Massachusetts 01760

FOLD

"to detach this form, cut along this line"

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.

"to detach this form, cut along this line"

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION
Cleaner Sheets, Offset Printing Press Roller MIL-C-43202A

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 61 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:54Z
Check the source to verify that this is the current version before use.