INCH-POUND

MIL-DTL-43243D
30 May 2002
SUPERSEDING
MIL-S-43243C
30 December 1975

DETAIL SPECIFICATION

SEPARATOR, PARACHUTE REMOVABLE CONNECTOR LINK

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of parachute removable connector link separator.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of the documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS), and the supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this document should be addressed to: Defense Supply Center Richmond, ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:58Z
Check the source to verify that this is the current version before use.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-129	- Standard Practice for Military Marking.
MIL-STD-1916	- DoD Preferred Methods for Acceptance of Product.

(Unless otherwise indicated, copies of the above specifications and standards are available from the Standardization Documents Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Electronic copies of military and federal standards and specifications may be obtained from http://astimage.daps.dla.mil/quicksearch/.)

2.2.2 Other government publications. The following other government publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DEFENSE FEDERAL ACQUISITION REGULATION SUPPLEMENT (DFARS)

DFARS Subpart 209.3	- First Article Testing and Approval.

(Application for copies should be addressed to Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies may be obtained from http://www.acq.osd.mil/dp/dars/dfars.html.)

DRAWINGS

11-1-176	- Separator, Parachute Removable Connector Link; Assembly and Details.
11-1-240	- Spring, Helical, Extension.

(Copies of drawings required by suppliers in connection with a specific procurement function should be obtained from the procuring activity or as directed by the contracting officer.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the separator to be procured under this specification for first article inspection and approval (see 4.2).

3.2 Materials and construction. The materials, construction, and supplementary processes involved in the fabrication of the separator assembly shall conform to the requirements specified or shown on drawings 11-1-176 and 11-1-240.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:58Z
Check the source to verify that this is the current version before use.

3.3 Workmanship. The parachute removable connector link separator, including all components and assemblies, shall be fabricated and finished in a thoroughly workman-like manner. Particular attention shall be given to the following:

a. All areas shall be free of rust or corrosion, dirt, oil, grease or other foreign matter and tool marks or breaks through plating to metal.
b. Free from metal slivers.
c. All welding, silver soldering, and brazing shall be smooth, clean, free of flux, pits, slag, spatter, or porosity, and shall be continuous, adherent, and not burnt through. The joints shall be thoroughly fused.
d. Rivets shall be fully peened with heads in full contact with riveted members. The rivets shall be firmly set and completely fill the hole. Rivet heads shall be full, neatly made, and concentric with rivet holes. Holes for rivets shall be accurately punched or drilled and free of any obstruction.

4. VERIFICATION

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. When a first article inspection is required (see 6.2), the number of units to be provided for inspection shall be specified (see 6.2). Units provided for first article inspection shall be examined for the defects in table I as well as the examinations of paragraph 4.3.1, 4.3.2, and 4.3.3. The presence of any major defect or two or more minor defects listed in table I or any dimension not within specified requirements shall be cause for rejection of the first article.

TABLE I. Classification of defects.

Examine	Defect	Classification	
		Major	Minor
Finish, protective	Any area of rust or corrosion	101	
	Any area with no finish, tool marks, or breaks through plating to metal		201
	Dirt, oil, grease, or other foreign matter		202
Design construction and workmanship	Any sharp edges, burrs, or metal slivers	102	
	Any component missing or damaged	103	
	Any steel component not assembled or joined as specified	104	
	Felt pad not securely cemented to base		203

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:58Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects - Continued.

Examine	Defect	Classification	
		Major	Minor
Design construction and workmanship	Welding incomplete or improper type	105	
	Weld, braze, or silver solder not smooth; any slag or spatter or burn through		204
	Weld, braze, or solder not free of pits or porosity		205
	Weld, braze, or solder area not clean or free of		206
	Lever binds not self-returning	106	
	Rivet not firmly set or adequately peened	107	
	Rivet heads not in full contact with adjacent		207
	Rivet heads not concentric to rivet holes		208
Identification marking	Missing, incomplete, illegible, incorrect, or not applied as specified		209

4.3 Conformance inspection. Conformance inspection shall consist of the visual examination for defects listed in table I as well as the examinations of paragraphs 4.3.1 and 4.3.3. Unless otherwise specified (see 6.2), the manufacturer, in accordance with MIL-STD-1916, shall select the type of sampling plan (attribute, variable, or continuous). The sample size shall be selected in accordance with verification level II of MIL-STD-1916.

4.3.1 Component and material inspection. Components and materials shall be inspected in accordance with all of the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 Process examination. Examination shall be made of the following fabrication processes to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the process and all items processed.

a. Heat treatment of spring (see drawing 11-1-240).
b. Cementing of felt pad (see drawing 11-1-176).

4.3.3 Dimensional examination. Inspection shall be made of the separators to determine compliance with dimensions on drawings specified in 3.2. Any dimension not within specified tolerances shall be classified a defect.

4.4 Rejection and retest. Any separator failing to meet first article or conformance inspection requirements shall be cause for rejection of the lot. Separators that have been rejected may be replaced or repaired and the lot retested using a tightened sample size in accordance with verification level III of MIL-STD 1916. Prior to retesting, the manufacturer shall provide all corrective actions taken to correct the defect(s) in writing to the procuring activity. Units rejected after retest shall not be resubmitted and the lot shall be rejected unless specific approval is authorized by the procuring activity granting additional corrective actions and testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:58Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the inventory control point's packaging activity within the military department or defense agency, or within the military department's system command. Packaging data retrieval is available from the managing military department's or defense agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The separator assembly covered by this specification is used to disengage the leg members of mating parachute removable connector links to facilitate the assembly or disassembly of the applicable parachute components used with the connector links.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1 and 2.2.2).
c. When a first article is required (see 3.1 and 4.2).
d. Number of units required for first article testing (see 4.2).
e. Required type of sampling plan (see 4.3).
f. Packaging requirements (see 5.1).

6.3 Subject term (key word) listing.

felt pad
lever binds

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - GL
Navy - AS

Reviewers:
Army - AV
Navy - MC

Preparing activity:
DLA - GS1

(Project 1670-1005)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-43243D	**2. DOCUMENT DATE** (YYYYMMDD) 20020530

3. DOCUMENT TITLE
SEPARATOR, REMOVABLE CONNECTOR LINK

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN *(if applicable)*	**7. DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME Defense Supply Center Richmond	b. TELEPHONE (*Include Area Code*) Commercial: (804) 279-5019 DSN: 695-5019
c. ADDRESS *(Include Zip Code)* ATTN: DSCR-VBD (C. Hammond) 8000 Jefferson Davis Highway Richmond, VA 23297-5610	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE STANDARDIZATION PROGRAM OFFICE (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, VA 22060-6221 Commercial: (703) 767-6888 DSN: 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:58Z
Check the source to verify that this is the current version before use.