MILITARY SPECIFICATION

STAPLER, BOX

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers electric, pneumatic, and manual powered box staplers.

1.2 Classification. Box stapler machines covered by this specification shall be of the following types, classes, and sizes as specified (see 6.2).

Type I - Floor mounted for stapling bottoms of empty solid and corrugated fiberboard boxes, foot treadle operated.

Class 1 - Electrically powered.

Size A - 9-1/2 inch depth of throat, for 1-1/4 inch wide crown staples.
Size B - 13 inch depth of throat, for 3/8 inch wide crown staples.
Size C - 24 inch depth of throat, for 1-1/4 inch wide crown staples.

Class 2 - Foot powered, 9-1/2 inch depth of throat, for 1/2 inch wide crown staples.

Type II - Portable, for stapling closed, filled corrugated fiberboard boxes.

Class 3 - Pneumatically powered (preformed staples).

Size D - For 1-1/4 inch wide crown staples.
Size E - For 1-3/8 inch wide crown staples.

Class 4 - Manually powered, for 1-1/4 inch wide crown staples.

FSC 3540

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip (Polyolefin)
CC-M-636	-	Motors, Fractional Horsepower (Alternating-Current)
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes, Setup
PPP-C-650	-	Crate, Wood, Open and Covered
PPP-F-320	-	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-P-116	-	Preservation, Methods Of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-C-4109	-	Coupling Assembly, Low Pressure, Air Hose, Quick-Disconnect

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-461	-	Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462	-	Electromagnetic Interference Characteristic, Measurements Of

(Copies of specifications, standards, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following document forms a part of the specification to the extent specified herein. Unless a specific issue is identifiec the issue in effect on date of invitation for bids or request for proposal shal apply.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

Underwriter's Laboratories, Inc. (UL)

Standard No. 73 - Motor-Operated Appliances

(Applications for copies should be addressed to the Underwriter's Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 1285 Walt Whitman Road, Melville, L.I., NY 11749: or 1655 Scott Blvd., Santa Clara, CA 95050.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

U. S. Postal Service

U. S. Postal Service Manual

(Application for copies should be addressed to Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

American Society for Testing and Materials (ASTM)

E 18 - Methods of Test for Rockwell Hardness and Superficial Hardness of Metals

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the item to be procured under this specification for first article inspection and approval (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

* 3.2 Standard product. The staplers delivered under this specification shall be the manufacturer's commercial product, except for any changes necessary to comply with specification requirements. All like items furnished on any one contract, including parts and subassemblies thereof shall be new and interchangeable.

* 3.3 Codes and standards. Type I, class 1, staplers shall comply with the applicable requirements of UL Standard No. 73.

* 3.3.1 Compliance. Prior to approval of the first article, if one is submitted, or prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the type I, class 1, staplers that he proposes to furnish under this specification meet the applicable requirements of UL Standard No. 73.

* 3.3.1.1 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating the type I, class 1, staplers have been tested and conform to UL Standard No. 73.

* 3.4 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial stapler provided that the completed item complies with all provisions of this specification.

* 3.5 Design and construction. Type I and II staplers shall be floor mounted or portable, as applicable (see 1.2). The staplers essentially shall have: (1) provisions for loading and automatically feeding staples; (2) a steel stapling head for accommodating staples of the same crown width, with a drive-chute and driver for guiding and driving staples, and (3) a steel anvil or clincher for clinching the ends of the driven staples in toward the staple crown. The staplers shall staple bottoms of empty fiberboard boxes or closed filled fiberboard boxes as applicable (see 1.2), with preformed staples or partially formed staples. Unless otherwise specified (see 6.2), type I and II staplers shall accommodate staples shown in table I.

TABLE I. Staple sizes (inches) and form

Stapler	Crown width	Wire width & thick	Leg length (outside dimensions)	Form
Type I, class 1				
Size A	1-1/4	0.090 x 0.040	7/16 to 3/4	preformed
Size B	3/8	0.051 x 0.026	5/16 to 1/2	preformed
Size C	1-1/4	0.074 x 0.037	7/16 to 3/4	partially formed
Type I, class 2	1/2	0.103 x 0.020	1/4 to 1/2	preformed
Type II, class 3				
Size D	1-1/4	0.090 x 0.060	1 to 1-1/2	preformed
Size E	1-3/8	0.092 x 0.037	5/8	preformed
Type II, class 4	1-1/4	0.090 x 0.040	7/16 to 3/4	preformed

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the current version before use.

3.5.1 Type I. Type I, class 1 and 2 staplers shall be motor or foot powered, as applicable (see 1.2). The staplers shall have a floor mounted frame and foot treadle. The frame shall consist of a front post with an anvil or clincher that shall be adjustable for alignment with the stapling head and a rear post that shall accommodate a stapling head and linkage mechanism for the operation of the head. The front post in addition to having an anvil or clincher shall be either a rigid or tilt post. The tilt post shall be capable of tilting forward to facilitate insertion and removal of the stapled box and shall automatically straighten to the vertical position by the action of a foot treadle as the foot treadle is being depressed to perform the stapling operation. Unless otherwise specified (see 6.2), type I machine shall have a tilt post.

3.5.1.1 Throat depth. Unless otherwise specified (see 6.2), type I staplers shall have throat depths as specified (see 1.2). Throat depth shall be measured from the anvil or clincher, with the front post in the vertical position to the inside surface of the rear post, within a tolerance of plus or minus 1 inch.

3.5.1.2 Height. Type I staplers shall have a minimum working height of 36 inches from the floor to the anvil or clincher, with the front post in the vertical position.

* 3.5.1.3 Staple capacity. Type I staplers except type I, class 1, size C shall have a minimum magazine capacity for 200 preformed staples. Type I, class 1, size C stapler shall accommodate a coil containing a minimum of 4000 partially formed staples.

3.5.1.4 Motor. The motor of type I, class 1 stapler shall conform to CC-M-636. The motor shall be started by a switch activated by the foot treadle. The switch on the stapler with tilt post shall be activated after the straightening operation of the post is accomplished.

3.5.1.5 Stapling speed. Stapling speed of type I staplers shall be as follows:

(1) Type I, class 1 staplers shall apply one staple at a time by the intermittent depressing of the foot treadle or apply staples continuously at a maximum rate of 186 staples per minute by the constant depressing of the foot treadle.

(2) Type I, class 2 stapler shall apply one staple at a time by the intermittent depressing of the foot treadle.

* 3.5.2 Type II. Type II staplers shall have a body with a carrying handle for portability. The body shall have a stapling head with a magazine with a minimum staple capacity for 100 staples. The stapling head shall include retractable anvils or clinchers, one for each leg of the staple with adjustable means to provide complete or partial penetration of the box material as specified herein. The anvils or clinchers shall be interchangeable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:53Z
Check the source to verify that this is the current version before use.

3.5.2.1 Class 3. Type II, class 3 staplers shall have a pneumatic drive. The stapler shall have a handle for portability, holding and guiding the stapler during operation; a 1/4-inch size quick-disconnect fitting conforming to type II, style 1 of MIL-C-4109 for coupling with an air power source; and a hand switch for control of stapler operation. The stapler shall apply one staple at a time with each activation of the switch.

* 3.5.2.2 Class 4. Type II, class 4 stapler shall have one handle or handgrip for portability, holding and steadying the stapler during stapling and a second handle or lever for manual application of the staples. The stapler shall apply one staple at a time with each actuation of the handle.

3.5.3 Electrical characteristics. Unless otherwise specified (see 6.2), the electric motor of type I, class 1 stapler shall operate from a 120 volt, 60 hertz, single phase, alternating current source.

* 3.5.4 Hardness. Anvils or clinchers, drive-chutes, drivers and magazine parts, as applicable, subject to rubbing and wear shall be heat treated to a Rockwell "C" hardness of 37 to 57 or case hardened to Rockwell "30N" Superficial hardness of 57 to 69, when tested in 4.6.1.

3.6 Performance. Type I and II staplers shall be capable of being readily loaded with applicable staples and shall automatically feed staples and tightly staple fiberboard with no jamming of the stapler when tested in 4.6.2, as follows:

(1) Type 1 staplers shall staple fiberboard at the speeds specified in 3.5.1.5.

(2) Type II staplers shall staple fiberboard with partial and complete penetration of the staple, and no tearing of the fiberboard.

3.7 Interchangeability. All parts of box staples of any one contract having the same manufacturer's part number shall be functionally and physically interchangeable for the same type, class and size of stapler.

3.8 Electromagnetic compatibility. When specified (see 6.2), type I, class 1 staplers shall be designed and equipped for electromagnetic compatibility in accordance with class 11 B of MIL-STD-461 (see 4.6.3).

* 3.9 Marking for identification. A corrosion-resisting metal or metallic nameplate, permanently and legibly marked in accordance with the manufacturer's standard practice shall be attached to the stapler.

* 3.10 Finish. The stapler shall be finished in accordance with the manufacturer's commercial practice.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

3.11 Workmanship. The stapler shall be properly assembled, in alignment, and free of burrs, slivers, and rust or corrosion. Parts shall not be loose, bent, dented, fractured or broken. Adjustable parts shall be capable of being adjusted.

* 3.11.1 Welding. Welding shall be sound, adherent, and free from cracks, pits, and slag.

* 3.11.2 Finish coat. Finish coat shall have no visual evidence of peeling, blistering, sags, tackiness and free from embedded foreign matter and uncoated areas.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are as follows:

1. First article inspection (qualification inspection) (see 4.3).
2. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required, the box stapler shall be examined for defects as specified in 4.4.2.1, dimensions as specified in 4.4.2.2 and tested as specified in 4.6.1, 4.6.2, and 4.6.3, when applicable. Presence of any visual defect, dimensional defect, or failure of any test shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Inspection of components and materials. In accordance with 4.1, components and materials shall be tested and inspected in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.4.2 End item inspection. The inspection lot shall consist of all box staplers of the same type, class and size offered for inspection at one time.

4.4.2.1 Visual examination. The box stapler shall be examined for defects in table II. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not in accordance with manufacturer's standard practice		X
Workmanship, general	Stapler not properly assembled or in alignment	X	
	Not free of burrs, slivers, rust or corrosion	X	
	Parts loose		X
	Parts bent, dented, fractured or broken	X	
	Adjustable parts not capable of being adjusted	X	
Welding	Not sound, adherent, free of cracks, pits or slag	X	
Finish coat	Peeling, blistered, with sags, tacky and not free from embedded foreign matter and uncoated areas		X
Marking, identification	Missing, incomplete or not legible	X	

4.4.2.2 Dimensional examination. The box stapler shall be examined for compliance with dimensions specified. Any nonconforming dimension shall be classified a defect. The inspection level shall be S-2 and the AQL shall be 4.0 expressed in terms of defects per hundred units.

* 4.4.2.3 End item testing. When a first article is not required, the first produced box stapler shall be tested as specified in 4.6.1, 4.6.2, as applicable, and 4.6.3, when applicable. Failure to pass any test shall be cause for rejection of the lot. Each stapler shall be tested as specified in 4.6.2, as applicable. Failure to pass the test shall be cause for rejection of the item.

4.4.3 Examination of preparation for delivery. An examination shall be made to determine that preservation, packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored as indicated in table III. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 and the AQL shall be 6.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

TABLE III. Examination of preparation for delivery

Examination	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Preservation	Preservative improperly applied or missing
Materials	Component missing, damaged, or otherwise defective
Workmanship	Inadequate application of components such as bulging or distortion of containers
Weight	Exceeds specified weight

4.4.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-C-650 or PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the applicable specification.

* 4.5 Certificate examination. Certificate of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.6 Tests.

* 4.6.1 Hardness test. Stapler parts shall be tested for hardness in accordance with ASTM Standard E-18, based on the average hardness of 3 determinations to determine compliance with 3.5.4. Any nonconformance shall constitute failure of this test.

* 4.6.2 Performance test. The stapler shall be loaded with applicable staples (see table I) and shall staple test specimens consisting of 2 pieces of the same fiberboard. Fiberboards for the test specimens shall be per PPP-F-320, as follows:

(a) V2s for solid-walled fiberboard.
(b) V3c for single-walled fiberboard.
(c) Type CF, class domestic, DW, grade 275 "BR" flute for double-walled fiberboard.
(d) Type CF, variety TW, grade 1100 for triple-walled fiberboard.

Test specimens 4-inches wide by 8-inches long using a minimum of 15 staples per specimen shall be stapled by staplers to determine compliance with 3.6, as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

(1) Type I, class 1, size A stapler shall staple first two pieces of solid fiberboard using staples with 7/16 inch legs and second, two pieces of double-walled fiberboard using staples with 3/4 inch legs.

(2) Type I, class 1, size B stapler shall staple first two pieces of solid fiberboard using staples with 5/16 inch legs and second, two pieces of single-walled fiberboard using staples with 1/2 inch legs.

(3) Type I, class 1, size C stapler shall staple first two pieces of solid fiberboard using staples with 7/16 inch legs and second, two pieces of double-walled fiberboard using staples with 3/4 inch legs.

(4) Type I, class 2 stapler shall staple first two pieces of solid-wall fiberboard using staples with 1/4 inch legs and second, two pieces of single-walled fiberboard using 1/2 inch legs.

(5) Type II, class 3, size D staples shall staple two pieces of triple-walled fiberboard first using staples with 1 inch legs for partial penetration to within the bottom flute of the specimen and second, using staples with 1-1/2 inch legs for complete penetration of the two pieces of triple-walled fiberboard.

(6) Type II, class 3, size E shall staple first two pieces of solid fiberboard using staples with 5/8 inch legs for complete penetration of the two pieces and second, two pieces of double-walled fiberboard for partial penetration to within the bottom flute of the specimen.

(7) Type II, class 4 shall staple first two pieces of solid-walled fiberboard using staples with 7/16 inch legs for complete penetration of the two pieces and second, two pieces of double-walled fiberboard using staples with 3/4 inch legs for partial penetration to within the bottom flute of the specimen. Any nonconformance with the requirements of 3.6 shall constitute failure of this test.

4.6.3 Electromagnetic compatibility test. When electromagnetic compatibility is required, the first article shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The supplier shall furnish the contracting officer, written certification that the Interference Control Plan, the EMI/EMC (Electromagnetic Interference/Electromagnetic Compatibility) Test Plan, the Electromagnetic Compatibility Test Report and the requirements meet MIL-STD-461.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Preservation. All exposed, uncoated, ferrous metal surfaces of each stapler shall be cleaned process C-1 of MIL-P-116 and thoroughly dried. Surfaces, cleaned and dried as specified, shall then be coated with type P-7 preservative of MIL-P-116. Surfaces from which preservative might be removed by contact with packaging and packing materials shall be covered, wrapped, or bagged with greaseproof barrier material conforming to type I or II, grade A of MIL-B-121. Barrier material shall be secured with twine made of juts, sisal, manila, or cotton, or with tape conforming to type III, grade A of PPP-T-45 or heat sealed when heat sealable barrier material is used. Each stapler shall be lubricated to capacity with the manufacturer's recommended lubricant containing a rust inhibitor.

5.1.1.2 Packaging.

5.1.1.2.1 Type I, class 1 and 2. Each stapler, preserved as specified in 5.1.1.1, shall have movable parts, such as the foot pedal, anvil, et cetera, secured and immobilized with cotton tape or twine.

5.1.1.2.2 Type II, class 3 and 4. Unless otherwise specified herein each stapler, preserved as specified in 5.1.1.1, shall be packaged in a snug-fitting fiberboard box conforming to class weather resistant of PPP-B-636. When specified (see 6.2), each stapler, preserved as specified in 5.1.1.1, shall be packaged in a snug-fitting box conforming to variety 1, style III or VIII, type G, class i of PPP-B-566; type 1 variety 1, class A, style 4 of PPP-B-676; or type CF (variety SW) or type SF, class domestic, grade 125 of PPP-B-636, as applicable. The stapler shall be immobolized within the box with scored or die-cut, fiberboard inserts of the same material as the box. The weight limitation of each box specification shall apply. Closure shall be in accordance with the appendix of the applicable box specification.

* 5.1.2 Level C (commercial packaging). Staplers shall be packaged to afford adequate protection against corrosion and physical damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Type I, class 1 and 2 stapler. Each stapler, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to style A, type IV of PPP-C-650 or overseas type style A or B of PPP-B-601. Each PPP-B-601 container shall be provided with skids. The contents shall be anchored and waterproofed with a full-height shroud in accordance with the appendix of PPP-C-650. Each shipping container shall be closed and strapped in accordance with the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 202640-21T20:53Z
Check the source to verify that this is the currentversion before use.

5.2.1.2 Type II, class 3 and 4 stapler. Staplers of one class and size only, preserved and packaged as specified in 5.1, shall be packed in a snug fitting shipping container conforming to style RSC, V2s of PPP-B-636 or style A or B of PPP-B-601. The weight of contents of each fiberboard container shall not exceed 65 pounds. Each fiberboard shipping container shall be closed, waterproofed by means of tape, and each shipping container shall be reinforced with strapping or tape banding in accordance with the appendix of the applicable container specification.

5.2.2 Level B.

5.2.2.1 Type I, class 1 and 2 stapler. Each stapler, preserved and packaged as specified in 5.1, shall be packed as specified in 5.2.1.1, except that the shroud shall be made from 0.003 inch thick polyethylene film conforming to type I of L-P-378.

5.2.2.2 Type II, class 3 and 4 stapler. Staplers of one class only, preserved and packaged as specified in 5.1, shall be packed in a snug fitting shipping container conforming to type SF or CF (variety SW) class domestic, style RSC, grade 275 of PPP-B-636. The weight of contents of each shipping container shall not exceed 65 pounds. Box closures shall be in accordance with method II of the appendix of the box specification.

5.2.2.2.1 When specified (see 6.2) the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the box specification.

* 5.2.3 Level C (commercial packing). Staplers of one type and class only, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with U. S. Postal Service, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The staplers covered by this specification are intended for stapling bottoms of empty or closing of filled corrugated or solid fiberboard cartons.

6.1.1 Type II. Type II staplers have been found satisfactory for closing cartons to be packaged within a shipping container.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:53Z
Check the source to verify that this is the currentversion before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type, class, and when applicable, size required (see 1.2).
(c) When first article is not required (see 3.1).
(d) When staples required for type I and II staplers are other than specified (see 3.5).
(e) When tilt post for type I is not required (see 3.5.1).
(f) When throat depth required for type I is other than specified (see 3.5.1.1).
(g) Electrical requirements, if other than specified (see 3.5.3).
(h) When electromagnetic compatibility is required (see 3.8).
(i) Selection of applicable levels of preservation and packaging and packing (see 5.1 and 5.2).
(j) When domestic grade boxes are required for level A packaging (see 5.1.1.2.2).
(k) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.2.1).

6.2.1 Contract Data Requirements. Any requirements for equipment manuals for the item covered by this specification should be included in DD Form 1423 Contract Data Requirements List and cited in the contract.

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 The margins of this specification have been marked with an asterisk(*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 84

Preparing activity:

Army - GL

Project No. 3540-0092

Review activities:

Army - MD, SM

Source: https://assist.dla.mil -- Downloaded: 202640-21T20:53Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-S-43194C STAPLER, BOX

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:53Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

STSNLT-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:53Z
Check the source to verify that this is the current version before use.