INCH-POUND
MIL-DTL-22442/21C(AS)
5 January 1998
SUPERSEDING
MIL-C-22442/21B(AS)
2 September 1988

DETAIL SPECIFICATION SHEET

CABLE ASSEMBLY, AIRCRAFT AUDIO, CX-12974/AR

This specification sheet is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-22442 listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



FIGURE 1. Cable Assembly CX-12974/AR P/N M22442/21-1.



FIGURE 2. Cable Assembly CX-12974/AR P/N M22442/21-1 Schematic Diagram.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:27Z
Check the source to verify that this is the current version before use.

APPLICABLE DOCUMENTS:

MIL-J-641/22	-	Jacks, Telephone, U-385/U
MS3116	-	Connector, Plug, Electric, Series 1, Solder Type, Straight, Bayonet Coupling

REQUIREMENTS:

l. The cable shall be in accordance with MIL-DTL-22442/3.

2. Connector "X" shall be MS3ll6Fl0-6P or functional equivalent. Black tubing may be used as a bushing under strain relief.

3. The weight of the cable assembly shall not be greater than l0 ounces.

4. The stay cord shall be firmly attached to the connectors.

5. The DC resistance shall be less than 2 ohms between the following contacts.

(a) Contact B of "X" and contact 5 of P/N M64l/22-0l (U-385/U).

(b) Contact A of "X" and contact 4 of P/N M64l/22-0l (U-385/U).

(c) Contact C of "X" and contact 3 of P/N M641/22-0l (U-385/U).

(d) Contact E of "X" and contact 2 of P/N M641/22-0l (U-385/U).

(e) Contact D of "X" and contact l of P/N M64l/22-0l (U-385/U).

6. The cable assembly shall be tested in accordance with the tests listed in Table I.

NOTES:

l. All dimensions are in inches.

2. Tolerances are metal parts ±.005, molded sections ±.05 inches unless otherwise specified.

3. MIL-C-8l863 is superseded by MIL-DTL-22442/2l.

Preparing activity:
Navy - AS
(Project No. 5995-0128-28)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:27Z
Check the source to verify that this is the current version before use.

TABLE I. Tests

Inspection	Requirement Paragraph	Test Paragraph	Group I Qualification Tests	Group II Quality Conformance Test 100%	Group III Sample Testing Per 4.4.1
GROUP A (ALL SAMPLE UNITS) 1/					
Visual & Mechanical Inspection	3.1 & 3.4	4.5.2	X	X	
Soldering	3.4.18	4.5.2.1	X	X	
Continuity	3.5.1	4.5.3	X	X	
GROUP B					
Dielectric Withstanding Voltage	3.5.2	4.5.4	X		X
Gauging 1/	3.5.3	4.5.5	X		X
Pull and Twist Test 1/	3.5.4	4.5.6	X		X
GROUP C					
Durability 1/	3.5.7	4.5.9	X		X
Ozone Resistance 1/	3.5.8	4.5.10	X		X
Jacket Elongation	3.5.9	4.5.11	X		X
GROUP D 1/					
Salt Fog	3.6.2	4.6.2	X		
Humidity	3.6.5	4.6.5	X		
Thermal Shock	3.6.5	4.6.6	X		

1/ Minimum tests for QPL retention (see paragraph 4.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:27Z
Check the source to verify that this is the current version before use.