NOTICE OF CANCELLATION

INCH-POUND
MIL-E-23765/2E(SH)
NOTICE 1
16 August 2024

MILITARY SPECIFICATION

ELECTRODES AND RODS – WELDING, BARE, SOLID, OR ALLOY CORED; AND FLUXES, LOW ALLOY STEEL

MIL-E-23765/2E(SH), dated 22 April 1994, is hereby canceled. MIL-DTL-23765/1F(SH), "Electrodes and Rods - Welding, Bare, Solid and Alloy-Cored, Ordinary Strength, and Low Alloy Steel," and T9074-BC-GIB-010/0200, "Filler, Materials for Critical Applications: Requirements for Flux-Cored Welding Electrodes, Bare Welding Electrodes and Fluxes, and Covered Welding Electrodes for Low-Alloy Steel Applications," supersede MIL-E-23765/2E(SH).

CAUTION: The supersession information is valid as of the date of this notice and may be superseded by subsequent revisions of the superseding document.

(Copies of MIL-DTL-23765/1F are available from https://quicksearch.dla.mil/.)

(Copies of T9074-BC-GIB-010/0200 are available online via Model Based Product Support (MBPS) at https://mbps.navseaplm.navy.mil/Windchill/app/. To gain access to MBPS, obtain an account with National Help Desk Service Management (NHDSM) at https://nhdsm.navair.navy.mil (a valid CAC is required to access this website) and submit a SAAR-N Request. Refer questions, inquiries, or problems to (888) 292-5919. This document is available for ordering (hard copy) via the Naval Logistics Library (NLL) at https://nll.navsup.navy.mil. For questions regarding the NLL, contact the NLL Customer Service at nllhelpdesk@navy.mil, (866) 817-3130, or (215) 697-2626/DSN 442-2626.)

CONCLUDING MATERIAL

Custodian:
Navy – SH

Review activity:
DLA – GS

Preparing activity:
Navy – SH
(Project 3439-2022-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:49Z
Check the source to verify that this is the current version before use.