MILITARY SPECIFICATION

TEST HARNESS, RADAR SET AN/APM-153(*)

This specification has been approved by the
Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 Scope - The test equipment covered by this specification shall be for shop use and shall support, position, and electrically provide for interconnection of Radar Set AN/A PN-59 or AN/A PN-59B components, in all system configurations, for bench checking purposes.

1.2 Classification - The Test Harness, Radar Set AN/A PM-153(*) shall consist of the following items:

Item	Type Designation	Appl. Para.
Workbench Mounted Components		3.4.1
Antenna Holding Fixture		3.4.2
Cables, Test Harness	W-1 thru W-13 of AN/A PM-153	3.4.3
Cables, Interconnecting and Test	W-14 thru W-20 of AN/A PM-153	3.4.4
Cables, Interconnecting and Test	TC-1 thru TC-14	3.4.4
Cable, Interconnecting and Test	CX-3302/U	3.4.4
Tools, Aligning		3.4.5
Covers		3.4.5

2. APPLICABLE DOCUMENTS

2.1 General - The following documents of the issue in effect on the date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-T-5422	Testing, Environmental, Aircraft Electronic Equipment
MIL-I-6181	Interference Control Requirements, Aircraft Equipment
MIL-H-15362	Harnesses; Test Bench, Avionic Equipment, General Specification for
MIL-E-17555	Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

MIL-T-18303	Test Procedures, Preproduction and Inspection, For Aircraft Electronic Equipment, Format for
MIL-N-18307	Nomenclature and Nameplates for Aeronautical Electronic and Associated Equipment
MIL-T-21200	Test Equipment for Use with Electronic and Fire Control Systems, General Specification for

STANDARDS

Military

MIL-STD-242	Electronic Equipment Parts
MS21993	Cable Assemblies, Power Electrical

2.2 Availability of Documents

(1) When requesting specifications, standards, drawings, and publications refer to both title and number. Copies of this specification and applicable specifications required by contractors in connection with specific procurement functions may be obtained upon application to the Commanding Officer, Naval Supply Depot, Code DCS, 5801 Tabor Avenue, Philadelphia 20, Pennsylvania.

3. REQUIREMENTS

3.1 Parts and Materials - In the selection of parts and materials, fulfillment of major design objectives shall be the prime consideration. Parts and materials requirements shall conform to Specification MIL-T-21200. Parts selected from specifications called out in Specification MIL-T-121200 shall be limited to those values, styles, tolerances, etc. , set forth in MIL-STD-242.

3.1.1 Nonstandard Parts and Material Approval - Approval for the use of nonstandard parts and materials shall be obtained as outlined in Specification MIL-T-21200.

3.2 Design and Construction - The equipment shall conform with all the applicable requirements of Specifications MIL-T-21200 and MIL-H-15362 for design. construction and workmanship except as otherwise specified herein.

3.2.1 Total Weight - The total weight of the equipment, including cables, shall be a minimum consistent with good design and shall not exceed 500 pounds.

3.2.2 cables and Connectors - The equipment shall provide for the use of cables and connectors in accordance with Specification MIL-T-21200.

3.2.2.1 Cable Assemblies, Power Electrical - Applicable input power cable and connections shall conform to MS 21993.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

3.2.3 Interchangeability - The equipment shall meet the interchangeability requirements as defined in Specification MIL-T-21200.

3.2.4 Interference Control - The generation of radio interference by the equipment and the vulnerability of the equipment to radio interference shall be controlled within the limits of Specification MIL-I-6181.

3.2.5 Nomenclature and Nameplates - Nomenclature assignment and nameplate approval for equipment identification shall be in accordance with Specification MIL-N-18307.

3.2.6 Standard Conditions - The following conditions shall be used to establish normal performance characteristics under standard conditions and for making laboratory bench tests.

Temperature	Room ambient (30° ±10° C)
Altitude	Normal ground
Vibration	None
Humidity	Room ambient

3.2.7 Service Conditions - The test equipment shall operate satisfactorily under any of the environmental service conditions or reasonable combination of these conditions as specified in Specification MIL-T-21200 for Class 3 equipment, except as modified herein.

3.2.8 Primary Input Power Requirements - This equipment has no appreciable input power requirements of its own, but shall serve to connect the primary input power to the equipment under test.

3.28.1 Voltage Protection - The equipment shall not be damaged when exposed to transient voltages as defined in MIL-STD-704, and shall automatically resume normal operation when the voltage returns within limits of normal operation.

3.3 Performance - The performance of the equipment shall be as set forth below. Unless otherwise specified, these requirements shall apply under both standard and extreme service conditions, When reduced performance requirements for service conditions are acceptable, such variation will be specified.

3.4 Detail Requirements

3.4.1 Workbench Mounted Components - The Test Harness Workbench Components shall meet the following requirements:

3.4.1.1 Function - The Test Harness Workbench Components consist of a terminal panel, brackets and fixtures for mounting the radar system components to be serviced or tested. In addition, manually operated synchros provide roll, pitch and compass excitation voltages to simulate the functions of Stabilization Data Generator CN-221/APN-59, for Antenna AS-653/APN-59.

3.4.1.2 Form Factor - The Test Harness Workbench components are mounted on a standard Navy Type 57A-53 Workbench which is not supplied as a part of this equipment,

3.4.1.3 Contents - The Test Harness Workbench components shall consist of the following assembles and fixtures.

3.4.1.3.1 Terminal Panel - The Terminal Panel consists of eight (8) rows of terminal

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

boards for terminating and providing test points for the test bench harness and a Top Panel Assembly.

3.4.1.3.2 Top Panel Assembly - The Top Panel Assembly consists of the following items attached thereto.

CONTROL	QUANTITY	FUNCTION
Circuit Breaker	1	To provide 25 to 29 volts DC and to open circuit if more than 10 amperes is drawn.
Circuit Breaker	1	To provide 110 to 120 volts, 380 to 420 cps, single phase AC and to open circuit if more than 10 amps is drawn.
Circuit Breaker	1	To provide 110 to 120 volts, 380 to 1000 cps, single phase AC and to open circuit if more than 20 amps is drawn.
Compass Synchro B-23	1	To provide the compass excitation voltage for "Antenna AS-653 /A PN-59,"
Pitch Synchro B-22	1	To provide the pitch excitation voltage of Antenna AS-653 /A PN-59.
Roll Synchro B-21	1	To provide the roll excitation voltage for Antenna AS-653 /APN-59.
Receptacle	1	For cable W-8 (MS3106A-20-29SW Mating)
Test Jacks	10	The jacks arranged in five (5) rows are labeled as follows: (1) ACIF, (2) ACCF, (3) +27. 5V, (4) GND, (5) -255V, (6) -105V, (7) +150V, (8) +250V, (9) +300V and (10) +300V unreg.

3.4.1.3.3 Mounting Bracket - The Mounting Bracket houses the following units of the AN/A PN-59 under test:

(1) Azimuth and Range Indication IP-239/APN-59
(2) Radar Set Control C-1242/APN-59
(3) Synchronizer Control C-2302/APN-59

3.4.1.3.4 Convenience Receptacle Assembly - Consists of two duplex outlets for 115 volt, AC-60 cps power, two fuse holder assemblies (one for spare fuse) to protect the convenience receptacles and one receptacle for 28 volt-DC power to the workbench and one receptacle for 115 volt, 400 cps single phase power.

3.4.1.3.5 Holding Fixture - The Holding Fixture is for accommodating the RT-289/APN-59 and Vaneaxial Fan HD-150/APN-50 under test or service on the Test Bench.

3.4.1.3.6 Mounting Bases - The following mounting bases are secured under the workbench on the left side shelves as follows:

(1) Top Shelf - Power Supply Mount for PP-1073/APN-59, Stabilization Data Generator CN-221/APN- 59, Aux Azimuth & Range Indicator IP-268/APN-59

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

(2) Bottom Shelf - Electronic Control Amplifier AM-853/APN-59, Electrical Synchronizer SN-198/APN-59

3.4.2 Antenna Holding Fixture - The Antenna Holding Fixture shall meet the following requirements

3.4.2.1 Function - The Antenna Holding Fixture shall hold the Antenna Assembly AS-653/APN-59 during test and repair,

3.4.2.2 Form Factor - The Antenna Holding Fixture shall have maximum dimensions of 54 inches wide by 4 5 inches high by 45 inches long.

3.4.2, 3 Contents - The unit shall be mounted on casters and shall have alignment leveling screws on all four corners. The Antenna Mounting yoke shall remounted in the top of the Holding Fixture by a swivel bracket, with a drag adjustment on one side and a handwheel for adjusting the tilt angle of the antenna under test and a calibrated dial and indicator to show the tilt angle in degrees.

3.4.3 Test Harness Cables W-l Thru W-13, AN/APM-153 - The Test Harness Cables shall meet the following requirements:

3.4.3.1 Function - The Test Harness Cables form the interconnections to the test equipment, test servos and power connections to the AN/APN-59power supplies.

3.4.3.2 Form Factor and Contents - The following table lists the cables and them contents.

Cable Designation	From Terminal Panel to	Type Connector	Length in Inches
W-l	J-101	MS3106A-36-7S	84
	J-2501	MS3106A-14S-5S	60
	J-2501	MS3106A-14S-5S	60
W-2	J-401	AN3106A-28-15SX	180
W-3	J-402	MS3106A-24-28S	180
W-4	J-403	MS3106A-18-1S	180
W-5	J- 501	MS3108A-24-28S	48
W-6	J-502	AN3108A-28-15SW	48
W-7	J-601	AN3106A-28-15S	144
W-8	J-7	MS3106A-2O-29SW	180
W-9	J-1451	AN3106A-28-15S	144
W-10	J-1452	MS3106A-28-12S	144
W-11	J-2901	MS3106A-24-28A	120
W-12	J-5501	MS3106A-2O-29S	48
W-13	J-5601	MS3106A-18-1S	144

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

3.4.4 Cables, Interconnecting and Test - The Interconnecting and Test Cables shall meet the following requirements:

3.4.4.1 Function - The Interconnecting Cables are to perform the connections to the individual units of the Radar Set AN/APN-59 or AN/APN-59A under test and the Test Cables permit removal of components or subassemblies for their test and service on the workbench.

3.4.4.2 Form Factor and Contents - The following table lists the Interconnecting and Test Cables as to function and contents.

Cable Designation	One End		Other End		Length in Inches
	Connect To	Connector	Connect To	Connector	
CX-3302/7J	J-3302		P-2702		60
W-14	J-609	UG-260B/U	J-2902	UG-260B/U	179
W-15	J-606	UG-260B/U	J-2902	UG-260B/U	179
W-16	J-608	UG-260B/U	J-105	UG-260B/U	179
W-17	J-605	UG-260B/U	J-103	UG-260B/U	179
W-18	J-2905	AN3106A-28-15P	Term BD	--	120
			P-2701	AN3101A-28-15S	60
W-19	J-2906	UG88C/U	P-2703	UG89B/U	60
W-20	J-2904	UG88C/U	P-2704	UG89B/U	60
TC-1	P-1201	MRE-20P *	J-1201	MRE-20S *	36
TC-2	J-175	MRE-7S *	P-175	MRE-7P *	36
TC-3	P-1301	MRE-18S *	J-1301	MRE-18P *	36
TC-4	P-1302	MRE-14S *	J-1302	MRE-14P *	36
TC-5	P-1303	MRE - 9S *	J-1303	MRE-9P *	36
TC-6	P-1304	M-7P *	J-119	M-7S *	36
TC-7	P-20B	MRE-34P *	J-208	MRE-34S *	36
TC-8	P-3001	MRE-20S *	J-3001	MRE-20P *	12
TC-9	P-3101	MRE-14S *	J-3101	MRE-14P *	12
TC-10	P-3201	MRE-14S *	J-3201	MRE-14P *	12
	P-1801	SMRE-26P *	J-1801	SMRE-26S *	36
TC-11	P-1601		J-1601		
	P-701		J-701		
TC-12	P-1101	SMRE-14P *	J-1101	SMRE-14S *	36
	P-801		J-801		
	P-901		J-901		
	P-2801		J-2801		
TC-13	P-1701	SMRE-29P *	J-1701	SMRE-1701 *	36
TC-14	J-407	M-9P *	P-407	M-9S *	12
	J-408		P-408		

* Winchester Type with hoods or an approved equivalent.

3.4.5 Aligning Tools and Covers - The Aligning Tools and Covers shall meet the following requirements.

3.4.5.1 Function - The Aligning Tools are supplied for service and adjustment of the Antenna AS-653/APN-59 under test. The two covers are for safety and protection of personnel and equipment when working on the RT-289/APN-59 with the covers removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

3.4.5.2 Contents - The Aligning Tools and Covers consist of the following list of items, and may be stored m the Navy Type 57A-53 Workbench drawers or in the bottom shelves on the right hand side of the bench.

Item	Mfgr. Model	
Alignment Tool (3)	Special	
Wrench (2)	Special	
Handle	Special	
Screwdriver (2)	Standard	
Protractor Level	Sterrett Co. Model 12	or an
Cross Level	Sterrett Co. Model 136	approved
Spring Scale	Chatillon Co. Type H34	equivalent
Cover (2)	Special	
Adapter, Wave Guide	Special	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Classification of Tests - Items covered by this specification shall be subjected to the following tests to determine compliance with all applicable requirements:

(1) Preproduction Tests

(2) Production Sample Tests

(3) Acceptance Tests

4.2 Preproduction Tests - Preproduction tests shall be made on an equipment representative of the production equipments to be supplied under the contract. Preproduction tests shall consist of the following:

(1) Contractor Demonstration Tests

(2) Service Approval Tests

4.2.1 Contractor Demonstration Tests - Contractor demonstration tests shall be accomplished under the responsibility of the contractor and shall be conducted in accordance with the approved test procedure of 4.5. The government inspector and the procuring activity shall be advised when tests are to be conducted so that a representative may be designated to witness or supervise the tests when so desired. Contractors not having adequate facilities to conduct all required tests shall obtain the services of a commercial testing laboratory.

4.2.1.1 Demonstration Test Data - The contractor shall submit all data collected in conducting these tests to the procuring agency for review and approval.

4.2.2 Service Approval Tests - At the completion of the contractor demonstration tests and when requested by the procuring activity, the equipment shall be delivered at the contractor's expense to a specified government laboratory for additional testing. This additional testing may consist of duplicating tests previously conducted and such other tests as are deemed necessary to determine compliance with all applicable design and performance requirements,

4.2.2.1 Accessory Material - In addition to the complete equipment submitted for service approval tests the contractor shall also submit the accessory material and design and test data specified in Specification MIL-T-21200. This reformation shall indicate the physical and electrical characteristics of the equipment and establish the equipment's compliance with applicable requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

4.2.3 Scope of Tests - Preproductlon tests shall include all tests deemed necessary by the procuring activity to determine that the equipment meets all the requirements of this specification and the contract. Preproduction tests shall include environmental tests in accordance with the procedures of Specification MI L-T- 5422, modifying the test limits of the applicable tests to correspond with the limits specified herein. Interference tests shall be conducted in accordance with Specification MIL-I-6181.

4.2.4 Preproduction Approval - Approval of the preproduction sample shall be by the procuring activity upon satisfactory completion of all tests. No production equipments shall be delivered prior to the approval of the preproduction sample. Prefabrication of production equipment prior to the approval of the preproduction sample is at the contractor's own risk, The approved preproduction sample will be returned to the contractor for his use in the fabrication and testing of equipment to be submitted for acceptance. The preproduction sample shall not be considered as one of the equipments under the contract; however, it may be reworked by the contractor and submitted for acceptance as a production equipment.

4.2.5 Production Equipments - Equipments supplied under the contract shall in all respects, including design, construction, workmanship, performance and quality, be equivalent to the approved preproduction sample. Each equipment shall be capable of successfully passing the same tests as imposed on the preproduction sample. Evidence of non- compliance with the above shall constitute cause for rejection and for equipment already accepted by the government it shall be the obligation of the contractor to make necessary corrections as approved by the procuring activity.

4.3 Production Sample Tests - When requested by the procuring activity, one equipment shall be selected from the first 10 production equipments submitted for acceptance and sent at the contractors expense to a designated government laboratory for tests. This equipment shall be selected by the government inspector after the equipment has successfully passed all individual tests. The preproduction sample shall not be selected for this test.

4. 3.1 Scope of Tests - This equipment may be subjected to any and all tests the procuring activity deems necessary to assure that the production equipment is equivalent to the previously approved preproduction sample in design, construction, workmanship, performance and quality and that it meets all applicable requirements.

4.3.2 Production Sample Approval - Approval of the production sample shall be by the procuring activity upon satisfactory completion of all tests. Any design, material or performance defect made evident during this test shall be corrected by the contractor to the satisfaction of the procuring activity. Failure of the production sample to pass any of the tests shall be cause for deliveries of equipment under the contract to cease until proper corrective action is approved and accomplished. Corrective action shall also be accomplished on equipment previously accepted when requested by the procuring activity.

4.3.3 Reconditioning of Production Test Sample - On completion of the production sample test the equipment shall be reworked by the contractor by replacing all wear or damaged items. After reworking the contractor shall resubmit the equipment for acceptance.

4.4 Acceptance Tests - The contractor shall furnish all samples and shall be responsible for accomplishing the acceptance tests. All inspection and testing shall be under the supervision of the government inspector. Contractors not having testing facilities satisfactory to the procuring activity shall engage the service of a commercial testing laboratory acceptable to the procuring activity. The contractor shall furnish test reports showing quantitative results for all acceptance tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

Such reports shall be signed by an authorized representative of the contractor or laboratory, as applicable. Acceptance or approval of material during the course of manufacture shall not be construed as a guarantee of the acceptance of the finished product. Acceptance tests shall consist of the following:

(1) Individual Tests

(2) Sampling Tests

(3) Special Tests

4.4.1 Individual Tests- Each equipment submitted for acceptance shall be subjected to the individual tests. These tests shall be adequate to determine compliance with the requirements of material, workmanship, operational adequacy and reliability. As a minimum, each equipment accepted shall have passed the following tests:

(1) Examination of Product

(2) Operational Test

(3) Manufacturing Run In Test

4.4.1.1 Examination of Product - Each equipment shall be examined carefully to determine that the material and workmanship requirements have been met.

4.4.1.2 Operational Test - Each equipment shall be operated long enough to permit the equipment temperature to stabilize and to check sufficient characteristics and record adequate data to assure satisfactory equipment operation.

4.4.1.3 Manufacturlng Run In Test - Each equipment shall be operated under the condition: specified herein for a period of 6 hours without failure. A failure shall be defined as anything which causes malfunctioning of the equipment. Only those adjustments will be permitted which can be made by using such controls and adjustments that are accessible to the operator during the normal use of the equipment,

Temperature	Ambient room
Humidity	Ambient room
Vibration	Any selected frequency within the range of 20 to 30 cps (excluding resonant points) and a minimum amplitude of ±3 g's

The equipment shall be vibrated (without vibration isolators) for a period of 10 minutes prior to the beginning of the 6-hour period of operation. Where feasible, the equipment shall be operated during this vibration period for the purpose of detecting flaws and imperfect workmanship. Operation within the specified limits of satisfactory performance is not necessarily required during the vibration period. The direction of vibration should be vertical to the normal mounting plane for 5 minutes and lateral to that plane for 5 minutes. Where it is not feasible to vibrate the equipment in 2 directions the vertical direction shall be used. During the 6-hour period of operation following the 10 minute vibration period, the equipment shall be mechanically cycled periodically through its various phases of operation. Should a failure occur, it should be repaired and the test started over, except that the 10- minute vibration period need not be repeated when it is certain the failure was not a result of the vibration. Should repetitive failures occur, corrective action shall be taken to eliminate this defect from future equipment. A record shall be kept of all failures. The 6-hour period specified above may be composed of two 3-hour periods to conform with standard working hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19 11:39Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling Tests - Equipments selected for sampling tests Shall first have passed the lndividual tests. Equipments shall be selected for sampling tests by the government inspector in accordance e with the following:

Quantity of Equipments Offered for Acceptance	Quantity to be Selected For Sampling Test
First 10	1
Next 50	1
Next 75	1
Next 100	1
	1 for each additional 200 or fraction thereof

4.4.2.1 Scope of Tests - As a minimum, each equipment selected for sampling tests shall be subjected to the following tests:

(1) Complete operational test at ambient room conditions, making all necessary measurements to assure that all applicable specification requirements have been met.

(2) Operational test at certain environmental conditions. The conditions may vary for each equipment tested and should be based on results of the preproduction and special tests.

4.4.3 Special Tests - Special tests shall be conducted on a quantity of equipments for the purpose of checking the effect of any design or material change on the performance of the equipment and to assure adequate quality control The equipment selected for special tests may be selected from equipments previously subjected to the sampling tests.

4.4.3.1 Special Test Schedule - Selection of equipments for special tests shall be made as follows. except that when a Production Sample is requested and delivered to a government laboratory for test (see 4. 3) the requirement for a special test on an early production equipment may be omitted.

(1) On an early production equipment,

(2) On an early equipment after an engineering change.

(3) Whenever failure reports or other information indicate additional equipments should be tested. (This will be determined by the procuring activity.)

4.4.3.2 Scope of Tests - Special tests shall consist of such tests as are approved by the procuring activity. Tests procedures previously approved for the preproduction and sampling tests shall be used where applicable. When not applicable, the contractor shall prepare a test procedure and submit it to the procuring activity for approval prior to conducting the tests As a minimum, the following tests shall be made, except that for those equipments selected as a result of design changes and failure reports, only those tests required to check the characteristics in question need be conducted.

(1) Temperature - Altitude Tests

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

(2) Vibration Test (commutes cycling in each of 3 planes)

(3) Humidity Tests

4.4.4 Equipment Failure - Should a failure occur during either the sampling or special tests, the following action shall be taken:

(1) Determine the cause of failure.

(2) Determine if the failure is an isolated case or design defect.

(3) Submit to the procuring activity for approval, proposed corrective action intended to reduce the possibility of the same failure(s) occurring in future tests.

(4) Where practical, include a test in the individual test to check all equipment for this requirement until reasonable assurance is obtained that the defect has been satisfactory corrected,

4.5 Test Procedures - The procedures used for conducting preproduction tests and acceptance tests shall be prepared by the contractor and submitted to the procuring activity for review and approval, The right is reserved by the procuring activity to modify-the tests or re quire any additional tests deemed necessary to determine compliance with the requirements of this specification or the contract, Specification MI L-T- 18303 shall be used as a guide for preparation of test procedures. When test procedures are available from previous contracts such procedures may be used when approved by the procuring activity.

4.6 Presubmission Testing - No item, part or complete equipment shall be submitted by the contractor until it has been previously tested and inspected by the contractor and found to comply, to the best of his knowledge and belief, with all applicable requirements

4.7 Rejection and Retest - Equipment which has been rejected may be reworked or have parts replaced to correct the defects and resubmitted for acceptance. Before resubmitting, full particulars concerning previous rejection and the action taken to correct the defects found in the original shall be furnished the government inspector.

5. PREPARATION FOR DELIVERY

5.1 General - All major units and parts of the equipment shall be preserved, packaged, packed and marked for the level of shipment specified in the contract or order in accordance with Specification MIL-E - 17555.

6. NOTES

6.1 Performance Objectives - Minimum size and weight, simplicity of operation, ease of maintenance, and an improvement in the performance and reliability of the specific functions beyond the requirements of this specification are objectives which shall be considered in the production of this equipment. Where it appears a substantial reduction in size and weight or improvement in simplicity of design performance, ease of maintenance or reliability will result from the use of materials, parts and processes other than those specified in Specification MIL-T-21200, it is desired their use be investigated. When investigation shows advantages can

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

be realized a request for approval shall be submitted to the procuring activity for consideration. Each request shall be accompanied by complete supporting information.

6.2 Precedence of Documents - When the requirements of the contract, this specification, or applicable subsidiary specifications are in conflict, the following precedence shall apply:

(1) Contract - The contract shall have precedence over any specification.

(2) This Specification - This specification shall have precedence over all applicable subsidiary specifications. Any deviation from this specification, or from subsidiary specifications where applicable, shall be specifically approved in writing by the procuring activity.

(3) Referenced Specifications - Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply to the extent specified.

6.3 Ordering Data - Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, number, and date of this specification,

(b) Selection of applicable levels of packaging and packing (see 5. 1).

6.4 The parentheses (*), when used in the type designation, may be replaced by either a number or letter furnished by the procuring activity upon application by the contractor for assignment of nomenclature in accordance with 3.2.5. The complete type number shall be used on nameplates, shipping records and instruction books, as appli cable.

NOTICE - When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications, or other data in not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

'ECIFICATION ANALYSIS SHEET
VWEPS FORM 4121/3 (8-62)

FORM APPROVED
BUDGET BUREAU NO 45-R309

INSTRUCTIONS

is sheet is to be filled out by Government or contractor rsonnel involved in the use of this specification in ocurement of products for ultimate use by the activity own on the reverse of this sheet.

is sheet is provided for obtaining information which ll aid the activity shown in insuring that through use of this specification suitable products can be procured with a minimum amount of delay and at the least cost.

Comments and the return of this sheet will be appreciated.

Fold on dotted lines on reverse side, staple in corner, and send to the activity shown.

EC FICATION *(No and abbrev title)*

GANIZATION	CITY	STATE

NTRACT NUMBER	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

ATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT		OR A SUBCONTRACT		

HAS ANY PART OF THIS SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
(If so, give paragraph number and wording, and recommendations for correcting the deficiencies.)

COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

IS THE SPECIFICATION RESTRICTIVE?
☐ YES ☐ NO IF YES IN WHAT WAY?

REMARKS *(Attach any pertinent data which may be of use in improving this specification. If additional papers are attached, send this form and papers in an envelope. This form is addressed for use in window envelope when appropriate.)*

BMITTED BY *(Print name and title)*	DATE
	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.

Fold

DEPARTMENT OF THE NAVY
BUREAU OF NAVAL WEAPONS
WASHINGTON 25, D.C.

OFFICIAL BUSINESS

POSTAGE AND FEES P
NAVY DEPARTMENT

Chief, Bureau of Naval Weapons (RREN-5)

Navy Department

Washington 25, D. C.

Fold

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:39Z
Check the source to verify that this is the current version before use.