INCH-POUND

MS27997P
10 December 2020
SUPERSEDING
MS27997N
27 November 2003

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 25 AMPERES, 3 PST N.O. TYPE I, HERMETICALLY SEALED

INACTIVE FOR NEW DESIGN AFTER 29 FEBRUARY 2000.
NO SUPERSEDING SPECIFICATION.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm
.010	0.25	.297	7.54	1.812	46.02
.031	0.79	.328	8.33	2.000	50.80
.047	1.19	.375	9.52	2.167	51.21
.063	1.60	.391	9.93	2.578	65.48
.079	2.01	.438	11.13	2.687	68.25
.138	3.51	.625	15.88	2.897	73.58
.140	3.56	.656	16.66	3.250	82.55
.190	4.83	.750	19.05	3.337	84.76
.210	5.33	.812	20.62	3.734	94.84
.218	5.54	1.156	29.36		

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.031 (0.79 mm).
4. Coil and auxiliary terminals may use additional washer for terminal seat.
5. Terminal covers and barriers may be required at power or auxiliary terminals.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Dash numbers and general characteristics: See table I.

Contact data:

Load ratings: See table II.

Maximum contact drop, initial: 0.150 V.

After life test: 0.175 V.

Overload current (NO): 200 amperes.

Rupture current (NO): 250 amperes.

Coil data: See table III.

Duty rating: Continuous.

RFI specification: MIL-STD-461 (applicable to coil circuits of ac operated relays).

Electrical data:

Minimum insulation resistance:

Initial: 100 megohms.

After life or environmental tests: 50 megohms.

Dielectric strength:

Sea level, 2 - 5 seconds:

	Initial		After life tests	
	28 V dc	115 V ac	28 V dc	115 V ac
Coil to case	1,250	1,500	1,000	1,125
Auxiliary contacts	1,250	1,500	1,000	1,125
All other points	1,250	1,800	1,000	1,350

Altitude, 1 minute:

	28 V dc	115 V ac
Coil to case	500	500
Auxiliary contacts	500	500
All other points	700	700

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.

Environmental characteristics:

Temperature range: -70°C to +125°C.

Maximum altitude rating: 80,000 feet.

Shock g level: 50 g's.

Duration: 6-9 ms.

Maximum duration contact opening: 2 ms.

Vibration (sinusoidal): See table IV.

Nonoperate:

G-level: 15 g's.

Frequency range curve: 20 to 2,000 Hz.

Acceleration: 15 g's.

Terminal strength (high temperature pull and torque test): Not applicable.

Qualification by similarity: See MIL-PRF-6106.

Group B and group C testing are not required. The manufacturer shall notify the qualifying activity in the event of any design or construction changes, and shall impose additional testing requirements as necessary.

Part or Identifying Number (PIN): MS27997- (plus applicable dash number from table I).

TABLE I. Dash numbers and general characteristics.

MS PIN-MS27997-	Type	Coil type	Terminal type	Mounting or mating socket	Auxiliary terminals	Max weight in pounds 1/
D1	I	dc	Stud	Flange	None	1.20
D2	I	dc	Stud	Flange	Yes	1.25
A1	I	ac	Stud	Flange	None	1.25
A2	I	ac	Stud	Flange	Yes	1.30

1/ Weights include covers and barriers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.

TABLE II. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/				See appropriate notes
		Main		Aux		Main		Aux		Main		Aux		
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	
Resistive	50	25		5	5	25		5		25				
Inductive	10	25		5	5	25		5		25				
Motor	50	25				25				25				
Lamp	50			1	1			1						
Transfer, load														2/
Mechanical life reduced current	100	6.3		1.25	1.25	6.3		1.25		6.3				
Mixed loads	50	Applicable according to MIL-PRF-6106												

1/ Absence of value indicates relay is not rated for 3 phase applications.
2/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

TABLE III. Operating characteristics.

PIN MS 27997-	Coil data											Time - (milliseconds maximum)					
	Coil	Rated			Max		Max pick-up voltage			Hold voltage 2/	Drop out voltage 2/	Operate 3/	Release 4/	Contact Bounce 3/			
														Main		Aux	
		Volts 1/	Freq Hz	Res Ω ±10%	Volts	Amp	Normal 2/	High Temp test	Cont current test					NO	NC	NO	NC
D1	X1,X2	28	dc	51	29	.6	18	21	22.5	7.0	1.5	25	10	2			
D2	X1,X2	28	dc	51	29	.6	18	21	22.5	7.0	1.5	25	10	2		4	4
A1	X1,X2	115	60/ 400	N/A	124	.2	90	100	104	40	10	30	50	2			
A2	X1,X2	115	60/ 400	N/A	124	.2	90	100	104	40	10	30	50	2		4	4

1/ CAUTION: Use of any coil voltage less than rated coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With rated coil voltage.
4/ From rated coil voltage.

TABLE IV. Vibration levels (sinusoidal).

PIN MS27997-	Frequency			
	5-10 Hz	10-55 Hz	55-750 Hz	750-1500 Hz
D1	.08 DA	.06 DA	15 g's	12 g's
D2	.08 DA	.06 DA	10 g's	10 g's
A1	.08 DA	.06 DA	15 g's	12 g's
A2	.08 DA	.06 DA	10 g's	10 g's

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-PRF-6106, this document references the following:
MS27243 MIL-STD-461

Custodians:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2020-065)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.