
FED. SUP CLASS
5305



NOMINAL SIZE	D		2 (.086)	4 (.112)	6 (.138)	8 (.164)
THREADS PER INCH			56NC	40NC	32NC	32NC
BODY DIAMETER	D_e	Max	.0860	.1120	.1380	.1640
		Min	.0717	.0925	.1141	.1399
HEAD DIAMETER	A	Max	.167	.219	.270	.322
		Min	.155	.205	.256	.306
HEAD HEIGHT	H	Max	.053	.068	.082	.096
		Min	.045	.058	.072	.085
SLOT WIDTH	J	Max	.031	.039	.048	.054
		Min	.023	.031	.039	.045
SLOT DEPTH	T	Max	.033	.041	.050	.058
		Min	.023	.030	.038	.043
RADIUS ON HEAD	R_1	Nom	.035	.042	.046	.052
RADIUS UNDER HEAD	R	Max	.013	.018	.023	.023

LENGTH	L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE HEAD, OR CLOSER IF PRACTICABLE.	1/8	+0 -1/32	1	11	24	39
	3/16		2	12	25	40
	1/4		3	13	26	41
	5/16		4	14	27	42
	3/8		5	15	28	43
	7/16		6	16	29	44
	1/2		7	17	30	45
	5/8		8	18	31	46
	3/4		9	19	32	47
	7/8		10	20	33	48
	1			21	34	49
	1-1/4	+0 -1/16		22	35	50
	1-1/2			23	36	51
	1-3/4				37	52
	2				38	53
Minimum Complete Thread Length of 1-3/4.	2-1/4			Ⓐ CANCELLED SEE SHEET 2		54
	2-1/2	+0 -3/32				55
	2-3/4					56
	3					57

MATERIAL: Carbon Steel, Specification QQ-W-409 or QQ-S-633, except Bessemer compositions; 55,000 PSI minimum ultimate tensile strength.

FINISH: Plain (untreated).

THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services Handbook H-28.

NOTES: (1) Referenced documents of issue in effect on date of invitation for bids shall apply.
(2) In case of conflict with any referenced document, this standard will govern.
(3) The MS part number consists of the MS sheet number, plus the dash number. Example: MS 35221-1.
(4) All dimensions in inches.

Ⓐ For changes, see sheets 1 and 2.

APPROVED FEB 9, 1954 REVISED Ⓐ 15 JUN 1962

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	Ord
Other Cust	Ships

TITLE: SCREW, MACHINE, PAN HEAD, SLOTTED, CARBON STEEL, PLAIN FINISH, NC-2A AND UNC-2A

MILITARY STANDARD

MS 35221

PROCUREMENT SPECIFICATION	SUPERSEDES:	SHEET 1 OF 2
FF-S-92		

DD FORM 1 SEP 57 672-1 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:11Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5305

NOMINAL SIZE		D		10 (.190)	1/4	5/16	3/8
THREADS PER INCH				24NC	20UNC	18UNC	16UNC
BODY DIAMETER		D_e	Max	.1900	.2500	.3125	.3750
			Min	.1586	.2127	.2712	.3287
HEAD DIAMETER		A	Max	.373	.492	.615	.740
			Min	.357	.473	.594	.716
HEAD HEIGHT		H	Max	.110	.144	.178	.212
			Min	.099	.130	.162	.195
SLOT WIDTH		J	Max	.060	.075	.084	.094
			Min	.050	.064	.072	.081
SLOT DEPTH		T	Max	.067	.087	.109	.130
			Min	.050	.070	.092	.113
RADIUS ON HEAD		R_1	Nom	.061	.087	.099	.143
RADIUS UNDER HEAD		R	Max	.031	.025	.027	.031
LENGTH		L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD, OR CLOSER IF PRACTICABLE.		1/8				Ⓐ CANCELLED SEE NOTE	
		3/16		58			
		1/4		59			
		5/16		60	76		
		3/8	+0 -1/32	61	77	92	
		7/16		62	78	93	
		1/2		63	79	94	107
		5/8		64	80	95	108
		3/4		65	81	96	109
		7/8		66	82	97	110
		1		67	83	98	111
		1-1/4	+0 -1/16	68	84	99	112
		1-1/2		69	85	100	113
		1-3/4		70	86	101	114
		2		71	87	102	115
Minimum Complete Thread Length of 1-3/4.		2-1/4	+0 -3/32	72	88	103	116
		2-1/2		73	89	104	117
		2-3/4		74	90	105	118
		3		75	91	106	119

NOTE: For illustration, material, finish, and other pertinent data, see sheet 1.

Ⓐ CANCELLED AFTER 15 JUN 1962. USE MS 35206. INTERCHANGEABILITY RELATIONSHIP - MS35206 can replace the cancelled screws of the same size. The cancelled MS35221 cannot always replace MS35206 and should be used until existing stock is depleted. Then use only the superseding MS screws of the same size for design and replacement.

APPROVED FEB 9, 1954 REVISED Ⓐ FOR CHANGES SEE SHEETS 1 AND 2.

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

C.A. Ord Other Cust Ships	TITLE SCREW, MACHINE, PAN HEAD, SLOTTED, CARBON STEEL, PLAIN FINISH, NC-2A AND UNC-2A	MILITARY STANDARD MS 35221	
PROCUREMENT SPECIFICATION FF-S-92	SUPERSEDES:	SHEET 2 OF	

DD FORM SEP 57 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:11Z
Check the source to verify that this is the current version before use.