A-A-744
August 20, 1980

COMMERCIAL ITEM DESCRIPTION

MOWER, LAWN, ROTARY, WALK BEHIND (HAND PROPELLED WITH BLADE STOP)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers rotary type, hand-propelled, walk behind, 4 cycle, recoil starter, gasoline powered, safe lawn mower intended for light or intermediate use on improved lawns.

Salient characteristics:

Power requirements:

Class A - 3-1 /3 rated horsepower
Class B - 4 rated horsepower
Class C - 5 rated horsepower

Cutting swath in inches (nominal):

Size 1 - 18 inches
Size 2 - 20 inches
Size 3 - 21 inches
Size 4 - 22 inches

Mininmum acceptable blade tip speed at full throttle - 250 feet per second (i 70.5 mph).

The engine rated horsepower specifier-i shall be maximum engine power rated at 3600 rpm per SAE J-607 procedure. The Maximum operating speed may be lower than 3600 rpm.

The mowers shall be equipped with a blade stopping device that meets all applicable requirements as set forth in the Federal Register, Volume 44, Number 33, dated February 15, 1979, Part 1205 - Safety Standards for Walk-Behind Power Lawn Mowers.

The sound level shall not exceed 86dB(A) at the operator's ear when measured in accordance with SAE 2-1174 procedure.

The wheels shall nave a quick lift height adjuster not requiring the use of tools for adjustment and with a minimum range of 2 inches adjustable to a mininmum of 3 cutting heights.

The handle shall be adjustable to a minimum of 3 positions. Ail operator's controls shall be conveniently located for ease of operations from the operator's position. All controls shall be positive in action and remain fixed in set position.

The mower shall withstand dropping 10 times from a height of 15 inches onto a concrete floor and landing essentially on all wheels. Wheel alignment shall be measured before and after to assure no permanent deformation has occurred. The blade height inside the housing to the lower edge of the housing shall be measured before and after. No more than 1/8 inch deformation shall have occurred to the deck as measured at any point around the blades circumference. Acccptance shall require that none of the component parts shall fracture, break, loosen, or deform in a manner that would adversely affect performance or would constitute a hazard to the operator.

The fuel tank shall have a mininmum capacity of 1 quart or larger if specified.

The mower handle while attached to the mower and the mower restrained shall withstand 120 foot pounds of torque applied at the operator's end of the handle. The torque small be applied five times clockwise and five times counter-clockwise in sequence. The component parts shall not break, or deform in a manner that would adversely affect performance or constitute a hazard to the operator.

The wheels shall be metal or linear polyethylene construction with semi-pneumatic rubber tires. Minimum diameter of both front and rear wheels shall be 6 inches.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:10Z
Check the source to verify that this is the current version before use.

The mower shall have either an Outdoor Power Equipment Institute (OPEI) label or meet all applicable requirements of ANSI-B71.1 Safety Specifications for Power Lawn Mowers, Lawn and Garden Tractors, and Lawn Tractors, latest revisions, when tested by an independent testing laboratory acceptable to the Government.

Where referenced requirements are in conflict with this commercial item description, the requirements herein specified shall govern.

Workmanship. The mower shall be free from defects such as fractures, splits, punctures, dents, rust deterioration or malformations, sharp edges, burrs and slivers. Finish shall consist of a durable rust-proof, weather proof coating of lacquer, enamel or equal.

The issues of ANSI and SAE Standards in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The packaging and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

ANSI Sandards are available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

SAE Standards are available from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.