
DETAIL SPECIFICATION SHEET

CONNECTOR, FEMALE PLUG ELECTRICAL, RECTANGLAR,
POLARIZED SHELL, MINIATURE TYPE, SOCKET CONTACTS
(STYLE 023A)

This specification is approved for use by all Departments and agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-21617.



23 SIZE 20 CONTACTS

FIGURE 1. Type P, class F inserts containing socket contacts.

DISTRIBUTION STATEMENT A. Approved for public release; distribution if unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.005	0.13	.135	3.43	.546	13.87
.010	0.25	.225	5.72	.750	19.05
.015	0.38	.234	5.94	.984	25.00
.076	1.93	.245	6.22	1.125	28.58
.078	1.98	.291	7.39	1.610	40.89
.120	3.05	.390	9.91	2.062	52.37
.128	3.25	.525	13.34	2.312	58.72

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 1. Type P, class F inserts containing socket contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.



Dimension	Contact size
	20 (mm)
A (mm)	.400 ±.025 (10.16 ±0.63)
B (mm)	057 ±.025 (1.45 ±0.63)

Inches	mm	Inches	mm
.005	0.13	.125	3.18
.010	0.25	.156	3.96
.015	0.38	.750	19.06
.020	0.51	1.010	25.65
.025	0.64	1.067	27.10
.035	0.89	1.693	43.00
.120	3.05		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 2. Type P, class F large flange female receptacles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2.


Reference material: See MIL-DTL-21617.

Service rating: Contacts 1 through 14 service rating A, contacts 15 through 23 service rating D (see MIL-DTL-21617).

Mating connector: See MIL-DTL-21617/14 and /15.

Contacts: Contacts shall be in accordance with MIL-DTL-21617.

Part or Identifying Number (PIN): PIN example as follows:



Type: P - Plug.
Class: F - Female, insert containing socket contacts.
Style: 023A - Contacts size 20.

Supersession data: Old PIN PF023A.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
DLA – CC

Review activities:
Army - AV, MI

Preparing activity:
DLA - CC

(Project 5935-4335-013)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.