DETAIL SPECIFICATION SHEET

CONNECTOR, MALE RECEPTACLE ELECTRICAL, RECTANGLAR, POLARIZED SHELL, MINIATURE TYPE, PIN CONTACTS (STYLE 023A)

This specification is approved for use by all Departments and agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-21617.




FIGURE 1. Type J, class M inserts containing pin contacts.

DISTRIBUTION STATEMENT A. Approved for public release; distribution if unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.005	0.13	.188	4.78	.546	13.87
.015	0.38	.225	5.72	.750	19.05
.076	1.93	.234	5.94	1.000	25.40
.078	1.98	.245	6.22	1.125	28.58
.120	3.05	.291	7.39	1.625	41.28
.128	3.25	.390	9.91	1.750	44.45
.136	3.45	.525	13.34	2.062	52.37
				2.312	58.72


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 1. Type J, class M inserts containing pin contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.



SECTION A-A



REAR VIEW

Dimension	Contact size
	20 (mm)
A (mm)	.400 ±.025 (10.16 ±0.63)
B (mm)	057 ±.025 (1.45 ±0.63)

Inches	mm	Inches	mm
.010	0.25	.156	3.96
.015	0.38	.188	4.78
.016	0.41	.344	8.74
.020	0.51	.700	17.78
.025	0.64	1.135	28.83
.045	1.14	1.693	43.00
.094	2.39	1.750	44.45

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 2. Type J, class M large flange male receptacles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2.


Reference material: See MIL-DTL-21617.

Service rating: Contacts 1 through 14 service rating A, contacts 15 through 23 service rating D, (see MIL-DTL-21617).

Mating connector: See MIL-DTL-21617/13.

Contacts: Contacts shall be in accordance with MIL-DTL-21617.

Part or Identifying Number (PIN): PIN example as follows:



Type: J - Receptacle.
Class: M - Male, inserts containing pin contacts.
Style: 023A - Contacts size 20.

Supersession data: Old PIN JM023A.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
DLA – CC

Preparing activity:
DLA - CC

(Project 5935-4335-014)

Review activities:
Army - AV, MI

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:07Z
Check the source to verify that this is the current version before use.