
DETAIL SPECIFICATION SHEET

CONNECTOR, MALE RECEPTACLE ELECTRICAL, RECTANGLAR,
POLARIZED SHELL, MINIATURE TYPE, PIN CONTACTS
(STYLE 040A)

This specification is approved for use by all Departments and agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-21617.



CONTACTS 40 SIZE 20

FIGURE 1. Type J, class M inserts containing pin contacts.

DISTRIBUTION STATEMENT A. Approved for public release; distribution if unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:08Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.13	.156	3.96	.391	9.93	1.000	25.40
.015	0.38	.188	4.78	.468	11.89	1.125	28.58
.078	1.98	.234	5.94	.547	13.89	1.625	41.28
.120	3.05	.292	7.42	.625	15.88	1.750	44.45
.136	3.45	.312	7.92	.750	19.05	2.062	52.37
						2.312	58.72


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 1. Type J, class M inserts containing pin contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:08Z
Check the source to verify that this is the current version before use.



SECTION A-A



REAR VIEW

Dimension	Contact size
	20 (mm)
A (mm)	.400 ±.025 (10.16 ±0.65)
B (mm)	057 ±.025 (1.45 ±0.63)

Inches	mm	Inches	mm
.010	0.25	.156	3.96
.015	0.38	.188	4.78
.016	0.41	.344	8.74
.020	0.51	.700	17.78
.025	0.64	1.135	28.83
.045	1.14	1.693	43.00
.094	2.39	1.750	44.45

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).

FIGURE 2. Type J, class M large flange male receptacles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2.


Reference material: See MIL-DTL-21617.

Service rating: A (see MIL-DTL-21617).

Mating connector: See MIL-DTL-21617/22.

Contacts: Contacts shall be in accordance with MIL-DTL-21617.

Part or Identifying Number (PIN): PIN example as follows:



Type: J - Receptacle.
Class: M- Male, inserts containing pin contacts.
Style: 040A - Contacts 40 size 20.

Supersession data: Old PIN JM040A.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
DLA – CC

Review activities:
Army - AV, MI

Preparing activity:
DLA - CC

(Project 5935-4335-023)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:08Z
Check the source to verify that this is the current version before use.