

NOM DIA	A DIA		B MIN	HARDNESS ROCKWELL 15-N	HARDNESS VICKERS 10KG LOAD	RECOMMENDED DRILL HOLE DIA +.005 -.002
1/32	.030	+.000 -.003	.032	65 TO 70	200 TO 300	.035
3/64	.048		.047			.062
1/16	.061		.063			.067
5/64	.076	+.000 -.004	.078	60 TO 70	170 TO 245	.094
3/32	.090		.094			.096
1/8	.122		.125	55 TO 67	140 TO 220	.129
5/32	.150		.156			.161
3/16	.176		.188			.188
7/32	.207	+.000 -.005	.219			.219
1/4	.225		.250			.238
5/16	.280		.313			.295

LENGTH L	DASH NUMBERS 1/32	3/64	1/16	5/64	3/32	1/8	5/32	3/16	7/32	1/4	5/16
.313		15-5	2-5								
.375	1-6	15-6	2-6								
.438		15-7	2-7								
.500	1-8	15-8	2-8	25-8	3-8	4-8	5-8				
.625		15-10	2-10	25-10	3-10						
.750	1-12	15-12	2-12	25-12	3-12	4-12	5-12				
.875		15-14	2-14	25-14	3-14	4-14					
1.000	1-16	15-16	2-16	25-16	3-16	4-16	5-16				
1.125				25-18	3-18	4-18	5-18				
1.250		15-20	2-20	25-20	3-20	4-20	5-20				
1.375				25-22	3-22	4-22	5-22				
1.500		15-24	2-24	25-24	3-24	4-24	5-24	6-24			
1.625				25-26	3-26	4-26	5-26	6-26			
1.750		15-28	2-28	25-28	3-28	4-28	5-28	6-28			
2.000		15-32	2-32	25-32	3-32	4-32	5-32	6-32	7-32	8-32	10-32
2.250						4-36	5-36	6-36	7-36	8-36	10-36
2.500							5-40	6-40	7-40	8-40	10-40
3.000								6-48		8-48	
3.500										8-56	
4.000										8-64	

PRONG OF PIN SHALL WITHSTAND BENDING FLAT ON ITSELF WITHOUT CRACKING. FLAT OF PRONG SHALL FORM OUTSIDE OF BEND.

MATERIAL: CORROSION-RESISTANT STEEL (TYPE C AS SPECIFIED IN PROCUREMENT SPECIFICATION).

FINISH: PASSIVATE AFTER PICKLING.

EXAMPLE OF PART NO: AN381-2-10 = 1/16 (2/32) NOM DIA COTTER PIN, .625 IN LENGTH.
AN381-25-10 = 5/64 (2.5/32) NOM DIA COTTER PIN, .625 IN LENGTH.

COTTER PINS SHALL BE FREE FROM BURRS.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.010.

INACTIVE FOR DESIGN AFTER 1 MARCH 1961. USE MS24665.

AN381 AND MS24665 CORROSION RESISTANT STEEL PINS OF THE SAME NOMINAL DIAMETER AND BASIC LENGTH ARE UNIVERSALLY, FUNCTIONALLY AND DIMENSIONALLY INTERCHANGEABLE.

④CANCELED AFTER 1 AUGUST 1968.

APPROVED 10 Oct 45 REVISED (1) 13 Mar 47 (2) 18 May 56 (3) 1 Mar 61 (4) 1 Aug 68

PROCUREMENT SPECIFICATION	AIR FORCE-NAVY AERONAUTICAL STANDARD	AN381
FF-P-386	PIN, COTTER (CORROSION-RESISTANT STEEL)	

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTE: This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new designs, not later than 6 months after the latest date of approval shown.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-510/A-565

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:15Z
Check the source to verify that this is the current version before use.