NOTICE OF CANCELLATION

INCH-POUND

AN815 REV 9
NOTICE 2
21 January 2009
SUPERSEDING
NOTICE 1
28 September 1999

AIR FORCE/NAVY AERONAUTICAL STANDARD

UNION – FLARED TUBE

AN815 REV 9, dated 04 August 1983, is hereby canceled. Future acquisitions for this item should refer to SAE-AS5174, "Fitting, Union and Reducer, Flared."

(Copies of these documents are available online at http://www.sae.org or from the SAE World Headquarters, 400 Commonwealth Drive, Warrendale, PA 15096-0001.)

Reason for NOTICE 2: SAE inactivated Part or Identifying Numbers (PIN) with material code letter D for replacement parts and for new design to use code letter W. This is because code letter W is stronger in tensile strength than code letter D. This is based on the previous PA's revision, as a result of lessons learned. Plus to add back material code letter S for replacement parts and for new design to use code letter R. The code letter R is better for applications requiring higher temperature.

Table I provides a detailed supersession cross-reference of cancelled AN815 REV 9 PINs and replacement SAE-AS5174 PINs.

CAUTION: The supersession information is valid as of the date of this notice and may be superseded by subsequent revisions of the superseding document.

CONCLUDING MATERIAL

Custodians:
Army – AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2008-082)

Review activities:
Army – AR, CR4, MI
Navy – MC, SA
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:16Z
Check the source to verify that this is the current version before use.

TABLE I. AN815 REV 9 to SAE-AS5174, cross-reference data.

Cancelled Tube AN PIN	Size	Replacement AS PIN		Cancelled Tube AN PIN	Size	Replacement AS PIN	
AN815-2	.125	AS5174-0202		AN815-8	.500	AS5174-0808	
AN815-2D	.125	AS5174D0202	1/	AN815-8D	.500	AS5174D0808	1/
AN815-2D	.125	AS5174W0202	2/	AN815-8D	.500	AS5174W0808	2/
AN815-2J	.125	AS5174J0202		AN815-8J	.500	AS5174J0808	
AN815-2K	.125	AS5174K0202		AN815-8K	.500	AS5174K0808	
AN815-2S	.125	AS5174S0202	3/	AN815-8S	.500	AS5174S0808	3/
AN815-2S	.125	AS5174R0202	4/	AN815-8S	.500	AS5174R0808	4/
AN815-2T	.125	AS5174T0202		AN815-8T	.500	AS5174T0808	
AN815-2W	.125	AS5174W0202		AN815-8W	.500	AS5174W0808	
AN815-3	.188	AS5174-0303		AN815-10	.625	AS5174-1010	
AN815-3D	.188	AS5174D0303	1/	AN815-10D	.625	AS5174D1010	1/
AN815-3D	.188	AS5174W0303	2/	AN815-10D	.625	AS5174W1010	2/
AN815-3J	.188	AS5174J0303		AN815-10J	.625	AS5174J1010	
AN815-3K	.188	AS5174K0303		AN815-10K	.625	AS5174K1010	
AN815-3S	.188	AS5174S0303	3/	AN815-10S	.625	AS5174S1010	3/
AN815-3S	.188	AS5174R0303	4/	AN815-10S	.625	AS5174R1010	4/
AN815-3T	.188	AS5174T0303		AN815-10T	.625	AS5174T1010	
AN815-3W	.188	AS5174W0303		AN815-10W	.625	AS5174W1010	
AN815-4	.250	AS5174-0404		AN815-12	.750	AS5174-1212	
AN815-4D	.250	AS5174D0404	1/	AN815-12D	.750	AS5174D1212	1/
AN815-4D	.250	AS5174W0404	2/	AN815-12D	.750	AS5174W1212	2/
AN815-4J	.250	AS5174J0404		AN815-12J	.750	AS5174J1212	
AN815-4K	.250	AS5174K0404		AN815-12K	.750	AS5174K1212	
AN815-4S	.250	AS5174S0404	3/	AN815-12S	.750	AS5174S1212	3/
AN815-3S	.188	AS5174R0303	4/	AN815-10S	.625	AS5174R1010	4/
AN815-4T	.250	AS5174T0404		AN815-12T	.750	AS5174T1212	
AN815-4W	.250	AS5174W0404		AN815-12W	.750	AS5174W1212	
AN815-5	.312	AS5174-0505		AN815-16	1.000	AS5174-1616	
AN815-5D	.312	AS5174D0505	1/	AN815-16D	1.000	AS5174D1616	1/
AN815-5D	.312	AS5174W0505	2/	AN815-16D	1.000	AS5174W1616	2/
AN815-5J	.312	AS5174J0505		AN815-16J	1.000	AS5174J1616	
AN815-5K	.312	AS5174K0505		AN815-16K	1.000	AS5174K1616	
AN815-5S	.312	AS5174S0505	3/	AN815-16S	1.000	AS5174S1616	3/
AN815-5S	.312	AS5174R0505	4/	AN815-16S	1.000	AS5174R1616	4/
AN815-5T	.312	AS5174T0505		AN815-16T	1.000	AS5174T1616	
AN815-5W	.312	AS5174W0505		AN815-16W	1.000	AS5174W1616	
AN815-6	.375	AS5174-0606		AN815-20	1.250	AS5174-2020	
AN815-6D	.375	AS5174D0606	1/	AN815-20D	1.250	AS5174D2020	1/
AN815-6D	.375	AS5174W0606	2/	AN815-20D	1.250	AS5174W2020	2/
AN815-6J	.375	AS5174J0606		AN815-20J	1.250	AS5174J2020	

See notes at end of tables

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:16Z
Check the source to verify that this is the current version before use.

TABLE I. AN815 REV 9 to SAE-AS5174, cross-reference data – Continued.

Cancelled Tube AN PIN Size	Replacement AS PIN	
AN815-6K .375	AS5174K0606	
AN815-6S .375	AS5174S0606	3/
AN815-6S .375	AS5174R0606	4/
AN815-6T .375	AS5174T0606	
AN815-6W .375	AS5174W0606	
AN815-24 1.500	AS5174-2424	
AN815-24D 1.500	AS5174D2424	1/
AN815-24D 1.500	AS5174W2424	2/
AN815-24J 1.500	AS5174J2424	
AN815-24K 1.500	AS5174K2424	
AN815-24S 1.500	AS5174R2424	3/
AN815-24S 1.500	AS5174S2424	4/
AN815-24T 1.500	AS5174T2424	
AN815-24W 1.500	AS5174W2424	
AN815-28 1.750	AS5174-2828	
AN815-28D 1.750	AS5174D2828	1/
AN815-28D 1.750	AS5174W2828	2/
AN815-28J 1.750	AS5174J2828	
AN815-28K 1.750	AS5174K2828	
AN815-28S 1.750	AS5174S2828	3/
AN815-28S 1.750	AS5174R2828	4/
AN815-28T 1.750	AS5174T2828	
AN815-28W 1.750	AS5174W2828	
AN815-32 2.000	AS5174-3232	
AN815-32D 2.000	AS5174D3232	1/
AN815-32D 2.000	AS5174W3232	2/
AN815-32J 2.000	AS5174J3232	
AN815-32K 2.000	AS5174K3232	
AN815-32S 2.000	AS5174S3232	3/
AN815-32S 2.000	AS5174R3232	4/
AN815-32T 2.000	AS5174T3232	
AN815-32W 2.000	AS5174W3232	

Cancelled AN PIN	Tube Size	Replacement AS PIN	
AN815-20K	1.250	AS5174K2020	
AN815-20S	1.250	AS5174S2020	3/
AN815-20S	1.250	AS5174R2020	4/
AN815-20T	1.250	AS5174T2020	
AN815-20W	1.250	AS5174W2020	
AN815-40	2.500	AS5174-4040	
AN815-40D	2.500	AS5174D4040	1/
AN815-40D	2.500	AS5174W4040	2/
AN815-40J	2.500	AS5174J4040	
AN815-40K	2.500	AS5174K4040	
AN815-40S	2.500	AS5174R4040	3/
AN815-40S	2.500	AS5174S4040	4/
AN815-40T	2.500	AS5174T4040	
AN815-40W	2.500	AS5174W4040	
AN815-48	3.000	AS5174-4848	
AN815-48D	3.000	AS5174D4848	1/
AN815-48D	3.000	AS5174W4848	2/
AN815-48J	3.000	AS5174J4848	
AN815-48K	3.000	AS5174K4848	
AN815-48S	3.000	AS5174S4848	3/
AN815-48S	3.000	AS5174R4848	4/
AN815-48T	3.000	AS5174T4848	
AN815-48W	3.000	AS5174W4848	

1/ For replacements parts, use code letter “D”. Reason: SAE-G3 and DoD liaisons agreed to use code “D” for replacement PINs.
2/ For new design parts, use code letter “W” . Reason: SAE-G3 and DoD liaisons agreed to use code “W” for new design.
3/ For replacement parts: Use code letter “S”. Reason: SAE-G3 and DoD liaisons agreed to use code “S” for replacement PINs.
4/ For new design parts. Use code letter “R”. Reason: SAE-G3 and DoD liaisons agreed to use code “R” for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:16Z
Check the source to verify that this is the current version before use.