MILITARY SPECIFICATION

CYLINDERS, STEEL, COMPRESSED GAS, NONSHATTERABLE

This amendment forms a part of Military Specification MIL-C-7905F, dated 23 July 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, add the following to the list of classes:

"Class 1 - 1,800 psi (12,400 kPa) (rated pressure), seamless construction

Class 3 - 1,800 psi (12,400 kPa) (rated pressure), welded construction"

PAGE 3

Add the following new paragraph:

"2.1.2 Other Government documents and drawings. The following other Government documents and drawings form a part of this specification to the extent specified herein.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

1684AS100 Cylinder, Oxygen, Nonshatterable, Welded (1,800 psi)"

PAGE 4

3.3, line 1: Delete "Class 2" and substitute "Classes 1 and 2".

3.5, line 2: After "MS90389", add "or Drawing 1684AS100".
line 3: Delete "Class 2" and substitute "Classes 1 and 2".
line 4: Delete "Class 4" and substitute "Classes 3 and 4".

PAGE 5

3.6.4, delete and substitute the following:

"3.6.4 Burst pressure. When tested as specified in 4.7.5, classes 1 and 3 cylinders shall not burst at a pressure less than 4,000 psi (27,580 kPa), and classes 2 and 4 cylinders shall not burst at a pressure less than 4,500 psi (31,030 kPa). Failure of all classes of cylinders shall occur in a ductile manner."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.

PAGE 6

3.6.11, line 1: Delete "(class 4)" and substitute "(classes 3 and 4)".

3.7, line 2: After "MS90389", add "or Drawing 1684AS100".

3.9, line 2: After "MS90389", add "or Drawing 1684AS100".

3.10, line 6: After "MS90389", add "or Drawing 1684AS100".
line 8: After "MS90389", add "or Drawing 1684AS100".

PAGE 7

3.11.1, line 2: Delete "class 2" and substitute "classes 1 and 2".
line 3: Delete "class 4" and substitute "classes 3 and 4".
lines 4 & 5: Delete last sentence and substitute "Cylinder markings shall be at least 1/4 inch high and shall consist of the following:".
item b: Delete "MS".

3.11.2b, delete and substitute the following:

"b. Cylinders specified for aviator's breathing oxygen or compressed air shall be stenciled with the service pressure in psi and kPa in two places diametrically opposite of each other."

PAGE 8

4.3.1e, line 2: Delete "class 2" and substitute "classes 1 and 2".

PAGE 10

4.7.1.1.1, line 2: After "MS90389", add "or Drawing 1684AS100".

PAGE 13

4.7.10.2f, item (1): After "through -5", add "and Drawing 1684AS100"

4.7.12, line 1: Delete "class 4" and substitute "classes 3 and 4" (two places).

PAGE 15

6.2.1, add the following:

"h. Applicable Qualified Products List (QPL)."

6.2.1b, delete "MS".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.

PAGE 17

TABLE I, physical properties inspection: Delete "(class 4)" and substitute "(classes 3 and 4)".

PAGE 18

TABLE III, leakage test: Delete "class 2" and substitute "classes 1 and 2".
Delete "class 4" and substitute "classes 3 and 4".

Custodians:
Army - AV
Air Force - 99

Review activities:
Air Force - 11 and 71

Preparing activity:
Navy - AS
(Project 1660-0535)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:35Z
Check the source to verify that this is the current version before use.